



GILLIAM COUNTY WEIGHT RESTRICTED BRIDGES AND APPROVED ROUTE LIST ATTACHMENT C11 (REVISED 01-2002)

Gilliam County Weight Restricted Bridges

Highway	Crossing	Approximate Location	Mile Point	Tandem Axle	3 axle group within 20 feet not uniform in weight	3 axle group within 20 feet uniform in weight	4 axle group within 20 feet not uniform in weight	4 axle group within 20 feet uniform in weight
No Weight Restricted Bridges On The Approved Gilliam County Routes								

GILLIAM COUNTY PILOT VEHICLE REQUIREMENTS

WIDTH	FRONT PILOTS REQUIRED	REAR PILOTS REQUIRED
WIDTH 08'07" TO 09'00"	ONE	ONE
WIDTH 09'01" TO 10'00"	ONE	ONE
WIDTH 10'01" TO 11'00"	ONE	ONE
WIDTH 11'01" TO 12'00"	ONE	ONE
WIDTH 12'01" TO 14'00"	ONE	ONE

Gilliam County Approved Route List

Truck-Tractor Semitrailer Combinations may operate at a maximum of 60 feet in overall length on all county highways except those listed below.

- Log and Stinger steered Pole Trailer Combinations are allowed 65 feet in overall length on all county highways.
- The maximum length of a semitrailer in a truck tractor semitrailer combination is 53 feet.
- The maximum length of a semitrailer in a truck tractor semitrailer trailer combination (doubles) is 40 feet. The distance measured from the front trailer to the rear trailer cannot exceed 68 feet.

Truck-Tractor Semitrailer Combinations may operate at a maximum of 75 feet in overall length the county highways listed below.		
Double Trailer Combinations may operate at a maximum of 95 feet in overall length on the county highways listed below.		
Truck & Trailer Combinations may operate at a maximum of 75 feet in overall length on the county highways listed below.		
Highway	From	To
Cedar Springs Lane	Junction with OR19	Entrance of Chemical Waste Mng of the NW, approx 4.5 miles
Baseline Road	Junction with OR19	Morrow County line