



**MALHEUR COUNTY WEIGHT RESTRICTED BRIDGES
AND APPROVED ROUTE LIST
ATTACHMENT C23
(REVISED 01-2002)**

Malheur County Weight Restricted Bridge List

Highway	Crossing	Approximate Location	Tandem Axle	3 axle group within 20 feet not uniform in weight	3 axle group within 20 feet uniform in weight	4 axle group within 20 feet not uniform in weight	4 axle group within 20 feet uniform in weight
NO WEIGHT RESTRICTED BRIDGES ON MALHEUR COUNTY APPROVED ROUTES							

PILOT VEHICLE REQUIREMENTS

WIDTH	FRONT PILOTS REQUIRED	REAR PILOTS REQUIRED
WIDTH 08'07" TO 09'00"	NONE	NONE
WIDTH 09'01" TO 10'00"	ONE	NONE
WIDTH 10'01" TO 11'00"	ONE	NONE
WIDTH 11'01" TO 12'00"	ONE	ONE
WIDTH 12'01" TO 14'00"	ONE	ONE

Malheur County Approved Route List

Log Truck & Stinger steered Pole Trailer Combinations are allowed 65 feet in overall length on all highways. All other combinations are allowed 60 feet in overall length on all county highways.

- **The maximum length of a semitrailer in a truck tractor semitrailer combination is 53 feet.**
- **The maximum length of a semitrailer in a truck tractor semitrailer trailer combination (doubles) is 40 feet. The distance measured from the front trailer to the rear trailer cannot exceed 68 feet.**

**Truck-Tractor Semitrailer combinations may operate at a maximum of 75 feet in overall length on the county highways listed below.
Double trailer combinations may operate at a maximum of 95 feet in overall length on the county highways listed below.**

Highway	From	To
Clark Boulevard	Butler Boulevard	OR201
Railroad Ave.	Halliday Road	OR201