

ACRONYMS AND DEFINITIONS

The Following are common acronyms and definitions found in this manual. Other acronyms and definitions are found in Section 00110 of the Standard Specifications and in the Manual of Field Test Procedures Introduction page 3.

AASHTO:	American Association of State Highway and Transportation Officials
AWS:	American Welding Society
CGC:	Commercial Grade Concrete
CMO:	Certificate of Material Origin
DRR:	Documentation Review Report
EAC:	Emulsified Asphalt Concrete
FHWA:	Federal Highway Administration, U.S. Department of Transportation
FIR:	Field Inspection Report
HMAC:	Hot Mixed Asphalt Concrete
I.A.:	Independent Assurance
JMF:	Job Mix Formula
MAMD:	Moving Average Maximum Density
MDT:	Maximum Density Test
MDV:	Mix Design Verification
MFTP:	Manual of Field Test Procedures
MSG:	Maximum Specific Gravity
PCC:	Portland Cement Concrete
PM:	Project Manager. The Engineer's representative who directly supervises the engineering and administration of a Contract.
QA:	Quality Assurance
QAC:	Quality Assurance Coordinator
QC:	Quality Control
QCCS:	Quality Control Compliance Specialist. The Project Managers representative involved with the project Quality Assurance activities and is experienced and certified in all areas of field testing and documentation.
RAP:	Reclaimed Asphalt Pavement

RAS: Region Assurance Specialist
Va: Air Voids
VFA: Voids Filled with Asphalt
VMA: Voids in Mineral Aggregate
W/C Water Cement Ratio (Portland Cement Concrete)