

Standard Guidelines for Product Review
Detectable Warning Devices -
For Wheelchair Ramps; Section 00759.00
December, 2016

DEPARTMENT OF
TRANSPORTATION

Construction Section
800 Airport Road
Salem, OR 97301-4792
503/986-3059

Detectable Warning Devices - 00759.00

For Wheelchair Ramps ODOT is keeping a list of detectable warning devices that can be used on existing sidewalk accesses to cross streets. We have approved the in-line truncated dome design as required by American with Disabilities Act Accessible Guidelines (ADAAG).

Dome size allowed: Base Diameter: 0.9"- 1.4"
Dome Diameter at top: 50-65% of Base Diameter
Dome Height: 0.2"

ODOT's preference for color is safety yellow. Safety yellow for the purposes of this category is defined as one of the following colors from the FHWA color chart at:

<http://www.fed-std-595.com/>

13591
13655
23640
23655
33538
33655
38907

Agencies outside of ODOT may use other colors available that meet contrast requirements required by ADAAG. The color must be through-out the material, top coats will not be allowed. Products submitted for this category should not become slippery if wet, and should be capable of being permanently attached to concrete surfaces. We expect the manufacturer of the warning device to recommend an adhesive that is suitable to affix the warning device to the sidewalk.

Suitable for Fresh (Uncured) Concrete
Suitable for Existing Concrete
Suitable for Asphalt Surfaces

Additional information can be obtained by reviewing our Standard Drawings. RD 759 covers Detectable Warning Devices. Our Standard Drawings can be found at:
http://www.oregon.gov/ODOT/HWY/ENGSERVICES/pages/roadway_drawings.aspx

Standard Guidelines for Product Review
Detectable Warning Devices -
For Wheelchair Ramps; Section 00759.00
December, 2016

DEPARTMENT OF
TRANSPORTATION

Construction Section
800 Airport Road
Salem, OR 97301-4792
503/986-3059

Process - Submit the following:

- [Preliminary Information for Product Evaluation Form.](#)
- Spec Data Sheet including a list of limitations and precautions.
- Detailed drawings including dimensions.
- Detailed installation instructions.
- MSDS if required.
- List of the long-term maintenance required with this product.
- Submit the equivalent of 2 each 6" by 6" samples.

- Adhesive Recommended: _____

Submit all documentation to:

Oregon Department of Transportation
Product Evaluation Coordinator
800 Airport Rd SE
Salem OR 97301-4798