

Standard Guidelines for Product Review
Fencing, Work Zone Delineation
Section 00225.12
December, 2016

Fencing, Work Zone Delineation-00225.12

General – ODOT requires the use of plastic fencing in and around work zones to delineate the work area. The fence shall be sturdy and be able to withstand normal wear and tear of the construction site, including high winds.

Our Standard Specifications can be found at:
<http://www.oregon.gov/ODOT/HWY/SPECS/pages/index.aspx>

Our Standard Drawings can be found at:
http://www.oregon.gov/ODOT/HWY/ENGSERVICES/pages/standard_drawings_home.aspx

Process – Submit the following:

- [Preliminary Information for Product Evaluation Form](#).
- Documentation showing compliance with Specs listed below.
- Spec Data Sheet.
- Detailed installation instructions.
- List of Limitations and Precautions.
- 3 small samples, approx. 8" x 8" each.

Specifications

- A 4 foot roll, 50 feet long shall weigh at least 6 pounds.
- Color: Highly Visible Orange
- Height: 48 inches.
- Legible identification label with the product name and manufacturer's identification every 100 feet (one label per roll if less than 100 feet long).
- The fence must have a porosity (area of holes divided by total area of the fence multiplied by 100) rating of 40 – 70.

Please forward your information and/or questions to:

Oregon Department of Transportation – Materials Laboratory
Product Evaluation Coordinator
800 Airport Road SE
Salem OR 97301-4798
503-986-3059