

MAP OF SURVEY

A PROPERTY LINE ADJUSTMENT being located within the Southeast One-quarter of the Southeast One-quarter of Section 7, Township 37 South, Range 1 West of the Willamette Meridian, in the City of Medford, Jackson County, Oregon.

PREPARED FOR:

MEDFORD WATER COMMISSION
 C/O: Eric Johnson
 Lausmann Annex
 200 South Ivy Street, Rm. 177
 Medford, Oregon 97501

IT IS THE INTENT OF THIS SURVEY TO SUPERSEDE SURVEY NUMBER 20911, WHICH WAS FILED PRIOR TO FINAL CITY OF MEDFORD APPROVAL SIGNATURES

APPROVALS (CITY OF MEDFORD FILE NO. PLA-11-061):

Examined and approved this 3 day of Aug, 2011.
James E. Heber
 Planning Director

Examined and approved this 3 day of Aug, 2011.
[Signature]
 City Surveyor

LEGEND:

- Indicates a set 5/8-inch diameter Iron pin, 24 inches in length, with an orange plastic cap marked "NEATHAMER SURVEYING".
- ▲ Indicates a set .38 caliber shell with brass tag and tack in concrete marked "NEATHAMER SURVEYING".
- ⊙ Indicates a found aluminum cap per ODOT R/W records.
- ⊕ Indicates a calculated Section Corner per Jackson County Re-establishment notes, as depicted hereon.
- Indicates a found 5/8-inch diameter Iron pin per SN 10433, or as otherwise noted hereon.
- Indicates a found 5/8 inch diameter Iron pin per SN 20282.
- ⊠ Indicates a found 3/4 inch diameter pipe per ODOT R/W records.
- Indicates a computed position, nothing found or set.
- () Indicates record information per SN 20282.
- INST Indicates an instrument recorded by number pursuant to the Official Records of Jackson County, Oregon.
- SN Indicates a survey filed by number in the office of the Jackson County Surveyor.

CENTERLINE CRATER LAKE HIGHWAY

SCALE: 1" = 300'

HELD PROPORTIONED SPLIT BETWEEN RECORD MONUMENTS PD. PER ODOT TO LOCATE INCOMING TANGENT LINE

2283+47.21, 64.71 RT. 2283+47.36
 106.17 LT.
 2283+98.852 P.S. 500°02'05"E
 1.20'
 750.00' SPIRAL
 S=16°52'30"

COMPUTED POINT OF SPIRAL AT CENTERLINE STATION 2283+48.65 BEARS S06°12'04"W, 743.84' FROM COMPUTED 1/4 CORNER COMMON TO SECTIONS 7 & 8

C/L CIRCULAR CURVE


DEGREE OF CURVE: 04°30'27"
 RADIUS: 1271.14'
 DELTA: 17°11'45"
 ARC: 381.50'
 LONG CHORD: S25°27'57"W, 380.07'

C/L CIRCULAR CURVE

DEGREE OF CURVE: 04°30'27"
 RADIUS: 1271.14'
 DELTA: 17°11'45"
 ARC: 381.50'
 LONG CHORD: S25°27'57"W, 380.07'

LINE TABLE

LINE	BEARING	DISTANCE
L1	N34°42'19"E	20.46'
L2	S89°24'48"W	3.50'
L3	S86°57'17"W	3.74'
L4	South	0.17'
L5	N00°47'28"W	5.16'
L6	S39°02'00"E	73.00'
L7	S82°19'51"E	11.90'



(SURVEY NARRATIVE IS ON A SEPARATE SHEET)

**** RECEIVED ****
 DATE 8-3-11 BY [Signature]
 This survey consists of:
1 sheet(s) Map
1 page(s) Narrative
 JACKSON COUNTY SURVEYOR

REGISTERED PROFESSIONAL LAND SURVEYOR

Carl E. Neathamer
 OREGON
 JULY 9, 2001
 CAEL E. NEATHAMER
 58545
 Renewal Date 12/31/12

BASIS OF BEARINGS:

Geodetic North referenced to the NAD83 (GRS 96) (Epoch 2002.0000) datum, obtained via Real-Time Kinematic methods utilizing Trimble 5100 Global Positioning System equipment and the Oregon Real-time GPS Network (ORGN). Basis applied to the East line of Section 7, between the Southeast corner and the East One-quarter corner thereof.

PREPARED BY: Neathamer Surveying, Inc.
 3126 State St, Suite 100
 P.O. Box 1584
 Medford, Oregon 97501
 Phone (541) 732-2869
 FAX (541) 732-1382

PLOT DATE: August 3, 2011 **PROJECT NUMBER:** 10003-E

Sheet 1 of 1 © CN