

SAFETY MEETING QUIZ

Employee Name:	Signature:
Department:	Date:
Score: _____ / 7	<input type="checkbox"/> Pass <input type="checkbox"/> Fail
Trainer:	Signature:

Rigging loads for cranes

June 2011

Question 1: The first step in loading should be inspecting all rigging equipment.
 True False

Question 2: Red marks on the surface of nylon slings are nothing to worry about.
 True False

Question 3: You should always check for a weight limit capacity label on a sling.
 True False

Question 4: Safety latches on hooks are a good idea, but they are not really needed.
 True False

Question 5: Tag lines on slings enable you to control loads and steer them into tight places.
 True False

Question 6: Signs of damage on wire slings include:
 A. Kinking.
 B. Cracks.
 C. Splits.
 D. Breaks.
 E. All of the above.

Question 7: To make sure a load is safely rigged, it should be raised three to six feet before beginning the lift.
 True False

Safety Toolbox Talks © 2011 is protected by copyright law. As a paid subscriber you may copy and distribute this material for internal employee training purposes only. It may not be duplicated or posted in any other form without express written consent of the publisher.

**B21 Business 21
Publishing**

453A Baltimore Pike • Springfield, PA 19064
Phone: 484-479-2700 • Fax: 610-543-2292
www.b21pubs.com