



Permit Weight Table 2

(REVISED 01-2019)

See Weight Table 1, if using less than five axles or 47 feet wheelbase.

The following exemptions apply to the table of weights shown below:

Exemption 1: An additional 550 pounds above the weights shown below is allowed for fully functional idle reduction systems.

Exemption 2: An additional 2000 pounds above the weights shown below is allowed for a vehicle that uses natural gas as its fuel source.

Wheelbase In Feet ▼	Number of Axles			
	5	6	7	8 or More
47	77500	81000	81000	81000
48	78000	82000	82000	82000
49	78500	83000	83000	83000
50	79000	84000	84000	84000
51	80000	84500	85000	85000
52	80500	85000	86000	86000
53	81000	86000	87000	87000
54	81500	86500	88000	91000
55	82500	87000	89000	92000
56	83000	87500	90000	93000
57	83500	88000	91000	94000
58	84000	89000	92000	95000
59	85000	89500	93000	96000
60	85500	90000	94000	97000
61	86000	90500	95000	98000
62	87000	91000	96000	99000
63	87500	92000	97000	100000
64	88000	92500	97500	101000
65	88500	93000	98000	102000
66	89000	93500	98500	103000
67	90000	94000	99000	104000
68	90000	95000	99500	105000
69	90000	95500	100000	105500
70	90000	96000	101000	105500
71	90000	96500	101500	105500
72	90000	96500	102000	105500
73	90000	96500	102500	105500
74	90000	96500	103000	105500
75	90000	96500	104000	105500
76	90000	96500	104500	105500
77	90000	96500	105000	105500
78	90000	96500	105500	105500

The loaded weight of any group of axles, vehicle, or combination of vehicles shall not exceed that specified in Permit Weight 1 or any of the following:

- The manufacturer's side wall tire rating but not to exceed 600 pounds per inch of tire width.
- 20,000 pounds on any one axle, including any one axle of a group of axles.
- 34,000 pounds on any tandem axle.
- The sum of the permissible axle, tandem axle, or group of axle weights shown above, whichever is less.

Note exemptions 1 - 2 above.