Appendix A: Additional Excess Thermal Load Limitations

During the term of this permit, a registrant must comply with the applicable temperature excess thermal load limit in the tables below corresponding to the facility's discharge location.

Contents

| 1) | Closed Lake Basin | 1 |
|-----|-----------------------------------|-------|
| 2) | Grande Ronde Basin | 1 |
| - | Klamath Basin | |
| • | Rogue Basin | |
| - | Snake River/Hells Canyon Subbasin | |
| | Willamette Basin | |
| - / | | |

1) Closed Lake Basin

| Alvord Lake Subbasin | | | | |
|---|--|--|--|--|
| Timeframe when limit applies | June – October | | | |
| | Q _{ed} * (0.14*S ₂₅ - T _{SP}) * 3.78541 | | | |
| Effluent Limit Needed to Address Excess Thermal Load | Where: S ₂₅ is the critical dilution provided by DEQ at the time of permit assignment Q _{ed} is the maximum design effluent flow from facility for all outfalls (MGD) T _{SP} is the applicable system potential temperature (from the TMDL) | | | |

2) Grande Ronde Basin

| Upper Grande Ronde Subbasin | | | |
|--|---|--|--|
| Timeframe when limit applies June – October | | | |
| Effluent Limit | Q _{ed} * (0.14*S ₂₅ - T _{SP}) * 3.78541 Where: | | |
| Needed to Address Excess Thermal Load | S ₂₅ is the critical dilution provided by DEQ at the time of permit assignment Q _{ed} is the maximum design effluent flow from facility for all outfalls (MGD) T _{SP} is the applicable system potential temperature (from the TMDL) | | |

3) Klamath Basin

| Upper Klamath and Lake Drainage | | | |
|---|---|--|--|
| Timeframe when limit applies | June – October | | |
| Effluent Limit Needed to Address Excess Thermal Load | Q _{ed} * (0.14*S ₂₅ - T _{SP}) * 3.78541 Where: S ₂₅ is the critical dilution provided by DEQ at the time of permit assignment Q _{ed} is the maximum design effluent flow from facility for all outfalls (MGD) T _{SP} is the applicable system potential temperature (from the TMDL) | | |

4) Rogue Basin

| Applegate Subbasin | | | |
|---|--|--|--|
| Timeframe when limit applies | Year-round | | |
| | Q _{ed} * (0.14*S ₂₅ - T _{SP}) * 3.78541 | | |
| Effluent Limit Needed to Address Excess Thermal Load | Where: S ₂₅ is the critical dilution provided by DEQ at the time of permit assignment Q _{ed} is the maximum design effluent flow from facility for all outfalls (MGD) T _{SP} is the applicable system potential temperature (from the TMDL) | | |

| Lower Sucker Creek Watershed | | | | |
|--|---|--|--|--|
| Timeframe when limit applies | Lung - Sentember | | | |
| Effluent Limit Needed to Address Excess Thermal Load | Q _{ed} * (0.14*S ₂₅ - T _{SP}) * 3.78541 Where: S ₂₅ is the critical dilution provided by DEQ at the time of permit assignment Q _{ed} is the maximum design effluent flow from facility for all outfalls (MGD) T _{SP} is the applicable system potential temperature (from the TMDL) | | | |
| | | | | |

| Upper Sucker Creek Watershed | | | | |
|--|---|--|--|--|
| Timeframe when limit applies | June – September | | | |
| Effluent Limit Needed to Address Excess Thermal Load | Q _{ed} * (0.14*S ₂₅ - T _{SP}) * 3.78541 Where: S ₂₅ is the critical dilution provided by DEQ at the time of permit assignment Q _{ed} is the maximum design effluent flow from facility for all outfalls (MGD) T _{SP} is the applicable system potential temperature (from the TMDL) | | | |

| Lobster Creek Watershed | | | |
|---|--|--|--|
| Timeframe when limit applies | Year-round | | |
| | Q _{ed} * (0.14*S ₂₅ - T _{SP}) * 3.78541 | | |
| Effluent Limit Needed to Address Excess Thermal Load | Where: S ₂₅ is the critical dilution provided by DEQ at the time of permit assignment Q _{ed} is the maximum design effluent flow from facility for all outfalls (MGD) T _{SP} is the applicable system potential temperature (from the TMDL) | | |

5) Snake River/Hells Canyon Subbasin

| Snake River/Hells Canyon Subbasin | | | |
|---|---|--|--|
| Timeframe when limit applies | May – September | | |
| Effluent Limit Needed to Address Excess Thermal Load | Q _{ed} * (0.14*S ₂₅ - T _{SP}) * 3.78541 Where: S ₂₅ is the critical dilution provided by DEQ at the time of permit assignment Q _{ed} is the maximum design effluent flow from facility for all outfalls (MGD) T _{SP} is the applicable system potential temperature (from the TMDL) | | |

6) Willamette Basin

| Lower Willamette Subbasin (Columbia Slough and Fairview Creek Watersheds) | | | | |
|---|---------------|---|--|--|
| Timeframe when limit applies | Year-round | | | |
| File No. | Permit No. | Common Name | Specific Excess Thermal Load (Million Kcal/day)¹ | |
| 52638 | 10451 | Herbert Malarkey Roofing Company | 5.77 | |
| 103832 | 12073 | Ventura Foods, LLC | 4.03 | |
| 65610 | 10618 | Owens-Illinois Glass Container Inc. (Owens Brockway) | 3.90 | |
| 103774 | 12024 | Miller Paint Co Inc | 1.30 | |
| Note: Basis for the TMDL temperature is BBNC. | | | | |

| Tualatin Subbasin | | | | |
|---|---|----------------------------|--|--|
| Timeframe when limit applies | June – October | | | |
| File No. | Permit No. | Common Name | Site Potential Temperature (°F) | Specific Excess Thermal Load (Million Kcal/day) |
| 103777 | 12029 | Pacific Foods | 62 | 1.1 |
| 103448 | 11779 | Epson Portland Inc | 61.1 | 0.082 |
| 87628 | 10833 | Tektronix | 61.1 | 0.15 |
| 108322 | 14334 | Maxim Wafer Fab Operations | 61.1 | 0.13 |
| 107618 | 13556 | Henningsen | 57.8 | 0.013 |
| Effluent Limit Needed to Address Excess Thermal Load for New Discharges | Q _{ed} * (0.14*S ₂₅ - T _{SP}) * 3.78541 Where: S ₂₅ is the critical dilution provided by DEQ at the time of permit assignment Q _{ed} is the maximum design effluent flow from facility for all outfalls (MGD) T _{SP} is the applicable system potential temperature (from the TMDL) | | | |