

RECORD IDENTIFICATION

RECORD NO..... M061421
RECORD TYPE..... X1M
COUNTRY/ORGANIZATION. USGS
MAP CODE NO. OF REC..

REPORTER

NAME..... JOHNSON, MAUREEN G.
UPDATED..... 80 12
BY..... FERNS, MARK L.; (BROOKS, HOWARD C.)

NAME AND LOCATION

DEPOSIT NAME..... BUCK POINT

MINING DISTRICT/AREA/SUBDIST. ASHLAND

COUNTRY CODE..... US
COUNTRY NAME: UNITED STATES

STATE CODE..... OR
STATE NAME: OREGON

COUNTY..... JACKSON

QUAD SCALE QUAD NO OR NAME
1: 62500 ASHLAND

LATITUDE LONGITUDE
42-08-55N 122-33-01W

UTM NORTHING UTM EASTING UTM ZONE NO
4666150.0 537150.0 +10

TWP..... 39S
RANGE..... 02E
SECTION.. 26
MERIDIAN. WILLAMETTE

LOCATION COMMENTS:

COMMODITY INFORMATION

COMMODITIES PRESENT..... AU CU AG

OCCURRENCE(S) OR POTENTIAL PRODUCT(S):

POTENTIAL.....
OCCURRENCE..... AU CU AG

DRE MATERIALS (MINERALS, ROCKS, ETC.):

EXPLORATION AND DEVELOPMENT
STATUS OF EXPLOR. OR DEV. 1

PROPERTY IS INACTIVE

DESCRIPTION OF DEPOSIT

DEPOSIT TYPES:

VEIN/FAULT ZONE

FORM/SHAPE OF DEPOSIT:

SIZE/DIRECTIONAL DATA

MAX WIDTH..... 28 INCHES

DESCRIPTION OF WORKINGS
SURFACE

COMMENTS (DESCRIP. OF WORKINGS):

FOUR CUTS

PRODUCTION

NO PRODUCTION

ANNUAL PRODUCTION (ORE, COMMOD., CONC., OVERBURD.)

GEOLOGY AND MINERALOGY

AGE OF HOST ROCKS..... OLIGO-MIO

HOST ROCK TYPES..... ANDESITE

PERTINENT MINERALOGY..... GYPSUM

LOCAL GEOLOGY

NAMES/AGE OF FORMATIONS, UNITS, OR ROCK TYPES

1) NAME: LITTLE BUTTE VOLCANICS

AGE: OLIGO-MIO

GENERAL REFERENCES

1) OREGON METAL MINES HANDBOOK, 1943, ODMGMI BULL. 14-C, VOL. 2, SEC. 2, P. 29



See 23 7395 R26.

STATE DEPARTMENT OF GEOLOGY AND
MINERAL INDUSTRIES

STATE ASSAY LABORATORY
802 EAST H STREET
GRANTS PASS, OREGON

ASSAY REPORT

December 31, 1937

Mr. J. E. Morrison, Mining Geologist
State Assay Laboratory
Grants Pass, Oregon

Following are the results of assays made on samples
from the property of H. Kerby and associates; Buck Point
Claim:

<u>Office number</u>	<u>Sample number</u>	<u>Gold</u>		<u>Silver</u>		<u>Total value</u>
		<u>Oz./ton</u>	<u>\$/ton</u>	<u>Oz./ton</u>	<u>\$/ton</u>	<u>\$/ton</u>
598	1	0.01	0.35	0.5	0.32	0.67
599	2	0.10	3.50	Trace		3.50
600	3	0.08	2.80	Trace		2.80
601	4-Grab	Trace		Trace		
606	5-Grab	Trace		Trace		

Signed... *Albert A. Lewis* ...
Assayer

- No 1 - Hole 10' deep 12' long on fracture
strike N 38° W dip 74° 5' W. 28" wide
gauge on ft wall. 14" from present
limb on hanging wall.
Sample taken in face 8' below surface.
This hole 150 ft S.E. of working on Ridge.
- No 3 - 16" limb rock north hole.
- No 4 - Grab sample from dump of 25 shaft.
some qt crystals. (surface deposition)
- No 5 - Grab sample of everything from dump.
- No 2 - Open cut Fracture 28" wide no gauge
cut 6 ft deep 4 ft long & 28" wide
dip 75° NE.

Property 1 mile south of Barrow mine

STATE DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES

ASSAY LABORATORIES

Baker, Oregon
Grants Pass, Oregon

SAMPLE INFORMATION REQUESTED

The law passed by the Legislature, governing the free assaying and analyzing of samples sent to a State Assay Laboratory, provides that certain information be furnished to the laboratory regarding samples sent for assays, etc. A copy of the law will be found on the back of this blank. Please read the law carefully. Will you please fill in the information called for in the following blank, as far as possible, and return the same to the nearest State Assay Laboratory, along with your sample. If you have made out a blank, this copy is for your future use. Keep a copy of the information on each sample for your own reference.

Your name in full J. E. Morrison

Post office address _____

Are you a citizen of Oregon? _____ Date on which sample is sent 12/7/37.

Name (or names) of owners of the property Buck Point, H Herby & Associates

Name of particular claim and date of location Buck Point

Location of property or source of sample:

(1) County Jackson (2) Mining District Ashland

(3) Township 375. (4) Range 2E. (5) Section 26

(6) Quarter Section NW 1/4 of SE 1/4.

How far from passable road? 1/4 mile

For what do you wish sample tested? gold.

Does your sample represent a new discovery? no

On a newly located claim? no Old? yes

Has any ore from this claim been milled or shipped? no.

Width of ore where sample was taken (length of channel cut) see samples.

Remarks: The Department would be pleased to have you add to the above, such information as you think would be of interest and value. This could be placed in the space below or upon a separate sheet. This could best be shown by a pencil sketch, indicating the development on the claim with widths of vein, especially the width of ore at the place where this sample was taken.

A sample, to be of value, should be taken in an *even channel across the vein* from wall to wall. Its position in the workings should be marked and the width measured. Assays of unlocated samples, without widths, are of little value. They create but little interest in the minds of experienced investors and engineers.

- 1 - 14"
- 2 - 28"
- 3 - 16"
- 4 - Grab
- 5 - Grab.

Signed J. E. Morrison
(Over)

ASSAY REPORT

December 31, 1937

Mr. J. E. Morrison, Mining Geologist
State Assay Laboratory
Grants Pass, Oregon

Following are the results of assays made on samples from the property of H. Kerby and associates; Buck Point Claim:

Office number	Sample number	Gold		Silver		Total value \$/ton
		Oz./ton	\$/ton	Oz./ton	\$/ton	
598	1	0.01	0.55	0.5	0.32	0.67
599	2	0.10	3.50	Trace		3.50
600	3	0.08	2.60	Trace		2.60
601	4-Grab	Trace		Trace		
606	5-Grab	Trace		Trace		

Signed.....*P. A. L.*.....
Assayer

12/6/37

Jackson County

Buck Point Quartz

Owners: H. Kerby, Frank Kerby, Talent, Oregon; Jessie Williams and Marion Briner, Coquille, Oregon.

Location: 11 miles S. E. of Ashland on a branch of Sampson Creek and about 1 Mile South of the Barron Mine in Sec. 26, T. 39 S., R. 25.

History: Discovered in 1935. Yearly assessment work is the only development work. No production

General

Information: Hilly topography, andesite lava country rock, elevation 3000 ft., no timber on property but can be secured close by. Water will have to be developed. A possible source is 1/4 mile from the property. Maximum snowfall is four feet. The road goes within 1/4 mile of property, needs repairing.

Geology: The veins are formed by filling in a fault zone which is about 28 inches wide. Minerals observed are quartz, calcite, pyrite, gypsum, and chalcopryrite. Five samples were taken, the highest run \$3.50.

Development: Four shallow open cuts opening the vein up, maximum distance of 500 feet.

Informant: J. E. Morrison

see assay report.