STATE OF OREGON
D. ..MENT OF GEOLOGY AND MINERAL INDUSTRI..
910 State Office Building Portland, OR 97201

WELL SUMMARY REPORT
(In compliance with rules and regulations pursuant to ORS 520)

Nahama & Weagant Energy Co. (Company or Operator) — Cavenham Energy Resources (Lease) — ~~CER 14-26-64~~ (Well No.)

Sec. 26, T 6N, R 4W Surveyed Coordinates (if directional, BHL & SHL): 1239' N & ~~521~~ 251' E of SW Cor.

Wildcat: Yes (or) Field Name: County: Columbia

Signature: Trent D. Rosenbel

Date: 12-13-91 Position: VP Engineering

Commended drilling: 9-5-91 Completed drilling: 9-13-91 P&A:

Total depth: 2702' Redrill depth:

Logs run: DIL-BCS-GR-CAL, FED

CASING RECORD

Size of hole	Size of casing	Wt. in lbs. per ft.	Grade Type	Depth	Amount of cement
8 3/4'	4.5"	10.5	J-55	2082'	175 sx

	Geological Marker	Depth
Plugs	Top Cowlitz	1640'
	Top C&W	1902'
Junk		

Perforations or Liner

Size of casing	From	To	Shots/ft.	Method of Perforating		
				Jet	Bullet	Slotted Line

Initial Production

Date	Clean Oil bbl/day	Gravity	Percent Water	F.T.P.	F.C.P.	S.I.T.P.	S.I.C.P.

OGSumm4.For/7

Rev. August 29, 1990

STATE OF OREGON
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES
800 NE Oregon St #28 Portland, OR 97201

WELL SUMMARY REPORT
(In compliance with rules and regulations pursuant to ORS 520)

Enerfin Resources Northwest (Company or Operator) — "Bascom Pacific LLC" (Lease) — 14-26-64 RD #1 (Cedar Point) (Well No.)

Sec. 26 T 6N R 4W Surveyed Coordinates:

SHL= 1,239' North and 251' East from the Southwest corner of Section 26

BHL= 981.66' South and 1,500.07' East from SHL at 3,050' (2,115.85' TVD)

Wildcat: NA (or) Field Name: Mist Gas County: Columbia

Signature: -Rob Lucas

Date: January 3, 2000 Position: Consultant

Commenced drilling: January 24, 2000 Completed drilling: January 28, 2000 P&A: January 30, 2000

Total depth: 3,050' (2,116' TVD) Redrill depth: NA

Logs run: Mud log from 550'-3,050'; AIT/DSN/CDL/BHC/GR from 3,039'-517'

Casing Record

Size of hole	Size of casing	Wt. in lbs. per ft.	Grade Type	Depth	Amount of cement
25"	16"			20'	Surf. Pour
13-3/4"	9-5/8"	36#	J-55/ST&C	520'	250 sx

	Geological Marker	Depth
Plugs 625'-467'	Cowlitz	2,110' (1,630' TVD)
	C&W	2,499' (1,835' TVD)
Junk Top of 4-1/2" casing at 631'		

Perforations or Liner

Size of casing	From	To	Shots/ft.	Method of Perforating		
				Jet	Bullet	Slotted Liner

Initial Production

Date	Clean Oil bbl/day	Gravity	Percent Water	F.T.P.	F.C.P.	S.I.T.P.	S.I.C.P.