

WELL SUMMARY REPORT  
(Submit in duplicate)

Operator Ivan Vojvoda Field Lebanon Area  
Well No. Barr 1 - Redrill NW1/4 Sec. 32, T 11S, R 1W, WM W. B. & M.  
Location 262'S & 790'E from NW cor. Elevation above sea level 355' feet  
All depth measurements taken from top of Kelly Bushings, which is 12 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date December 7, 1966 Signed Ivan J Vojvoda  
Title President  
Engineer or Geologist \_\_\_\_\_ Superintendent \_\_\_\_\_ (President, Secretary or Agent)

Commenced drilling Oct 23, 1966 Completed drilling Nov. 3, 1966 Drilling tools Cable Rotary  
Total depth 3937' Plugged depth 0 GEOLOGICAL MARKERS DEPTH  
Junk 4 3/4" mill bit, top at 3936'.  
Whipstock at 3934'

Commenced producing \_\_\_\_\_ Date \_\_\_\_\_ Flowing/gas lift/pumping (cross out unnecessary words)

|                          | Clean oil bbl. per day | Gravity Clean oil | Percent water including emulsion | Gas Mcf. per day | Tubing Pressure | Casing Pressure |
|--------------------------|------------------------|-------------------|----------------------------------|------------------|-----------------|-----------------|
| Initial production       |                        |                   |                                  |                  |                 |                 |
| Production after 30 days |                        |                   |                                  |                  |                 |                 |

CASING RECORD (Present Hole)

| Size of casing (A.P.L) | Depth of shoe | Top of casing | Weight of casing | New or second hand | Seamless or Lapweld | Grade of casing | Size of hole drilled | No. of sacks of cement | Depth of cementing if through perforations |
|------------------------|---------------|---------------|------------------|--------------------|---------------------|-----------------|----------------------|------------------------|--|
| 10 3/4"                | 440'          | 0             | 32               | New                | Seamless            | H-40            | 15"                  | 530 sacks              |  |
| 5 1/2"                 | 4422'         | 0             | 15.5             | New                | Seamless            | J-55            | 7 7/8"               | 600 sacks              |  |

PERFORATIONS

| Size of casing | From | To  | Size of perforations | Number of rows | Distance between centers | Method of perforations |
|----------------|------|-----|----------------------|----------------|--------------------------|------------------------|
|                | ft.  | ft. |                      |                |                          |                        |
|                | ft.  | ft. |                      |                |                          |                        |
|                | ft.  | ft. |                      |                |                          |                        |
|                | ft.  | ft. |                      |                |                          |                        |
|                | ft.  | ft. |                      |                |                          |                        |