

HISTORY OF OIL OR GAS WELL

(In compliance with rules and regulations pursuant to ORS 520)

D. Y. OIL, INC. ARGO BURRIS CC24-8  
(Company or operator) (Lease) (Well No.)  
Sec. 8, T. 5N, R. 4W W.B.&M. Surveyed Coordinates:  
1223.29 feet North and 2040.84 feet East from the SW corner  
Wildcat: \_\_\_\_\_ (or) Field Name: Mist County: Columbia  
Date: 08-28-89 Signature: Diane Leault  
Position: Agent

Use this form in reporting the daily operations at the well. (Operator may use his own forms, but heading of this form must also be completed and submitted.) Please submit a complete history of the well. Include such information as bit sizes, mud weights, casing sizes and depths set, amount of cement used, drilling depths, fishing, logging, perforating, and plugging procedures, and anything else pertinent to the operation. Do not include lithology.

| Date     |  |
|----------|--|
| 08-16-89 | Burriss CC24-8 (Mist)<br>TD:171' MUD:8.8 VIS: 38<br>Drill 12 $\frac{1}{4}$ " hole to 171': slight lose circ at 70'.  |
| 08-17-89 | Burriss CC24-8 (Mist)<br>TD:385' MUD:8.5 VIS:34<br>Drill to 385', wiper trip to surface: run 8 5/8" casing to 385'. Cemented w/200 sx. cement. No return. Top job with 50 sx with full return. Weld on well head. Tested at 1500 PSI for 15 min. Nippled up B.O.P. |
| 08-18-89 | Burriss CC24-8 (Mist)<br>TD:1026' MUD:9.0 VIS:38-40<br>Tested B.O.P. at 9:35am by DOGAMI: approved by Dan with DOGAMI. Drilled out cement 7 7/8" bit. Drill to 710'. Wiper trip out of hole. Check Bit. Drill to 1026'.  |
| 08-19-89 | Burriss CC24-8 (Mist)<br>TD:1924' MUD:9.2 VIS:38-42<br>Drilled to 1172, losing mud. Wipe trip to 650'. 1514' wiper trip and survey hole. Drilled to 1924' still losing mud.  |
| 08-20-89 | Burriss CC24-8 (Mist)<br>TD:2684' MUD:9.0 VIS:38<br>Drilled to 2006' losing mud slowly. Trip for #3 bit 7 7/8". Condition mud. Build volume. Drilled C & W sand at 2260'. Drilled sand to marker + 75'. TD 2684'. Circ clean hole.                                 |
| 08-21-89 | Burriss CC24-8 (Mist)<br>TD:2684'<br>Clean hole, clean bridge at 2250'. P.O.H. for logs. Rig up and L.D.D.C.S. cement w/55x + 2% cacl bottom at 428'. Plug slipped, recemented w/55sx bottom at 422' CIA at 12:01am.   |

Form 6  
(9/84)

HISTORY OF OIL OR GAS WELL

Page \_\_\_\_\_

| Date    |   |
|---------|---|
| 8-22-89 | Burriss CC24-8 (Mist)<br>TD:2684'<br>Tag plug at 281'. L.D.D.P. Nipple down and lay down, kelly & rig down. |