



45-184 Eye-Ease  
48-484 20/20 Buff  
Made in USA

# REC Busch 14-15 Completion Test

8/11/84

Perfs. 1524-56

1564-79

G/W 1634 (-1093)

Time (minutes)	Choke	outside	1			2		3		4	
			Casing Pr.	Tubing Pr.	Orifice Pr.	Flow Rate (MMCF)					
1	S.I.	1"	790	810	—	—	—	—	—	—	
2	16/64		780	795	40	1.16					
3	2		780	795	40	1.16					
4	3		780	795	39	1.14					
5	5		780	795	39	1.14					
6			- increase rate -								
7	18 1/2/64		780	790	58	1.55					
8	8		780	790	58	1.55					
9	10		780	790	58	1.55					
10	12		780	788	58	1.55					
11	14	21 3/4/64	775	765	80	2.03					
12	16		775	760	82	2.07					
13	18		775	750	78	1.99					
14	20		775	750	78	1.99					
15			- increase rate -								
16	22	24/64	775	720	97	2.39					
17	24		775	725	97	2.39					
18	26		775	730	98	2.42					
19	28		775	740	100	2.46					
20			- shut in -								
21	31		785	810	—	—					
22	32		790	810	—	—					
23	33		770	810	—	—					
24	34		790	810	—	—					
25	36		790	810	—	—					
26	40										
27	41	27 3/4/64	770	720	130 (off chart)	?					
28	44		- shut in -		—	—					
29	50	1 1/2	795	810	—	—					
30	51	31/64	760	680	44	3.39					
31	53		760	660	41	3.21					
32	55		765	660	41	3.21					
33	57		765	660	41	3.21					