STATE OF OREGON DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES

800 NE Oregon St =28

Portland, OR 97201

WELL SUMMARY REPORT (In compliance with rules and regulations pursuant to ORS 520)

Enerfin Resources Northwest						"Columbia County"					11-34-75 (Stegosaur)				
	(Company or Operator)					(Lease)					(Well No.)				
Sec.	34	34 T 7N R			·	5W Surveyed Coordinates:									
SHI.= 55	SHI.= 556.76' South and 1,034.20' East from the Northwest corner of Sec. 34 (X=1 290 081 Y=882 212)														
BHL=														<u>, </u>	
Wildcat:	NA		(or) Fi	eld Nam	ıe;	Mist Gas					County:	Columbia	-		
		_	_		•	Si	gnature:	1)	J-J ~	<u> </u>					
Date: July	13, 199	99				Po	osition:	Consu	ltant		-//				
Commenced	d=:11:	T 11	1000												
Commenced		June 11,	<u> 1999</u>		_		June 19, 1999				P&A:	NA	<u> </u>		
Total depth: 3,230' Redrill depth:															
Logs run: Mud log from 50'-3,230'; AIT/DSN/CDL/BHC/GR from 3,224'-518'; NDL/CBL/CCL from 3,050'-1,050'															
		Size of hole		Size of c			Wt. in Il	os. per	Grade		De	Depth		Amount of	
	25"						ft.	.	Type					cement	
Casing		25"		12"				· , <u>.</u>				20'		Surf. Pour	
Record		9-7/8"		7"		20#		J-55/ST		T&C	51:	3'	2	160 sx	
		6-1/4"		2-7/8"			6.5#		J-55/EUE		3,1	3,106'		244 sx	
												<u> </u>	_	<u> </u>	
										<u></u>					
							Geological	Marker					Depti	h	
Plugs Pittsburg F						rg Bluff						405'			
Sager Cree						reek						1,520'			
Keasey Cowlitz												1,875'			
Junk	Z							2,510'							
				C&W								897'	<u>.</u>		
	Size of	From	From 2,897'		То		Shots/ft,		Metho	hod of Perforating					
	<u> </u>									Jet		Bullet		Slotted Liner	
Perforations or	2-7/8"				2,897	2,903'		4		1			<u>. , .</u>		
Liner			_												
									_				<u> </u>		
İ														_	
7.574			Clean Oil bbl/day			y	Percent Water		F.T.P.		F.C.P.	S.I.T	.P.	S.I.C.P.	
Initial Production	7-8-9	7-8-99 (test) 1038 MCF			D									762	