



NEUTRON-  
MICRO-SEISMOGRAM  
LOG-CASED HOLE

COMPANY: PELLWOOD ENERGY CORP  
 WELL: WT-009-00084  
 FIELD: CO. WMAIR COUNTY Wb. 15-1  
 COUNTY: McMURRAY STATE: OKLAHOMA

Location: 399 N. E 152 E. # 28  
3rd 400 56-1  
W 8 & W  
 Sec: 1 Twp: 611 Rge: 5W  
 Other Services: GIS 4.1%  
GIS 4.1%  
GIS 4.1%

Permanent Datum: 5.6 Elev: 1153.1  
 Log Measured From: K.O. 14271 Above Perm. Datum  
 Drilling Measured From: K.O. Elev: K.O. 1153.1  
0.0

Run No: 1  
 Date & Time Survey: 8-18-91 Hour: 11:30  
 Date & Time Cementing: 8-18-91  
 Date of Drilling: 8-18-91  
 Depth Well: 2664.6  
 Depth Interval: 2664.6 to 2664.6  
 Casing Driller: 41179 to 41179  
 Floor Casing - D.V. Tool: 41179 to 41179  
 Squeeze Depth: 2635.0 to 2635.0

Amount & Type Cement: 200 Sacs Class 40  
 Type Fluid in Hole: Water  
 Fluid Level: Water  
 Solubly PPM Cl: Water  
 Weight lb/gal - Vis: Water  
 Approx. longest cem. top: Water  
 Calculated Cement Top: Water  
 Max. Hole Temperature: 75.5 F.  
 Log No. 2664.6  
 Section Recorded: 2664.6  
 Section by Action: WELDEX  
 Witnessed by: WELDEX

BORE HOLE RECORD			CASING RECORD				
Bit Size	From	To	Csg. Size	Wt.	From	To	Centralized Interval
			4 1/2"	12.5	5'	2710'	
							Scratched Interval
							Open Perforations

SERVICE TICKET NO. 22222 REMARKS: CEMENT INFO: 200 SACS 40 @ 13.5'

Weldex does not guarantee the accuracy of any interpretation of log data, conversion of log data to physical rock parameters, or recommendations which may be given by Weldex personnel or which may appear on the log or in any other form. Any use of such data, interpretations, conversions, or recommendations agrees that Weldex is not responsible, except where due to gross negligence or willful misconduct, for any loss, damages, or expenses resulting from its use thereof.

COLLAR LOG

NEUTRON

