

CC 14-02-65



2" = 100'  
WITH 2" LINEAR CORRELATION LOG


**DUAL INDUCTION  
GUARD LOG**

COMPANY: REICHOLD ENERGY CORPORATION  
 WELL: MIST NEHALEM BASIN  
 COUNTY: COLUMBIA COUNTY, OREGON  
 LOCATION: 330' NORTH & 546' EAST OF SOUTHWEST CORNER OF:  
 FIELD: MIST NEHALEM BASIN  
 STATE: OREGON  
 DATE: 11-5-80  
 TIME: 10:57 AM  
 DRILLER: T.D. DRILLER  
 LOGGERS: T.D. LOGGED, T.D. WELX  
 ELEVATION: 1192.95 G.L., 1182.45 G.L.

Change in Mud Type or Additional Samples		SCALE CHANGES			
Date	Sample No.	Type Log	Depth	Scale Up Hole	Scale Down Hole

Dens. & Fluid Loss		EQUIPMENT DATA			
Source	Loss	Run No.	Tool Type and No.	Pad Type	Tool Position
R <sub>u</sub> @ Meas. Temp.	@	3582	DIGL 21674		
R <sub>u</sub> @ Meas. Temp.	@	3582			
R <sub>u</sub> @ Meas. Temp.	@	3580			
R <sub>u</sub> @ Meas. Temp.	@				
R <sub>u</sub> @ BHT	1.87 @ 130°F				
R <sub>u</sub> @ BHT	1.6 @ 130°F				
R <sub>u</sub> @ BHT	1.21 @ 130°F				

Welex does not guarantee the accuracy of any interpretation of log data, conversion of log data to physical rock parameters, or recommendations which may be given by Welex personnel or which may appear on the log or in any other form. Any user of such data, interpretations, conversions, or recommendations agrees that Welex is not responsible, except where due to gross negligence or willful misconduct, for any loss, damages, or expenses resulting from the use thereof.



Rmf 1.6 at 130 °F	DEEP INDUCTION 30	SHALLOW GUARD 30
POTENTIAL MILLIVOLTS --- 10 --- +	O.S. 300	O.S. 300
	DEEP INDUCTION 0	DEEP INDUCTION 0
	SHALLOW GUARD 6	SHALLOW GUARD 6
	O.S. 2000	O.S. 2000
	AMPLIFIED GUARD 1000	AMPLIFIED GUARD 1000
	RESISTIVITY OHMS M <sup>2</sup> /M	CONDUCTIVITY M MHOS/M