STATE OF OREGON

DEP TMENT OF GEOLOGY AND MINERAL INL

1065 state Office Building Portland 1, Oregon

HISTORY OF OIL OR GAS WELL

(Submit in duplicate)

In compliance with rules and regulations adopted pursuant to ORS 520.095 (Chapter 667 OL 1953)

Operator REICHHOLD ENERGY CORPORATION

Field Mist

Well No. C.C. 32-33

, Sec. 33 . T. 7N

R. 5W

W. B. & M.

Date 8-16-82

Signed / in Welliamor
Title Drilling Superintendent

(President, Secretary or Agent)

It is of the greatest importance to have a complete history of the well. Use this form in reporting the history of all important operations at the well, together with the dates thereof, prior to the first production. Include in your report such information as size of hole drilled to cementing or landing depth of casings, number of sacks of cement used in the plugging, number of sacks or number of feet of cement drilled out of casing, depth at which cement plugs started, and depth at which hard cement encountered. If the well was dynamited, give date, size, position and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position and results of pumping or bailing.

Date

7-29-82

7-30-82 7-31-82

8 -1-82

8 -2-82

8- 3-82

8- 4-82 8- 5-82 Spudded, Drilling 9 5/8 surface hole to 510', Ran 12 JTs 7" K-55 pipe to a total depth of 480.60

Nippled up B.O.P.s & tested with Bill King witnessing Drilling $6\ 1/4$ hole to 1090'

Drilling 6 1/4 hole to 1480'
Drilling 6 1/4 hole to 2100'
Drilling 6 1/4 hole to 2577'

Drilling 6 1/4 hole to 2577'
T.D. well @ 2614', Rig up Schlumberger and logging
Plugged hole from 2614' - 2264' preparing to redrill.