



COMPANY NAHAMA & WEAGANT ENERGY CO.
WELL CC BIGFOOT #34-31-65 (RD #1)
FIELD MIST
LOCATION 2047.19' West and 661.60' North of the SE corner of Sec. 31, T6N, R5W, W. 1, W. M.
COUNTY, STATE Columbia Oregon
API WELL INDEX NO.
ELEVATION 786.44" G.L. 796.44" R.S.
DATES FROM 8-20-91 TO 8-22-91
DEPTHS FROM 543' TO 1902'
SPUD DATE 8-13-91
DRILLING CONTRACTOR Taylor Drilling Inc., Rig #7
MUD COMPANY Beaver Drilling Fluids
LOGGING GEOLOGISTS Jim Eastes John Riddle

ABBREVIATIONS		CASING RECORD	
NB BIT	MW MUD WEIGHT	8 5/8" AT 502' K.B.	
RRB RERUN BIT	VIS FUNNEL VISCOSITY		
RTB RE-TIP BIT	PV PLASTIC VISCOSITY		
CB CORE BIT	YP YIELD POINT		
T.G. TRIP GAS	FL FLUID LOSS (cc/30 min)		
S.G. SURVEY GAS	CL PPM CHLORIDE ION		
W.G. WIPER GAS	RM MUD RESISTIVITY		
C.G. CONNECTION GAS	RMF FILTRATE RESISTIVITY		
WOB WEIGHT ON BIT	LAT LOGGATE AFTER TRIP	12 1/4" AT 503' K.B.	
RPM ROTARY REV/MIN	NR NO RETURNS	7 7/8" AT 1902' K.B.	
PP PUMP PRESSURE	PR POOR RETURNS		
SPM STROKES/MIN	MUD TYPE Drispac/Polymer		

<input type="checkbox"/> SAND/SANDSTONE	<input type="checkbox"/> CLAY	<input type="checkbox"/> LIMESTONE	<input type="checkbox"/> TUFF	<input type="checkbox"/> LIGNITE
<input type="checkbox"/> SHALE	<input type="checkbox"/> DIATOMITE	<input type="checkbox"/> DOLOMITE	<input type="checkbox"/> FOSSIL	<input type="checkbox"/> GLAUCONITE
<input type="checkbox"/> SILTSTONE	<input type="checkbox"/> CONGLOMERATE	<input type="checkbox"/> BASALT	<input type="checkbox"/> MICA	<input type="checkbox"/> PYRITE

OIL: BASED ON LIVE OIL IN UNWASHED CUTTINGS AND PERCENT STAINING AND FLUORESCENCE OF WASHED SAMPLES.

