CC43-27-65

COMPENSATED SONIC LOG 5"

CSU

COMPANY: REICHHOLD ENERGY CORPORATION

WELL: COLUMBIA COUNTY #43-27

FIELD: MIST
COUNTY: COLUMBIA
STATE: OREGON

LOCATION: FR. E 1/4 COR. S1 00°31"W
477.87'-N89 59°29"W 740.96
SEC: 27 TWP: 6N RGE: 5W

PERMANENT DATUM: GL
ELEV. OF PERM. DATUM: 898.5 F
LOG MEASURED FROM: KB
12.5 F ABOVE PERM. DATUM
DRLG. MEASURED FROM: KB

ELEVATIONS-
KB: 911.0 F
DF:
GL: 898.5 F

DATE: 19 AUG 84
RUN NO: 1

OTHER SERVICES-
FDC/CNL/GR
DIL
HDT

API SERIAL NO:
3600900127

PROGRAM
TAPE NO:
26.2
SERVICE
ORDER NO:
382957

DEPTH-DRILLER: 2441.0 F
DEPTH-LOGGER: 2439.0 F
BTM. LOG INTERVAL: 2391.0 F
TOP LOG INTERVAL: 398.0 F

CASING-DRILLER: 400 F
CASING-LOGGER: 398 F
CASING: 8.625

BIT SIZE: 7.875
DEPTH: 2441 F

RECEIVED
SEP 26 1986
DOGAMI
Portland

TYPE FLUID IN HOLE: LIGNOSULFONATE
DENSITY: 11.0 LB/G
VISCOSITY: 53.0 S
PH: 9.0
FLUID LOSS: 4.6 C3
SOURCE OF SAMPLE: CIRC.
RM: 1.350 OHMM AT 81.0 DEGF
RMF: .860 OHMM AT
RMC: 2.000 OHMM AT 72.0 DEGF
SOURCE RMF/RMC: MEAS. /MEAS.
RM AT BHT: 1.176 OHMM AT 94.0 DEGF
RMF AT BHT: .059 OHMM AT 94.0 DEGF
RMC AT BHT: 1.564 OHMM AT 94.0 DEGF

TIME CIRC. STOPPED: 0230
TIME LOGGER ON BTM.: 0626

MAX. REC. TEMP: 94.0 DEGF

LOGGING UNIT NO: 8128
LOGGING UNIT LOC: SACRAMENTO
RECORDED BY: ANDERSEN
WITNESSED BY: ALGER

REMARKS:

EQUIPMENT NUMBERS-

IEM 304 SLM 138 IS 691 IC 658
MCD 1287 SLS 252 SLC 1468

ALL INTERPRETATIONS ARE OPINIONS BASED ON INFERENCES FROM ELECTRICAL OR OTHER MEASUREMENTS AND WE CANNOT, AND DO NOT GUARANTEE THE ACCURACY OR CORRECTNESS OF ANY INTERPRETATIONS, AND WE SHALL NOT, EXCEPT IN THE CASE OF GROSS OR WILLFUL NEGLIGENCE ON OUR PART, BE LIABLE OR RESPONSIBLE FOR ANY LOSS, COSTS, DAMAGES OR EXPENSES INCURRED OR SUSTAINED BY ANYONE RESULTING FROM ANY INTERPRETATION MADE BY ANY OF OUR OFFICERS, AGENTS OR EMPLOYEES. THESE INTERPRETATIONS ARE ALSO SUBJECT TO OUR GENERAL TERMS AND CONDITIONS AS SET OUT IN OUR CURRENT PRICE SCHEDULE.

FILE 9 19-AUG-84 07:33
DATA ACQUIRED 19-AUG-84 07:13

BS (IN)
6.0000 16.000
CALI(IN)
6.0000 16.000
SP (MV)
-100.0 0.0

TENS(LB)
10000. 0.0
DT (US/F)
175.00 75.000

FILE 9 19-AUG-84 07:31
DATA ACQUIRED 19-AUG-84 07:13



















FILE 9 19-AUG-84 07:27
DATA ACQUIRED 19-AUG-84 06:30

BS (IN)
6.0000 16.000
CALI(IN)
6.0000 16.000
SP (MV)
-100.0 0.0

TENS(LB)
10000. 0.0
DT (US/F)
175.00 75.000

SENSOR MEASURE POINT TO TOOL ZERO

CBL	43.9	FEET	AMPL	43.9	FEET
TT3	40.1	FEET	TT4	39.1	FEET
TT1	42.9	FEET	TT2	43.9	FEET
CALI	31.8	FEET	SRAT	41.4	FEET
SFL	6.4	FEET	ILD	9.4	FEET
SP	2.5	FEET	ILM	5.7	FEET
TENS	2.5	FEET	SPAR	2.5	FEET
NOIS	35.6	FEET			

PARAMETERS

NAME	VALUE	UNIT	NAME	VALUE	UNIT
WSV1	WF1		DWS	16	
DSIN	5	US	DDEL	200	US
CDTS	100.000		DWCO	512	
DTF	189.000	US/F	DTM	56.0000	US/F
SDR	1.00000	OHMM	DSEC	5.20000	MMHO
FPHI	SPHI		MSEC	6.40000	MMHO
BS	7.87500	IN	DHS	OPEN	
PP	NORM		DO	0.0	F

TAPE NOT MADE

BS (IN)
6.0000 16.000
CALI(IN)
6.0000 16.000
SP (MV)
-100.0 0.0

TENS(LB)
10000. 0.0
DT (US/F)
175.00 75.000

REPEAT SECTION

FILE 8 19-AUG-84 07:24
DATA ACQUIRED 19-AUG-84 06:26





FILE 8 19-AUG-84 07:24
DATA ACQUIRED 19-AUG-84 06:22

Curve	Left	Right
BS (IN)	6.0000	16.000
CALI(IN)	6.0000	16.000
SP (MV)	-100.0	0.0
TENS(LB)	10000.	0.0
DT (US/F)	175.00	75.000

SENSOR MEASURE POINT TO TOOL ZERO

CBL	43.9	FEET	AMPL	43.9	FEET
TT3	40.1	FEET	TT4	39.1	FEET
TT1	42.9	FEET	TT2	43.9	FEET
CALI	31.8	FEET	SRAT	41.4	FEET
SFL	6.4	FEET	ILD	9.4	FEET
SP	2.5	FEET	ILM	5.7	FEET
TENS	2.5	FEET	SPAR	2.5	FEET
NOIS	35.6	FEET			

PARAMETERS

NAME	VALUE	UNIT	NAME	VALUE	UNIT
WSV1	WF1		DWS	16	
DSIN	5	US	DDEL	200	US
CDTS	100.000		DWCO	512	
DTF	189.000	US/F	DTM	56.0000	US/F
SDR	1.00000	OHMM	DSEC	5.20000	MMHO
FPHI	SPHI		MSEC	6.40000	MMHO
BS	7.87500	IN	BHS	OPEN	
PP	NORM		DO	0.0	F

TAPE NOT MADE

BS (IN)
6.0000 16.000
CALI(IN)
6.0000 16.000
SP (MV)
-100.0 0.0

TENS(LB)
10000. 0.0
DT (US/F)
175.00 75.000

Sonic Check in Casing

FILE 5 19-AUG-84 07:26
DATA ACQUIRED 19-AUG-84 05:55



FILE 5 19-AUG-84 07:25
DATA ACQUIRED 19-AUG-84 05:53

BS (IN)
6.0000 16.000
CALI(IN)
6.0000 16.000
SP (MV)
-100.0 0.0

TENS(LB)
10000. 0.0
DT (US/F)
175.00 75.000

SENSOR MEASURE POINT TO TOOL ZERO

CBL	43.9	FEET	AMPL	43.9	FEET
TT3	40.1	FEET	TT4	39.1	FEET
TT1	42.9	FEET	TT2	43.9	FEET
CALI	31.8	FEET	SRAT	41.4	FEET
SFL	6.4	FEET	ILD	9.4	FEET
SP	2.5	FEET	ILM	5.7	FEET
TENS	2.5	FEET	SPAR	2.5	FEET
NOIS	35.6	FEET			

PARAMETERS

NAME	VALUE	UNIT	NAME	VALUE	UNIT
WSV1	WF1		DWS	16	
DSIN	5	US	DDEL	200	US
CDTS	100.000		DWCO	512	
DTF	189.000	US/F	DTM	56.0000	US/F
SDR	1.00000	OHMM	DSEC	5.20000	MMHO
FPHI	SPHI		MSEC	6.40000	MMHO
BS	7.87500	IN	BHS	OPEN	
PP	NORM		DO	0.0	F

TAPE NOT MADE

-END-