

WELL SUMMARY REPORT
 (Submit in duplicate)

RECEIVED
 SEP 21 1984

Operator Reichhold Energy Corporation Field Pittsburg
 Well No. CC 43-27 Sec. 27, T. 6N, R. 5W
 Location 478' S & 741' W of E 1/4 corner Elevation above sea level 898.54 feet
 All depth measurements taken from top of Kelly Bushing, which is 12.5 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date September 17, 1984 Signed Todd Thomas
 Title Field Operations Supervisor
 (President, Secretary or Agent)

Commenced drilling 8/14/84 Completed drilling 8/18/84 Drilling tools Cable Rotary
 Total depth 2441 Plugged depth _____ GEOLOGICAL MARKERS DEPTH
 Junk _____

Commenced producing awaiting pipeline hook-up Flowing/gas lift/pumping
 Date _____ (cross out unnecessary words)

Initial production
 Production after 30 days

Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure
			1.46MMCFD	665	640

CASING RECORD (Present Hole)

Size of casing (A.P.L.)	Depth of shoe	Top of casing	Weight of casing	New or second hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cementing if through perforations
8 5/8"	400	surf.	24#	new	seamless	K-55	12 1/4	200	--
5 1/2"	1799	surf.	15.5#	new	seamless	K-55	7 7/8	180	shoe-700'
2 3/8"	1624	surf.	4.7#	new	seamless	--	inside 5 1/2"	--	--

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
5 1/2"	1661 ft.	1668 ft.	1" hole	1	4 shots/foot	SSB II
5 1/2"	1675 ft.	1686 ft.	1" hole	1	4 shots/foot	SSB II
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				

Electrical Log Depths 2439' (Attach Copy of Log)