STATE OF OREGON JEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES 910 State Office Building Portland, OR 97201

WELL SUMMARY REPORT

(In compliance with rules and regulations pursuant to ORS 520)

		s Company	7		Caveni	am Forest	Indus	tries 🛭	41-4	
(Company or operator)						(Lease)			ell No.)	
Sec4	, T	5N	_, R	4W ·	_ W.B.& M. Si	ırveyed Coordi	nates: _			
SHL: 1095	5.50'S &	865.041	W of N	E Corne	r BHI	(RD #1):	164'	N & 268	B' E of SHL	
Wildcat:	(c	or) Field N	ame:	Mist		Co	unty:	Co1um	nbia	
Elevation of	ground above	sea level	is <u>88</u>	6 feet.	. All depth m	measurements a	re taken	from		
kelly	bushing			, whi	ich is	11'		abo	ove ground.	
,					C:	Living	uY)		
Date: Sar	120th,	, 1987				Dist. Drl			nden t	
Commenced dri	11ing:	9-10-86		Completed	drilling:	-17-86	P8	BA: <u>9-1</u>	8-86	
Total depth:	2584	1	Redrill	depth:	1935'		_			
Logs run:C	DH: DIL/B	HC/SP, FI	OC/CNL/	GR, Dipr	meter, Che	ck Shots	R	D: DIL/	BHC/SP	
	Size of	Size of Size of		in 1bs.	Grade		Amount of cement		7	
CASING RECORD	hole casing			ft.	Type	Depth				
		13-3/8'	' 6	8	K55 BTC	30'	Con	ductor		
		9-5/8'	36,	40 &	K55 STC/I	TC 441'	250 sx		_	
			5	3.5	L80 BTC				_	
		ļ							_	
						GEOLOG1	CAL MARK	ER	DEPTH	
Plugs <u>OH:</u>	2584 '	- 1672 ' (Mud)			Clark &	Wilson	n Sand	1684' TVD	
1672' - 1522' (Cement)					Plugs RD #1: 1935' - 498' (Mud)					
	647 ' -	- 608 ' (Cement)			498' -	- 385 '	(Cement)	
Junk Non	ie		, <u>.</u>	····			10'-	- Surfa	ce (Cement)	
r										
PERFORATIONS OR LINER	Size of casing	From		To	SH	Shots/ft.		Bullet	erforating Slotted Liner	
									STOCKE ETHER	
	N/A									
								· · · · · · · · · · · · · · · · · · ·		
}								·		
Į.		!				}			<u>. </u>	
INITIAL PRODUCTION	Date Clean Oil Gravity		Percent	Gas			S.1.	.I.T.P. S.I.C.P.		
		DD1/day	0.01107	Water	MMcf/day		F.C.P	_		
	N/A			<u> </u>			<u> </u>			
Form 4 (9/84)										