

RECEIVED-PTI

FEB 2 1982

DEPT OF GEOLOGY

COMPLETION REPORT

DIAMOND SHAMROCK CORPORATION

CROWN ZELLERBACH #11-28

Sec. 28, T. 5 N., R. 9 W.

CLATSOP COUNTY, OREGON

COMPLETION REPORT

WELL NAME: Diamond Shamrock Corporation
Crown Zellerbach #11-28

LOCATION: 1151 feet from the north line and 1143 feet from
west line
Sec. 28, T. 5 N., R. 9 W.
Clatsop County, Oregon

GROUND ELEVATION: 609 feet

KB ELEVATION: 618 feet

DRILLING RIG: Taylor Drilling Company Rig #4

DRILLING SUPERVISOR: Kelton Mann
Foy Boyd Associates, Inc.
Denver, Colorado

WELLSITE GEOLOGIST: Richard E. White
Consulting Geologist
Salem, Oregon

MUDLOGGERS: Michelle Miller
Ezekiel Carter
Tooke Engineering
Casper, Wyoming

SPUD DATE: May 19, 1981

DATE DRILLING COMPLETED: June 14, 1981

COMPLETION DATE: June 17, 1981 Plugged and abandoned

CASING: 9 5/8 inch set at 1011 feet

TOTAL DEPTH: 5700 feet

SAMPLES COLLECTED: All samples were caught by the mudloggers and
were lagged to compensate for circulation time.

One wet cut collected over 30-foot intervals from casing
point at 1011 feet to total depth was sent to Dan McKeel,
Lincoln City, Oregon for micropaleontologic evaluation.

One dry cut collected over 10-foot intervals from casing
point at 1011 feet to total depth was sent to Oregon
Department of Geology and Mineral Industries, Portland,
Oregon.

One set of canned samples was sent to Houston Oil and Minerals
Geology Lab, Houston, Texas for source rock analysis.

One dry cut collected over 10-foot intervals from casing point at 1011 feet to total depth was sent to Diamond Shamrock Corporation, Denver, Colorado.

TESTS: None

CORES: Sidewall cores were shot during logging run at T.D.

LOGS: Dual Induction--SFL--Sonic
Compensated Neutron--Formation Density
Dipmeter
Velocity Survey
Sidewall Cores