4-20-82

Tagged cement & release rig

STATE OF OREGON DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES 1069 State Office Building Portland 1, Oregon

HISTORY OF OIL OR GAS WELL (Submit in duplicate)

In compliance with rules and regulations adopted pursuant to ORS 520.095 (Chapter 667 OL 1953)

Mist REICHHOLD ENERGY CORPORATION Field 26 R. 4W 5N . Sec. W.B. & M. C.Z. 32-26 Well No. May 26, 1982 Title Drilling Superintendent (President, Secretary or Agent) Date It is of the greatest importance to have a complete history of the well. Use this form in reporting the history of all important operations at the well, together with the dates thereof, prior to the first production. Include in your report such information as size of hole drilled to cementing or landing depth of casings, number of sacks of cement used in the plugging, number of sacks or number of feet of cement drilled out of casing, depth at which cement plugs started, and depth at which hard cement encountered. If the well was dynamited, give date, size, position and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position and results of pumping or bailing. Date 3-27-82 Drilling 12½" surface hole Finished drilling surface hole to 772' 3-28-82 Ran 18 joints of 9 5/8" K-55 36# pipe to a depth of 746.95 as 3-29-82 measured from a 11.40 Kelly Bushing - cemented same with 300 sks class g cement - waiting on cement Waiting on cement, testing BOP's, drilling cement & guide shoe, 3-30-82 drilling 7 7/8" hole to 868' Drilling 7 7/8" hole to 1,392' 3-31-82 " 1,9211 4- 1-82 " 2,436' 4- 2**-**82 " 3,105' н 4- 3-82 н 4- 4-82 3.520' п 4- 5-82 4,005' п н 4- 6-82 4,333' 11 4,500' 4- 7-82 11 11 4,687' **4**- 8-82 ш П 4- 9-82 4.965 н 4-10-82 5.268' 11 4-11-82 5,655' It 5,885' 4-12-82 n 6,040' 4-13-82 4-14-82 6,208' п 6,443' 4-15-82 4-16-82 Shooting sidewall cores - running geotherm Plugging well - plugs set @ 6 0501 1- 1 0000 6,501' - Total Depth 4-17-82 4-18-82 Plugging well - plugs set @ 6,050' to 4,050', 4,830' to 4,630', 4-19-82 and 846' to 646' - used 195 sxs class g cement