

HISTORY OF OIL OR GAS WELL
(Submit in duplicate)

In compliance with rules and regulations adopted pursuant to ORS 520.095 (Chapter 667 OL 1953)

Operator Sinclair Oil & Gas Company Field Wildcat
Well No. 1 Eastern Oregon Land Co., Sec. 15, T. 16S R. 44E W.B. & M.
Signed *Henry W. DeYoung*
Date December 6, 1955 Title Senior Geologist
(President, Secretary or Agent)

It is of the greatest importance to have a complete history of the well. Use this form in reporting the history of all important operations at the well, together with the dates thereof, prior to the first production. Include in your report such information as size of hole drilled to cementing or landing depth of casings, number of sacks of cement used in the plugging, number of sacks or number of feet of cement drilled out of casing, depth at which cement plugs started, and depth at which hard cement encountered. If the well was dynamited, give date, size, position and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position and results of pumping or bailing.

Date

7-28-55 Spudded with Hughes GSC 13-3/4 in. bit.
7-29-55 478 ft., 10-3/4 in., 40.5 lb., new seamless surface csg. with 2 ft. shoe landed at 480 ft., and cemented with 220 sx. by Halliburton Oil Well Cementing Co.
7-31-55 Drilled out with Smith DT-2, 9-7/8 in. bit.
8-1-55 Baroid Well Logging Service begins logging at 800 ft.
8-21-55 Conventional Core. #1 3476-3493 ft. Recovered 17 ft. Twisted off at 3510 ft. with 4 drill collars in hole.
8-22-55 Recovered fish. Drilling ahead.
9-6-55 Conventional Core. #2 4863-4871 ft. Recovered 2 ft.
9-7-55 T.D. 4880 ft. Circulating. Waiting for Schlumberger.
9-8-55 Running Schlumberger Electrical Log, Microlog, Gamma Ray-Neutron Log. Maximum depth reached by Schlumberger 4889 ft.
9-9-55 Plugged with cement from 470 ft. to 500 ft. by Halliburton Oil Well Cementing Company. Abandoned.

Drilling Contractor: Colorado-Spoding Drilling Company, Denver, Colorado.
Days Drilling: 63
Bits Used: 34, including two core bits.
Drill Stem Tests: None.
Auxiliary Services: Baroid Well Logging Service;
Schlumberger Well Surveying Corporation;
Halliburton Oil Well Cementing Co.
Shows of Oil and/or Gas: None.
Deviation of Hole: Average deviation less than 1 degree;
maximum deviation 1 1/4 degree.

SCANNED