

DATE	DEPTH feet	WEIGHT lb/gal	VISCOSITY Sec API	PV cf	YE 10 sec/ 10 min	GELS 10 sec/ 10 min	pH	API	ml API	FILTRATION ml API	FILTRATION Cm 12hr	FILTRATION % 1hr	FILTRATE ANALYSIS			SAND %	RETURN Oil % Water %	CEC meq/ml	REMARKS AND TREATMENT
													Cl ppm	Ca ppm	Co ppm				
7/37	SPUD																		SPUD IN
7/4	130	8.9	36	10	4	2/17	8.5	N/C					50	TR 6	94			GEL/WATER	
7/5	280	8.9	36	8	4	12/31	8.5	16					50	TR 5	95				
7/6	480	8.9	36	10	3	6/24	8.5	16					50	TR 5	95				
7/7	650	8.9	37	11	3	5/23	8.5	17					50	TR 5	95			CASING DEPTH	
7/8	650	9.0	37	10	2	10/50	9.0	19					50	TR 6	94			REAM FOR CASING	
7/9	650	8.9	37	10	5	10/40	9.0	19					50	TR 5	95			DRILLING OUT CEMENT	
7/10	652	8.9	40	38	11	10/40	9.0	19					50	TR 5	95				
7/11	920	8.9	38	36	9	9/44	9.0	19					50	TR 5	95				
7/12	1083	8.9	39	11	2	10/40	9/0	20					50	TR 5	95			SWITCHING MUD OVER - BENEX	
7/13	1540	9.2	57	15	20	15/41	9.0	16.4					50	TR 5	95			SLOUGHING SHALE W/GAS	
7/14	1840	9.1	47	10	5	8/15	8.5	6.8					50	TR 6	94				
7/15	1870	9.9	65	20	26	25/40	8.5	18					50	TR 6	94			SLOUGHING SHALE RAISE WT	
7/16	2220	9.9	70	27	23	25/51	9	13					50	TR 9	91			REAMING	
7/17	2220	10.2	49	12	23	22/42	8.5	11					50	TR 9	91			REAMING	
7/18	2220	10.8	57	20	15	11/41	10.2	5.6					50	TR 10	90			DRILLING AHEAD	
7/19	2425	10.8	58	21	14	11/40	10.2	7					50	TR 10	90			PACKED OFF-REAM TO BOTTOM	
7/20	2505	10.8	47	23	12	10/37	10.8	5.1					60	TR 10	90				
7/21	2897	10.2	51	20	14	5/40	9.5	5.2					60	TR 7	93			PACKED OFF-COND FOR LOG	
7/22	3117	10.2	52	11	13	5/23	9.5	5.2					60	TR 9	91			REAMING TO BOTTOM-COND MUD	
7/23	3117	11.2	55	27	18	8/20	9.8	4.4					60	TR 8	92			PACKED OFF-FISH @ 2337'	
7/24	3117	10.8	50	27	18	4/17	10.2	1.2					60	TR 9	91			RAN LOGS 652'-2286'	