

WELL SUMMARY REPORT  
(Submit in duplicate)

Operator Reichhold Energy Corporation Field ---  
 Well No. NNG-Finn No. 1 Sec. 17, T. 6S, R. 4W, Polk Co. W. B. & M.  
 Location 1/431' N 1218' E of SW Cor. Sec. 17 Elevation above sea level 198 feet  
 All depth measurements taken from top of KB, which is 14 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date September 23, 1975Signed W. S. PattersonW. G. Bruer  
Engineer or GeologistH. C. Patterson  
SuperintendentTitle Engineer  
(President, Secretary or Agent)

Commenced drilling 8/26/75 Completed drilling 9/23/75 Drilling tools Cable Rotary  
 Total depth 7252' Plugged depth 5000'-4814'± GEOLOGICAL MARKERS DEPTH  
 Junk None 702'-486' Top Spencer Sand 600'±  
60'-18'

Commenced producing Abandoned Date                      Flowing/gas lift/pumping  
 (Cross out unnecessary words)

Initial production  
 Production after 30 days

| Clean oil<br>bbl per day | Gravity<br>Clean oil | Percent water<br>including<br>emulsion | Gas<br>Mcf per day | Tubing<br>Pressure | Casing<br>Pressure |
|--------------------------|----------------------|--|--------------------|--------------------|--------------------|
| Never produced.          |                      |  |                    |                    |                    |
|                          |                      |  |                    |                    |                    |

## CASING RECORD (Present Hole)

| Size of casing<br>(A.P.L.) | Depth of<br>shoe | Top of<br>casing | Weight of<br>casing | New or sec-<br>ond hand | Seamless<br>or Lapweld | Grade of<br>casing | Size of hole<br>drilled | No. of sacks<br>of cement | Depth of cement-<br>ing in through<br>perforations |
|----------------------------|------------------|------------------|---------------------|-------------------------|------------------------|--------------------|-------------------------|---------------------------|--|
| 9-5/8                      | 652              | 0                | 36                  | N                       | S                      | K                  | 13-3/4                  | 553 ft <sup>3</sup>       |  |
|                            |                  |                  |                     |                         |                        |                    |                         |                           |  |
|                            |                  |                  |                     |                         |                        |                    |                         |                           |  |
|                            |                  |                  |                     |                         |                        |                    |                         |                           |  |

## PERFORATIONS

| Size of casing | From | To  | Size of perforations | Number<br>of rows | Distance<br>between centers | Method of perforations |
|----------------|------|-----|----------------------|-------------------|-----------------------------|------------------------|
| None           | ft.  | ft. |                      |                   |                             |                        |
|                | ft.  | ft. |                      |                   |                             |                        |
|                | ft.  | ft. |                      |                   |                             |                        |
|                | ft.  | ft. |                      |                   |                             |                        |
|                | ft.  | ft. |                      |                   |                             |                        |