

STATE OF OREGON
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES
1069 State Office Building Portland 1, Oregon

HISTORY OF OIL OR GAS WELL
(Submit in duplicate)

Permit No. 47

In compliance with rules and regulations adopted pursuant to ORS 520.095 (Chapter 667 OL 1953)

Operator RUMBLE OIL & REFINING CO. Field Silverton Hills Area
Well No. Francis E. Wicks et ux No. 1, Sec. 11 , T. 7-S R. 1-E W. B. & M.

Signed

Date August 14, 1962

Title

(President, Secretary or Agent)

It is of the greatest importance to have a complete history of the well. Use this form in reporting the history of all important operations at the well, together with the dates thereof, prior to the first production. Include in your report such information as size of hole drilled to cementing or landing depth of casings, number of sacks of cement used in the plugging, number of sacks or number of feet of cement drilled out of casing, depth at which cement plugs started, and depth at which hard cement encountered. If the well was dynamited, give date, size, position and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position and results of pumping or bailing.

Date

Started rigging up 6/16/62. Spudded at 8:00 a.m. 6/18/62. Drilled 15" hole to 893' and 9-7/8" hole to 1165'. Ran 20 joints, 10-3/4", 40.57, J-55 casing and set at 883' using 475 sacks Class A cement with 8% gel after running electric log to 1165'. A 9-7/8" hole was drilled to the total depth of 7797' without encountering any shows of oil or gas. Two cores were taken, one from 6599-6601' and one, 7790-7797'. Plug No. 1 was placed at 876' using 50 sacks of cement. Plug No. 2 was placed with the top at 858' using 25 sacks of cement. The placement, location and hardness of the plug was witnessed by Mr. V. C. Newton, Jr., State representative. The casing was cut off 6 feet below ground level and 1/4" steel plate was welded on top of casing. No casing was pulled from the hole.