

RECEIVED-PTLD  
JUN 18 1984

DEPT. OF GEOLOGY  
& MINERAL INDUS.

WELL SUMMARY REPORT  
(Submit in duplicate)

Operator Selmar A. Hutchins & Mayo Marrs Field Wildcat

Well No. Glory Hole #1 Sec. 10, T 27 S, R 7 W, W.M. Douglas Co. W. B. & M.

Location From NW Corner 922ft east & 756ft South Elevation above sea level 715 feet

All depth measurements taken from top of drilling table, which is 8 feet feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date 3-21-84

Signed Mayo Marrs

Engineer or Geologist \_\_\_\_\_ Superintendent \_\_\_\_\_

Title Partner  
(President, Secretary or Agent)

Commenced drilling 10-27-83 Completed drilling 11-17-83 Drilling tools Rotary

Total depth 2980 Plugged depth top 450 ft GEOLOGICAL MARKERS \_\_\_\_\_ DEPTH \_\_\_\_\_

Junk Cement from 450' - 15'

Plugged & abandoned - Feb. 28-84

Commenced producing \_\_\_\_\_ Date \_\_\_\_\_ Flowing/gas lift/pumping (cross out unnecessary words)

Initial production  
Production after 30 days

Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure

CASING RECORD (Present Hole)

Size of casing (A.P.L.)	Depth of shoe	Top of casing	Weight of casing	New or second hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cementing if through perforations
<u>8 5/8</u>	<u>403</u>	<u>Surface</u>	<u>24</u>	<u>New</u>	<u>Seamless</u>	<u>K-40</u>	<u>12 3/4</u>	<u>275</u>	

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				