

RESTRICTION
LIFTEDLOG AND CORE RECORD OF OIL OR GAS WELL
(Submit in duplicate)

In compliance with rules and regulations pursuant to ORS 520.095 (Chapter 667 OL 1953).

Operator Standard Oil Company of California Field Wildcat
Well No. Hoagland Unit #1, Sec. 11, T. 7 N, R. 10 W, W. B. & M.

FORMATIONS PENETRATED BY WELL

Depth to		Thickness	Drilled or Cored (In Feet)	Recovery	Description
Top of Formation	Bottom of Formation				
50'	4900'	4850'	719-734 988-1000 1083-1100 1297-1307 1512-22 1727-37 1971-81 2188-2198 2408-18 2653-63 2904-14 3143-53 3393-3400 3455-65 3652-62 3844-54 4087-97 4328-38 4338-48 4583-87 4790-95	15' 12' 17' 10' 10' 10' 10' 10' 10' 10' 10' 10' 10' 7' 15' 4' 8' 10' N.R. 10' N.R. 5'	Thinly interbedded sandy siltstones and claystones.
4900'	5380'	480'	5048-58 5357-64	10' 4'	Volcanics.
5380'	5600'	220'	5388-98 5464-71	10' 6'	Thinly interbedded claystone and siltstone with some silty sandstone.
5600'	7101'	1501'	5772-81 6269-81 6410-20	8' 4' 10'	Volcanics.
			end of log		