

STATE OF OREGON  
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES  
1069 State Office Building                      Portland 1, Oregon

LOG AND CORE RECORD OF OIL OR GAS WELL  
(Submit in duplicate)

In compliance with rules and regulations pursuant to ORS 520.095 (Chapter 667 OL 1953).

Operator Mobil Oil Corp. Field Wildcat  
Well No. Ira Baker #1, Sec. 28, T. 15S, R. 3W, W. B. & M.

FORMATIONS PENETRATED BY WELL

Depth to		Thickness	Drilled or Cored	Recovery	Description
Top of Formation	Bottom of Formation				
670	1,120	450	Drilled	-	Poorly consolidated sandstone, sand, minor clay
1,120	1,625	505	Drilled	-	Tuff, tuffaceous sandstone, minor basaltic sand, minor lignite.
1,625	1,740	115	Drilled	-	Muddy siltstone
1,740	1,810	70	Drilled	-	Muddy sandy pebble conglomerate
1,810	2,000	190	Drilled	-	Clay, tuff, sandstone
2,000	2,785	785	Drilled	-	Tuff, basalt, conglomeratic mudstone
2,785	2,798	13	Cored	12	Conglomeratic mudstone
2,798	2,820	22	Drilled	-	Conglomeratic mudstone
2,820	4,210	1,390	Drilled	-	Basalt, mudstone, sandy mudstone, tuff
4,210	4,850	640	Drilled	-	Tuff
4,850	5,650	800	Drilled	-	Andesite
5,650	5,664	14	Drilled	-	Volcanic microbreccia
5,664	5,669	5	Cored	5	Volcanic microbreccia
5,669	6,460	791	Drilled	-	Volcanic microbreccia, tuff
6,460	6,695	235	Drilled	-	Diorite
6,695	8,690	1,995	Drilled	-	Volcanic microbreccia, claystone, mudstone, minor basalt
8,690	9,280	590	Drilled	-	Sandy siltstone, clayey siltstone, tuff andesite, minor sandstone
9,280	9,810	530	Drilled	-	Sandstone, siltstone, claystone
9,810	9,885	75	Drilled	-	Basalt
9,885	10,359	474	Drilled	-	Claystone, siltstone, sandstone, minor basalt
10,359	10,412	53	Cored	53	Sandstone, siltstone