

CONFIDENTIAL

STATE OF OREGON
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES
1069 State Office Building Portland 1, Oregon

PLUGGING RECORD

The owner or operator of any oil or gas well or stratigraphic hole shall file this form with the Director of the State of Oregon Department of Geology and Mineral Industries setting forth in detail the method used in plugging such well. The form must be filed within twenty (20) days after plugging for oil and gas wells, or within sixty (60) days for stratigraphic holes.

Rule L of rules and regulations adopted pursuant to ORS 520.095 (1) (13) (Chapter 667 OL 1953)

Operator STANDARD OIL CO. OF CALIFORNIA Field Wildcat
Pool _____
County Gilliam

ADDRESS ALL CORRESPONDENCE CONCERNING THIS FORM TO:

Street 557 Roy St. (Rm. 250) City Seattle 9 State Washington

Lease Name Kirkpatrick Well No. 1 Sec. 6 T. 4S R. 21E

Date well was plugged June 21, 1957.


Was the well filled with mud laden fluid, according to regulations of the Board of the State of Oregon Department of Geology and Mineral Industries? Yes

How was the mud applied? Left in hole Were plugs used? No If so, show all shoulders left for casing, depth of each, and size of casing, size and kind of plugs used, and depths placed. Also amount of cement and rock. Use additional sheets if necessary.

Was notice given, before plugging, to all available adjoining lease and land owners? Yes

STANDARD OIL COMPANY OF CALIFORNIA
(Operator)

AFFIDAVIT



State of WASHINGTON

County of KING

Before me, the undersigned authority, on this day personally appeared D. D. Hastings known to me to be the person whose name is subscribed to the above instrument, who being by me duly sworn on oath state that he is authorized to make this report and has knowledge of the facts stated herein and that said report is true and correct.

Subscribed and sworn to before me this 9th day of July 1957

Notary public in and for Merton C. Johnson
State of Washington

My commission expires March 28, 1961

State Department of Geology and Mineral Industries

1069 State Office Building
Portland 1, Oregon

RECEIVED
JUL 5 1957
STATE DEPT. OF GEOLOGY
& MINERAL INDS.

Plugging of Kirkpatrick No. 1 Well - permit no. 23.

Location: T. 4S, R. 21 #., Sec. 6, Condon Area.

Operator: Standard Oil Company of California

General: The writer was present at the well site on June 21, 1957 when a cement plug was placed in the hole by the Haliburton Company. A slurry was made from 150 bags of cement and pumped down the drill pipe to a depth of 2000 feet. According to Mr. Ferguson this should fill the interval between approximately 2000 feet and 1660 feet.

The following day after the plug had set, the drill mud above the plug was to be displaced with fresh water and a steel plate is to be welded over the surface casing before the well is abandoned. Because the land owner, Mr. Kirkpatrick, wishes to use the hole as a water well and has obtained a permit to do so, no surface plug was emplaced.

According to information received from Mr. Webb at the time of visit the total depth of the hole is 8726 feet. The upper 205 feet of the hole is 17 inches in diameter and is cased with 13 3/8 inch O.D. pipe. The interim is filled with cement. Below 205 feet the hole is 9 7/8 inches in diameter and is not cased but is filled with heavy drill mud below the above mentioned plug.

Examination by: Howard C. Brooks, June 21, 1957.

Informants: George Webb, Standard Oil Geologist and A.O. Ferguson, Standard Oil Drill Foreman.

Report by: Howard C. Brooks, June 24, 1957.