

RESTRICTED
CONFIDENTIAL

WELL SUMMARY REPORT
(Submit in duplicate)

Operator Standard Oil Co. of California Field Wildcat
Well No. Kirkpatrick #1 Sec. 6, T. 4S, R. 21E, W. B. & M.
Location 4319' W & 2909' S from NE corner Elevation above sea level 2747' ± USGS feet
All depth measurements taken from top of Derrick Floor, which is 10' feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date July 1, 1957 Signed D. D. Hastings
D. D. HASTINGS
Title Division Exploration Supervisor
(President, Secretary or Agent)

Engineer or Geologist Superintendent

Commenced drilling January 31, 1957 Completed drilling June 22, 1957 Drilling tools Cable Rotary
Total depth 8726' Plugged depth 1655' GEOLOGICAL MARKERS DEPTH
Junk None Basalt Flows 0'-2439'
Tuffs 2439'-3200'
Tuffs, Flows & Agglomerates 3200'-6700'
Marine Sediments w/interbedded Tuffs 6700'-8726'

Commenced producing _____ Date _____ Flowing/gas lift/pumping (cross out unnecessary words)

	Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure
Initial production						
Production after 30 days						

CASING RECORD (Present Hole)

Size of casing (A.P.L.)	Depth of shoe	Top of casing	Weight of casing	New or second hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cementing if through perforations
18 1/2"	22'	-5'	--	Second	Lapweld	--	30"	3 cu. yds.	--
13-3/8"	205'	-4'	54.5#	New	Seamless	J55	17 1/2"	185	--

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				