STATE OF OREGON F. CIMENT OF GEOLOGY AND MINERAL INDUSTR. 910 State Office Building Portland, OR 97201

WELL SUMMARY REPORT

(In compliance with rules and regulations pursuant to ORS 520)

	Nahama & We	eagant Energy	Company Lone	gview Fibr	e	12A-33-	-75
(Company or	Operator)		(Lea	ase)		(Well	1 No)
Sec. <u>33</u>	. т <u>7N</u> , в	Surveye	d Coordinates (i	f directions	1. BHT. & S	HL): SHL: 176	53'S & 705'F
from	the Northw	vest corner of	Sec. 33 BH	L: 378.32	' N & 150	5.91 E from S	SHL
		Field Name:	st			Columbia	
				Signature:	Zu	A R. Posen	1-1
Date: Aug	just 18, 19	93		Positio	. Vice	President Op	perations
			-	1087010		-	
Commended d	rilling: 5,	/21/93	Completed	drilling:	5/28/93	P&A	
Total depth	: 2475'	F	Redrill depth:			Tun	
Logs run: _	DIL-Sonic	2735! - 488'	CET-Neutron-	CCL 2326'	-800'	·	
	Size of	Size of	Wt. in 1h	s. Gra	do		Amount of cement
CASING RECORD	hole	casing	per ft.	Tyr		Depth	
	12 1/4"	8 5/8"	24#	.]_	55, ST&C	4961	225 sx.
	7 7/8"	4 1/2"	10.5 "				223 SX.
	7 7/8	4 1/2	10.5 #	J-	55, ST&C	2389'	200 sx.
			1				
	<u> </u>						
				 			
lugs			Ge	ological Mar	ker		Depth
					 ·		
unk ———	<u></u>						
				Ţ <u></u>			
Size of Method of Perform						forating	
Perforat.	ca	sing From	To	Shots/f	t. Je	t Bullet	Slotted Line
or or or a contract.	4	1/2" 2150		4-SPF	- x		The state of the s
Liner		1/2" 2164 1/2" 2222		4-SPF	X		
	-	1/2 / 222	2' 2240'	4-SPF	Х		
				<u>,.</u>	<u> </u>		<u> </u>
		Gas			<u></u>		
	Dat	XXXXXXXXXXXXXX	Gravity	Percent Water	F.T.P.	F.C.P. S.I	.T.P. S.I.C.P.
nitial roduction	7/20)/93 798			505	415	
	/II . -			l		<u> </u>	