STATE OF OREGON MENT OF GEOLOGY AND MINERAL IND Portland 1, Oregon

1069 State Office Building

PLUGGING RECORD The owner or operator of any oil or gas well or stratigraphic hole shall file this form with the Director of the State of Oregon Department of Geology and Mineral Industries setting forth in detail the method used in plugging such well. The form must be filed within twenty (20) days after plugging for oil and gas wells, or within sixty (60) days for stratigraphic holes. Rule L of rules and regulations adopted pursuant to ORS 520.095 (1) (13) (Chapter 667 OL 1953) Operator R. F. Harrison Field __ Hay Creek Anticline Jefferson ADDRESS ALL CORRESPONDENCE CONCERNING THIS FORM TO: Street 4710 University Way N. E. City Seattle State <u>Washington</u> Well No. <u>1-D</u> Sec. <u>18</u> T. 12 S R. 15 E Lease Name Morrow Ranch Date well was plugged August 9 _ 19<u>71</u> . Was the well filled with mud laden fluid, according to regulations of the Board of the State of Oregon Department of Geology and Mineral Industries? yes How was the mud applied? from surface ___ Were plugs used? yes If so, show all shoulders left for casing, depth of each, and size of casing, size and kind of plugs used, and depths placed. Also amount of cement and rock. Use additional sheets if necessary. Hole Condition: 8" surface casing cemented at 543" 7 5/8 hole from 543' to 3300' Lost circulation zone 600'; hole caving at 2000'-(See attached sheet for Water zone 400-500', low volume in Quaternary volcanics plugging details) Was notice given, before plugging, to all available adjoining lease and land owners? AFFIDAVIT State of County of ., being duly sworn, say that I have knowledge of the facts stated herein, that they are true and correct, and that I am authorized to make this report. Subscribed and sworn to before me this Notary public in and for R. F. Harrison Morrow Ranch #1-D August 19, 1971 PLUGGING DETAILS 1. Ran in hole with 7 5/8 by 36" wood plug on wire line to 600'. Placed 1 sack of Diacel M and 1 sack of lime on top of plug. 20 sacks of cement were placed on the plug at 600'. Filled hole with heavy gel mud to surface. Placed a 4 sack cement plug at the top of the 8" casing. Cut 8" surfacing casing off 3 feet below ground level and welded a steel plate over the stub. Form 5 1/54 STATE OF OREGON MENT OF GEOLOGY AND MINERAL INDI RIES DEP DEEPENING 1069 State Office Building Portland 1, Oregon PLUGGING RECORD The owner or operator of any oil or gas well or stratigraphic hole shall file this form with the Director of the State of Oregon De-The owner or operator of any on or gas well or stratigraphic note shall the this form with the Director of the state of Oregon Department of Geology and Mineral Industries setting forth in detail the method used in plugging such well. The form must be filed partment of Geology and Mineral industries setting forth in detail the method used in plugging such well. within twenty (20) days after plugging for oil and gas wells, or within sixty (60) days for stratigraphic holes. Rule L of rules and regulations adopted pursuant to ORS 520.095 (1) (13) (Chapter 667 OL 1953) ADDRESS ALL CORRESPONDENCE CONCERNING THIS FORM TO: County_ 4710 University Way, N.E. City_ Lease Name Merrow Bros. -----Well No. Date well was plugged September 98105 Was the well filled with mud laden fluid, according to regulations of the Board of the State of Oregon Department of Geology and How was the mud applied? for casing, depth of each, and size of casing, size and kind of plugs used, and depths placed. Also amount of cement and rock. If so, show all shoulders left Condition of hole: 8" surface casing cemented at 543 feet. 7-5/8" hole drilled to 3300 feet. (See attached description of work done.) WEICHBIRDEK BINKEICK PROGRESCHEICHE STAND ZUR AN FERSTEINE GERFEN FAN GEFFER FAN GEFFER FAN GEFFER FAN GEFFER F AFFIDAVIT the facts stated herein, that they are true and correct, and that I am authorized to make this report. __, being duly sworn, say that I have knowledge of Subscribed and swom to before me this day of September

My commission expires

Notary public in and for