

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

5. LEASE DESIGNATION AND SERIAL NO.

P 072

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

9. WELL NO.

1ET

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Block 65 W 57 N

Oregon Map No. 1

12. COUNTY OR PARISH 13. STATE

Oregon

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL GAS WELL OTHER **Wildcat**

2. NAME OF OPERATOR
Shell Oil Company

3. ADDRESS OF OPERATOR
1008 West Sixth Street, Los Angeles, California 90054

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface

1258' FEL & 5927' FSL of P 072 Lease

14. PERMIT NO.

15. ELEVATIONS (Show whether BP, RT, OR, etc.)

R. T. 69' above MLLW. Water depth 469'

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

With 24" x 13 3/8" casing cemented at 630' with 450 sacks, 11 3/4" casing cemented at 2012', with 750 sacks, and 9 5/8" casing cemented at 5167' with 1000 sacks and hole subsequently sidetracked through window at 4996', and total depth of 8019'; the well was abandoned on March 14, 1966 in the following manner:

1. Circulated hole with 11 3/4" cf mud using rig pumps.
2. Set bridge plug at 4950' and pressure tested to 800 psi. Held OK. Placed 250 feet cement plug on top of bridge plug and tested OK with 1000 psi.
3. Cut 9 5/8" casing at 1000'. Spotted 75 sacks cement plug at 1450' and attempted to squeeze away 50 sacks cement with 2000 psi. Could not break down annulus between 9 5/8" and 11 3/4" casings.
4. Cut 9 5/8" casing at 576' (38' below ocean floor). Pressured to 2500 psi and pulled 375,000 lbs. but could not shear pile. Ran spear and recovered 9 5/8" casing. Attempted to shear off pile, pulled 450,000 lbs. with 100 psi on pump. Would not shear.

(Continued on next page)

18. I hereby certify that the foregoing is true and correct

SIGNED _____

TITLE _____

DATE _____

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY: