SCHLUMBERGER

BOREHOLE COMPENSATED SONIC LOG WITH CALIPER

OCS P-093

COUNTY OFFSHORE
FIELD or LOCATION NEWPORT
WELL GREBE NO. 1 DEEPENING OCS P 093
COMPANY UNION OIL CO.

COMPANY UNION OIL COMPANY OF CALIFORNIA
OCS-P-093 TERMINATED
WELL GREBE NO. 1 DEEPENING OCS P 093
FIELD NEWPORT
COUNTY OFFSHORE STATE OREGON
LOCATION X=978,928 Y=327,172
Sec. Twp. Rge.
Other Services:

Permanent Datum: MLLW, Elev. 0
Log Measured From RT, 68 Ft. Above Perm. Datum
Drilling Measured From RT
Elev.: RT 68, D.F., G.L. 0

Date	10-2-66	10-10-66
Run No.	FOUR	FIVE
Depth—Driller	9050	9520
Depth—Logger	8953	9525
Btm. Log Interval	8950	9524
Top Log Interval	5616	8950
Casing—Driller	7 5/8 @ 5613	7 5/8 @ 5613
Casing—Logger	5616	
Bit Size	6 3/4	6 3/4
Type Fluid in Hole	LIGNO SULFONATE	LIGNO SULFANATE
Dens. / Visc.	116 / 77	114 / 53
pH / Fluid Loss	9.5 / 2.5 ml	10.5 / 2.7 ml
Source of Sample	CIRCULATED	CIRCULATED
R_m @ Meas. Temp.	0.47 @ 80 °F	0.51 @ 79 °F
R_{mf} @ Meas. Temp.	0.25 @ 71 °F	0.25 @ 79 °F
R_{mc} @ Meas. Temp.	0.74 @ 71 °F	0.75 @ 79 °F
Source: R_{mf} / R_{mc}	M / M	M / M
R_m @ BHT	0.20 @ 183 °F	0.19 @ 192 °F
Time Since Circ.	10 HR.	10 HR.
Max. Rec. Temp.	183 °F	192 °F
Equip. / Location	C60 / SAC	C60 / SAC
Recorded By	HALL	ANDERSEN
Witnessed By	BRATSLIN	BTEENAN

GEOLOGICAL SURVEY RECEIVED NOV 2 1966 LOS ANGELES

NOTED NOV 3 1966

NOTED NOV 7 1966

NOTED - LAVELLE

FOLD HERE

REMARKS

Changes in Mud Type or Additional Samples		
Date / Sample No.		
Depth—Driller		
Type Fluid in Hole		
Dens. / Visc.		
ph / Fluid Loss	ml	
Source of Sample		
R_m @ Meas. Temp.	@ °F	@ °F
R_{mf} @ Meas. Temp.	@ °F	@ °F
R_{mc} @ Meas. Temp.	@ °F	@ °F
Source: R_{mf} / R_{mc}		
R_m @ BHT	@ °F	@ °F
R_{mf} @ BHT	@ °F	@ °F
R_{mc} @ BHT	@ °F	@ °F

Scale Changes

Type Log	Depth	Scale Up Hole	Scale Down Hole

Equipment Data

Run No.	Tool Type	Tool Position	Other
FOUR	BSL	CENTERED	
FIVE	BSL	CENTERED	

C.D.: USED S.O.:	CENTERED	CENTERED
Equip. Used: CART. No.	SLC-A 94	SLC-A 94
PANEL No.	SLP-A 89	SLP-A 89
SONDE No.	SLS-A 179	SLS-A 179

$$\text{Velocity (feet per second)} = \frac{1{,}000{,}000}{\text{Interval Transit Time (microseconds per foot)}}$$

SPONTANEOUS-POTENTIAL MILLIVOLTS — 10 — + | DEPTHS | INTERVAL TRANSIT TIME MICROSECONDS PER FOOT $T_3R_12R_2$ 150 — 50; 250 — 150

CALIPER HOLE DIAM. IN INCHES 5" — 15"

5" — 15" CALIPER HOLE DIAM. IN INCHES

10 — +

$T_3R_12R_2$ 150 — 50; 250 — 150

SPONTANEOUS-POTENTIAL MILLIVOLTS | DEPTHS | INTERVAL TRANSIT TIME MICROSECONDS PER FOOT

COMPANY UNION OIL COMPANY OF CALIFORNIA
WELL GREBE NO. 1 DEEPENING OCS P 093
FIELD NEWPORT
COUNTY OFFSHORE STATE OREGON

SWSC FR 9524
SWSC TD 9525
DRLR TD 9520
Elev: RT 68, DF, GL 0

CALIBRATION DATA



CALIBRATION DATA

COMPANY UNION OIL COMPANY OF CALIFORNIA
WELL GREBE NO. 1 DEEPENING OCS P 093
FIELD NEWPORT
COUNTY OFFSHORE STATE OREGON
SWSC FR 9524
SWSC TD 9525
DRLR TD 9520
Elev: RT 68, DF, GL 0