

LOG AND CORE RECORD OF OIL OR GAS WELL  
 (Submit in duplicate)

In compliance with rules and regulations pursuant to ORS 520.095 (Chapter 667 OL 1953).

Operator Standard Oil Company of California Field Wildcat

Well No. Pexco State #1, Sec. 36, T. 20S, R. 20E, W. B. & M.

FORMATIONS PENETRATED BY WELL

Depth to Top of Formation	Depth to Bottom of Formation	Thickness	Drilled or Cored in feet	Recovery	Description
Surface	7594'	7594'	1266'-76'	2"	Tuff, hard, dense, gray.
			3226'-33'	7'	" " " 5° Dips.
			4518'-33'	15'	Agglomerate, dense, 5° Dips.
			5394'-5404'	7'	Tuffaceous claystone, very firm, gray.
			5989'-6002'	3'	Claystone w. some limey nodules.
			6044'-51'	1'	Siliceous claystone, hard, dense, dark green
			6121'-28'	6"	As last above
			6695'-6711'	15'	As last above w. some chert
			6916'-36'	20'	As second above
			6936'-56'	20'	As last above
			7039'-51'	12'	As last above w. some calcite filled fractures
			7170'-88'	6"	Very siliceous tuff, dark green, dense
			7349'-54'	5'	Siliceous tuffs, dark green, dense
			7354'-65'	9'	As last above
			7365'-73'	8'	" " "
			7378'-86'	8'	" " "
			7584'-94'	7'	" " "

(Surface to 7594' Lithologic Log and brief descriptions attached)