

STATE OF OREGON  
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES  
1069 State Office Building, Portland 1, Oregon

WELL SUMMARY REPORT  
(Submit in duplicate)

Operator Oregon Oil & Gas Co. Field Nashville  
Well No. Roberts 1 NE 1/4 Sec. 25, T 10S, R 8W, WM W. B. & M.  
Location 1683'S & 1833'W from NE cor. Elevation above sea level 400' +        feet  
All depth measurements taken from top of       , which is        feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date        Signed A.M. Ropp  
Engineer or Geologist        Superintendent        Title President  
       (President, Secretary or Agent)

Commenced drilling Aug. 6, 1959 Completed drilling May 24, 1960 Drilling tools Cable Rotary  
Total depth 2630' Plugged depth 0 GEOLOGICAL MARKERS DEPTH  
Junk        Tyre Em. 0-350'  
       Kings Valley Siltst 350-960'  
       Siletz River Volcs 960-2630'

Commenced producing        Date        Flowing/gas lift/pumping  
(cross out unnecessary words)

	Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure
Initial production						
Production after 30 days						

CASING RECORD (Present Hole)

Size of casing ( A.P.L )	Depth of shoe	Top of casing	Weight of casing	New or sec- ond hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cement- ing if through perforations
<u>8 5/8"</u>	<u>168'</u>	<u>0</u>			<u>Smless</u>		<u>12 1/4"</u>	<u>100Sacks</u>	<u>Around shoe</u>

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				

Electrical Log Depths 2569' (Attach Copy of Log)