


APPLICATION FOR PERMIT TO DRILL NEW WELL OR STRATIGRAPHIC HOLE
(To be accompanied by a \$25.00 permit fee for new wells only and a surety bond conditioned as provided by law.)

Albany Oregon Feb. 27 1958

Department of Geology and Mineral Industries
Portland, Oregon

In compliance with rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) application is hereby made for permit to drill

a (new well) to be known as: Marion-Turner
(Stratigraphic Hole)
Well No. 7 in of Sec. 22, T. 9S, R. 21 W. B. & M.,
15 Field, Marion County.



This well is 50 feet (N) (9) of the South line and 330 feet
(E) (W) of the East line of Section 22.
(Give location from section or other legal subdivision lines or corners. Cross out wrong directions)

Elevation of ground above sea level is 355 feet. All depth measurements are taken from
top of Ground, which is even feet above ground.

The lessee is V V Erntson
Address 745 W 30th Albany, Oregon

The lessor is W G & Dora Schermerhorn
Address Box 55 Rt 1 Turner, Oregon

LOCATE WELL CORRECTLY

We estimate that the first productive oil or gas sand should occur at a depth of about 900 feet.
We propose to use the following strings of casing and to land or cement them as herein indicated:

| Size of hole | Size of casing | Weight in pounds per foot | Grade and type | New or second hand | Depth | Landed or cemented No. sacks cement |
|--------------|----------------|---------------------------|----------------|--------------------|-------|-------------------------------------|
| 10 | 10 | | Std | New | Rock | as needed |
| 6 | 6 | | Std | New | 900 | as needed |
| | | | | | | |

We propose to drill with rotary tools.

If changes in the above plan become advisable we will notify you before cementing or landing casing.

Additional information including names of and expected depths to objective sands (Use additional sheets as needed):

I understand that this plan of work must receive approval in writing by the Director of the State Department of Geology and Mineral Industries.

Approved March 4, 1958
except as follows: (1) a surveyed location must be submitted within sixty days, and (2) 100 feet of surface casing must be cemented in with cement around shoe.
DEPARTMENT OF GEOLOGY & MINERAL INDUSTRIES
By [Signature] Director

V V Erntson
COMPANY OR OPERATOR
By [Signature]
Position [Signature]
Send communications regarding well to:
Name V V Erntson
Address 745 W 30th Albany, Oregon

(Submit in triplicate)