

WELL SUMMARY REPORT  
(Submit in duplicate)

Operator V. V. Erntson Field Marion area  
Well No. Schermacher No. 1 Sec. 27, T 9 S, R 2 W, W.M. W. B. & M.  
Location 264.4 feet south and 345.3 feet west from the NE corner. Elevation above sea level 322 feet  
All depth measurements taken from top of Rotary table, which is 8.0 feet above ground  
In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.  
Date \_\_\_\_\_ Signed A.M. Ropp by V.C. Newton  
Engineer or Geologist A. M. Ropp Title Superintendent  
Superintendent (President, Secretary or Agent)

Commenced drilling April 17, 1958 Completed drilling January 14, 1959 Drilling tools Cable Rotary  
Total depth 2426 feet Plugged depth 190 feet GEOLOGICAL MARKERS DEPTH  
Junk Surface gravel 0' - 190'  
Volcanics 190' - 720'  
Marine sediments ? 720' - 2426'

Commenced producing Dry hole Date \_\_\_\_\_ Flowing/gas lift/pumping (cross out unnecessary words)

	Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure
Initial production						
Production after 30 days						

CASING RECORD (Present Hole)

Size of casing (A.P.L)	Depth of shoe	Top of casing	Weight of casing	New or second hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cementing if through perforations
8"	220'	Surface	25#	New (line pipe)			8"	5	---

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				

Electrical Log Depths 0-2426 feet T.D. (Attach Copy of Log)

WELL SUMMARY REPORT  
(Submit in duplicate)

Operator V.V. Erntson Field Turner Area  
Well No. Schermacher 1 Sec. SE 1/4 Sec. 22 27, T 9 S, R 2 W, WM W. B. & M.  
Location 50' N & 330' W from SE cor. Elevation above sea level 90' feet  
All depth measurements taken from top of \_\_\_\_\_, which is \_\_\_\_\_ feet above ground  
In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.  
Date Jan. 26, 1959 Signed V.V. Erntson  
Engineer or Geologist A.M. Ropp Title Operator  
Superintendent (President, Secretary or Agent)

Commenced drilling June 30, 1958 Completed drilling Jan. 14, 1959 Drilling tools Cable Rotary  
Total depth 2426' Plugged depth 0 GEOLOGICAL MARKERS DEPTH  
Junk Quat - Gravel 0-190'  
Stayton Lava 190'-730'  
Eugene Fm. 730'-2030'  
Spencer Fm. 2030'-2426'

Commenced producing \_\_\_\_\_ Date \_\_\_\_\_ Flowing/gas lift/pumping (cross out unnecessary words)

	Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure
Initial production						
Production after 30 days						

CASING RECORD (Present Hole)

Size of casing (A.P.L)	Depth of shoe	Top of casing	Weight of casing	New or second hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cementing if through perforations
8"	220'	0						?	

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				

Electrical Log Depths 2426' (Attach Copy of Log)