

PLUGGING RECORD

(In compliance with rules and regulations pursuant to ORS 520, this form must be submitted within 60 days after plugging.)

DAMON PETROLEUM COMPANY, INC. Stauffer Farms, Inc. 35-1
(Company or operator) (Lease) (Well No.)
Sec. 35, T. 4S R. 1W W.B.&M. Surveyed Coordinates: _____
1100' South & 625' East From NW Corner of Sec. 35
Wildcat: X (or) Field Name: Hubbard Area County: Marion

Date well was plugged: September 10, 19 87.

The interval between plugs shall be filled with a heavy mud-laden fluid. Was the well filled with mud-laden fluid as required? Yes How was the mud applied? Circulated through drill pipe

Please furnish the following information:

CASING: (1) Size (2) Weight (3) Depths set PLUGS: (1) Type (2) Depth/interval (3) Amount of cement

8 5/8" 24# 342' Cement 270'-380' 35 Sax

Top of cement plug witnessed and approved by DOGAMI

8 5/8" 24# Casing Cemented around the shoe with 225 sax of Type H Construction Cement, Float collar at 322'.

AFFIDAVIT

STATE OF OREGON
County of MARION } ss.

I, Robert W. Montgomery, being first duly sworn, depose and say that I have knowledge (Type or print operator's representative) of the facts stated herein, that they are true and correct, and that I am authorized to make this report.

Signature: Robert W. Montgomery
Position: PRESIDENT

Subscribed and sworn to before me this 8th day of October, 19 87

Signature: Johy Woodley
Notary Public for State of Oregon

My commission expires 4-7-90