

MISCELLANEOUS NOTICES AND REPORTS ON WELLS AND STRATIGRAPHIC HOLES
(Submit in triplicate)

This is a combined form, use only portions pertinent to your needs.

To comply with rules and regulations adopted pursuant to ORS 520 (Chapter 667 OL 1953).

Notices		Reports	
Indicate nature of notice by checking below:		Indicate nature of report by checking below:	
Notice of intention to plug well		Report on plugging well (use form 5)	X
Notice of intention to make formation test		Report on making formation test	
Notice of intention to make production test		Report on making production test	
Notice of intention to abandon well		Report on abandoning well	X
Notice of intention to test casing shut-off		Report on testing casing shut-off	
Notice of intention to redrill or deepen well		Report on redrilling or deepening well	
Notice of intention to shoot or chemically treat well		Report on shooting or chemically treating well	
Notice of intention to complete well		Report on completion of well	

Submit notices in triplicate before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Department or agent, of the plan submitted.

Submit reports in triplicate within 20 days after the work specified is completed.

Vale, Oregon, October 24, 1962

Department of Geology and Mineral Industries
Portland, Oregon

Following is a report on the work done and the results obtained at the Two States Oil & Gas Co
notice of intention to do certain work as described below Company or Operator
Vale City Well No. 1 in SW 1/4
Lease

of sec. 21, T. 18S, R. 45E, W.B. & M., Vale Area field,
Malheur County. The dates of this work were as follows: Oct 23 and 24, 1962.
by letter

Notice of intention to do the work was (was not) submitted on form on Oct 22 19 62
and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

The present condition of the well, including complete casing record, is as follows (Use additional sheets as needed):

16" casing at 200', cemented 100-0 with 50 sax constr. cement
12" casing at 560', driven, bentonite mud on outside
12" hole to 1185' T.D.

~~ATTACHED IS A COMPLETE DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED. THE ATTACHMENT~~
PROPOSED WORK

IS PART OF THIS NOTICE OR REPORT AND IS CONSIDERED COVERED BY THE AFFIDAVIT.

The hole was plugged from 20' to the surface with 15 sax of constr. cement on October 23, 1962. The hole was first bridged at 20'. Drilling fluid was left in the hole below the bridge plug. The sump was filled in on October 24, 1962 and the site cleaned up.

Last produced (date) (net oil) (gravity) (cut)
(Dry Hole)

Approved October 26 19 62
except as follows None
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES
By H.M. Dole, director
Director

Two States Oil & Gas Co, Inc
Company or operator
By
Position President
Send communications regarding well to
Name Maynard J. Davies, president
Address 6319 Randolph Drive
Boise, Idaho

by: AFFIDAVIT ON REVERSE SIDE FOR REPORTS
Petroleum Engineer