

STATE OF OREGON  
 DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES  
 1159 State Office Building, Portland 1, Oregon

WELL SUMMARY REPORT  
 (Submit in duplicate)

Operator American Quasar Petroleum Field Wildcat  
 Well No. Wetgen et al 26-32 Sec. 26, T. 13S, R. 4W, Linn County W. B. G. No.  
 Location 1980' FNL & 1980' FEL (SW $\frac{1}{4}$  NE $\frac{1}{4}$ ) Elevation above sea level 276.5 feet  
 All depth measurements taken from top of Kelly Bushing, which is 10.5 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 567 OR 1953) the information given herewith is a complete and correct record of the present condition of this well and all work done thereon, so far as can be determined from all available records.

Date 8/28/81 Signed John F. Works  
 Title Division Drlg. Engineer  
(President, Secretary, or Agent)

Commenced drilling 8/14/81 @ 11:00 pm Completed drilling 8/24/81 Drilling tools XXXX  
Rotary  
 Total depth 2620 Plugged depth 185 GEOLOGICAL MARKERS  
 Mark Spencer 1500  
Salt 1900  
Base Volcanics 2330

Commenced production Dry Hole Date                      Flowing (gas lift/pumping)  
(cross out unnecessary words)

Initial production	Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure
Production after 30 days						

CASING RECORD (Present Hole)

Size of casing (A.P.L.)	Depth of shoe	Top of casing	Weight of casing	New or sec- ond hand	Seamless or lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cement- ing if through perforations
14"	120'	Surf	Conductor						
7"	516'	Surf	20#	New	Seamless	K55	9-7/8"	225	Cmt'd to Surface

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				

Electrical Log Depths 2623'-516' (Attach Copy of Log)