MISCELLANEOUS NOTICES AND REPORTS ON WELLS AND STRATIGRA (Submit in triplicate)

This is a combined form, use only portions pertinent to your needs.

DEPT OF GEOLOGY & MINERAL INDUS

To comply with rules and regulations adopted pursuant to ORS 520 (Chapter 667 OL 1953).

Notices	Reports
Indicate nature of notice by checking below:	Indicate nature of report by checking below:
Native of intention to plug well	Report on plugging well (use form 5)
Private intention to make formation test Stiller of intention to make production test	Report on making formation test
Codice of intention to abandon well X	Report on making production test Report on abandoning well
Notice of intention to test easing shut-off	Report on testing casing shut-off
Protice of intention to redrill or deepen well-	Report on redrilling or deepening well
Notice of intention to shoot or chemically treat well	Report on shooting or chemically treating well
Notice of intention to complete well	Report on completion of well
Submit notices in triplicate before the work specified is to begin. \overline{A} copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Department or agent, of the plan submitted.	Submit reports in triplicate within 20 days after the work speci- fied is completed.
•	Bakersfield, Calif. May 19, 1980
Department of Geology and Mineral Industries Portland, Oregon	
Following to a PENOCKOR X DE X900 HOLD DE X010 K OB K DE NORTH CONTRACTOR OF THE CON	at the Reichhold Energy Corporation
notice of intention to do certain work as desc	ribed below Company or Operator
White	Well No. 33-13 in SE/4
	B & M., Mist field,
Columbia County.	The dates of this work were as follows:
Notice of intention to do the work was (was not) submitted on and approval of the proposed plan was (was not) obtained. (C	form on 19 Cross out incorrect words.)
The present condition of the well, including complete casing	·
	·
1. 7" 20# casing cemented at 407'	•
2. 6-1/4" hole drilled to 2708'.	
3. Top C&W sand 1895'. No gas sho	WS.
ATTITA CIVED TO A CONTROL TO THE CIVED TO TH	ሃጉ ፡፡፡፡ የ √ጌ/ጌኒየ √ለ-አየ/› √ ይወድ የተማዋድ √ ነ ደ ም ለተፈተደሙ
ATTACHED IS A COMPLETE DETAILED ACCOUNT OF P	CORNEX DONE AND XBESULTS XOB TAINED. THE ATTACHMENT
· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·
1. Hang drill pipe at 1925' and pur	RED COVERED BY THE AFFIDAVIT. mp in 40 sacks. Calculated to fill to 170
2. Hang drill pipe at 600' and pum	n in 70 sacks of cement
3. Top of Plug No. 2 will be locat	of at an above 750t
A Diversion 201 of 70 and in mile	ed at or above 550°.
4. Plug top 20' of /" casing with	cement. Cut off 7" casing 4' below
ground level.	
ast produced	
(date) Never (n	et oil) Produced (gravity) (cut)
Annauad	Reichhold Energy Corporation
Approved 19	Company or operator
except as follows:	1 Company of Operator
	By /1/.) Messerm
	Enginoor
	Position_Engineer
	Send communications regarding well to
CONTRACTOR OF CO	Name R. L. Beardsley
EPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES	Address P.O. Box 810
У	
Director	St. Helens, Oregon 97051