

November 6th. 1950

From	To	
0	38'	Gravel
38	74'	Shale & streaks of sand
74	346'	Lava (lost circulation)
346	372'	Hard Igneous rock
372	412'	Hard rock
412	457'	Sand (water flow started)
457	522'	Hard rock
522	548'	Sand (water sand)
548	583'	Lime & streaks of sand
583	659'	Lime & shale
659	675'	Shale & sand
675	692'	Hard rock
692	730'	Shale
730	1287'	Sand & shale
1287	1505'	Blue & red shale
1505	1870'	Shale
1870	2040'	Green & blue shale
2040	2162'	Brown & green shale
2162	2181'	Shale
2181	2194'	Hard sand
2194	2196'	Hard sand (cored) core no. 1
2196	2245'	Hard sand
2245	2316'	Sand & shale
2316	2495'	Shale
2495	2499'	Lime & Shale (cored) core no. 2
2499	2564'	Lime & shale
2564	2609'	Shale
2609	2699'	Shale & lime
		Total depth.

Copied from Drillers Log:

Plugged at 800 feet October 30th., 1950, with fifty sacks of cement  
 Plugged at top of surface casing on November 6th. 1950, with ten sacks  
 of drilling mud, wooden plug, and ten sacks of cement.

Signed by *I. W. Love*  
 Owner & operator