

STATE OF OREGON
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES
1069 State Office Building, Portland 1, Oregon

WELL SUMMARY REPORT
(Submit in duplicate)

Operator I. W. Love Field Hay Creek Ranch
Well No. Wickman 1 NE1/4 Sec. 27, T 11S, R 15E, WM W. B. & M.
Location _____ Elevation above sea level 2700' feet
All depth measurements taken from top of rotary table, which is 7.0' feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date Oct. 30, 1950 Signed I. W. Love
Title Operator
Engineer or Geologist _____ Superintendent _____
(President, Secretary or Agent)

Commenced drilling Aug. 1, 1950 Completed drilling Nov. 10, 1950 Drilling tools Cable Rotary
Total depth 2699' Plugged depth 0 GEOLOGICAL MARKERS DEPTH
Junk _____ John Day Fm. 0-74'
Clarno Fm. 74-2181'
Pre-Tertiary 2181-2699'

Commenced producing _____ Date _____ Flowing/gas lift/pumping (cross out unnecessary words)

	Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure
Initial production						
Production after 30 days						

CASING RECORD (Present Hole)

Size of casing (A.P.L.)	Depth of shoe	Top of casing	Weight of casing	New or second hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cementing if through perforations
<u>10 3/4"</u>	<u>200'</u>	<u>0</u>	<u>32</u>	<u>New</u>	<u>Smless</u>		<u>12 1/4"</u>	<u>100 Sacks</u>	<u>Around Shoe</u>

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				

Electrical Log Depths None (Attach Copy of Log)