Operator

Well No.

Date

## STATE OF OREGON DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES 1069 State Office Building Portland 1, Oregon

## HISTORY OF OIL OR GAS WELL

In compliance with rules and regulations adopted pursuant to ORS 520.095 (Chapter 667 OL 1953)

, Sec. 5

Reichhold Energy Corporation

Wilson Il-5

October 17, 1983

(Submit in duplicate)

Field

Title

It is of the greatest importance to have a complete history of the well. Use this form in reporting the history of all important operations at the well, together with the dates thereof, prior to the first production. Include in your report such information as size of hole drilled to cementing or landing depth of casings, number of sacks of cement used in the plugging, number of sacks or number of feet of cement drilled out of casing, depth at which cement plugs started, and depth at which hard cement encountered. If the well was dynamited, give date, size, position and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position and results of pumping or bailing.

Mist

6N

, T.

5₩

Williamson

Field Operations Supervisor (President, Secretary or Agent)

W.B. & M.

| 10/4/83      | Spudded well and drilling 12 1/4" hole.   |                                  |
|--------------|---|----------------------------------|
| 10/5/83      | Drilling 12 1/4" hole to 508'. Ran 12 joints of 8 5/8" casing to a measur of 486' and cemented with 215 sxs class "G" cement.   | red depth                        |
| 10/6/83      | Test BOP's with Bill King. Pressures did not hold.  |                                  |
| 10/7/83      | Test BOP's with Bill King. Pressures held. Drilling cement.   |                                  |
| 10/8/83      | Drilling 7 7/8" hole to 1165'.  | ÷.                               |
| 10/9/83      | Drilling to 1727'.  | •                                |
| 10/10/83     | Drilling to 2226'.  |                                  |
|              | Drilling to 2527'.  |                                  |
| ļ.           | Drilling. TD well at 2827'. Logging with Schlumberger.  |                                  |
|              | Logging with Schlumberger. Wait on Halliburton.   |                                  |
|              | Plug and suspend well. Bottom plug set from 1518' - 818' with 206 sxs cl Top plug set from 587' - 276' with 95 sxs class "G" cement. Go in hole a 346' with Bill King witnessing.   | ass "G" cement<br>nd tag plug at |
|              |   |                                  |
|              |   |                                  |
|              |   |                                  |
|              |   |                                  |
|              |   |                                  |
|              |   |                                  |
|              |   |                                  |
|              | STATE OF OREGON  DEPARTMENT OF GEDLOGY AND MINERAL INDUSTR  910 State Office Building Portland, OR 97201  |                                  |
|              | HISTORY OF OIL OR GAS WELL  |                                  |
|              | (In compliance with rules and regulations pursuant to ORS 520)  |                                  |
|              | ARCO Oil & Gas Company Wilson 11-   | -5                               |
|              | ARCO Oil & Gas Company Wilson 11- (Company or operator) (Lease) (Well N   |                                  |
| Sec.         | 5 , T. 6N , R. 5W W.B.&M. Surveyed Coordinates:  1,710.25' E & 690.89'S from NW Corner, Section 5, T6N, R5W   | ···                              |
| Wildo        | cat: (or) Field Name: Mist County: Columbia   | 3                                |
|              | Signature: Kwang Wank   |                                  |
| Date         | : March 18, 1986 Position: District Drilling Superint   | endent                           |
| form<br>as b | this form in reporting the <u>daily</u> operations at the well. (Operator may use his own forms, but heading must also be completed and submitted.) Please submit a complete history of the well. Include such it sizes, mud weights, casing sizes and depths set, amount of cement used, drilling depths, fishing, orating, and plugging procedures, and anything else pertinent to the operation. Do not include lith | information<br>logging,          |
| 10/14/8      | 3 WILSON #11-5 (8-5/8" @ 486')  |                                  |
|              | Bottom plug 1,518' to 818' Shoe plug 587' to 276' Tagged plug at 351' with Bill King witnessing. 10' surface plug and   |                                  |
|              | cut off 5' below ground level and welded plate on stub.   |                                  |
|              |   |                                  |
|              |   |                                  |
|              |   |                                  |
|              |   |                                  |
|              |   |                                  |
|              |   | RECEIVED - PTLD                  |
|              |   | MAR 2 0 1986                     |
|              |   | DEPT, OF GEOLOGY                 |
|              |   |                                  |
|              |   |                                  |

Tim B. Williamson, Drilling Foreman

Form 6 (9/84) (Formerly Drilling and Production Manager, Reichold Energy Company)