

2021 OREGON STANDARD DRAWINGS

Standard Distribution
Date of Issue: July 2022

William Lee Woods, PE
Senior Standards Engineer

This is the July 2022 release of the 2021 Oregon Standard Drawings.

For ODOT Projects the details in the standard drawings will be effective on the **Dec 1, 2022** bid opening where these drawings are called for in the project plans.

These drawings are for use with projects using the **2021 Oregon Standard Specifications**.

You will notice an “effective date” on the lower right bottom of each Standard Drawing. The bid opening date of a project should be in the effective date window of the drawings. This will ensure the correct drawings are being used on the projects.

Electronic PDF files with the effective date for each drawing are on the Web site at:

<http://www.oregon.gov/ODOT/Engineering/Pages/Standards.aspx>

The Standard Drawing Baseline Reports for the drawings contain useful information for the designer as well as updates that occur on the drawing. The link to the report is the title of the specific drawing on the webpage.

These Standard Drawings are the ones that have updates:

Drawing Number	Comment
RD317	
RD356	
RD386	
RD515	
RD526	
RD535	
RD536	New Drawing
RD545	
RD546	New Drawing
RD575	
RD576	New Drawing
RD595	New Drawing
RD596	New Drawing
RD722	

Drawing Number	Comment
RD908	
BR139	
BR140	
BR222	
BR241	
BR290	
BR400	
BR405	
BR410	
BR415	
BR420	
BR422	
BR445	
TM457	
TM467	
TM472	
TM492	
TM493	New Drawing
TM503	
TM530	
TM628	
TM655	
TM656	
TM800	
TM841	
TM850	
TM853	
TN854	New Drawing
TM870	
TM871	

OREGON STANDARD DRAWINGS 2021 NUMBERS AND REVISION DATES

DRAWING NUMBER	REVISION DATE	DRAWING NUMBER	REVISION DATE	DRAWING NUMBER	REVISION DATE
-------------------	------------------	-------------------	------------------	-------------------	------------------

RD100	
RD101	
RD110	
RD115	
RD120	
RD130	
RD140	
RD150	
RD160	
RD170	01/2021
RD250	
RD254	
RD255	
RD258	
RD262	
RD266	
RD270	
RD274	
RD278	
RD282	
RD286	
RD300	
RD302	
RD304	
RD306	
RD308	
RD310	
RD312	
RD316	
RD317	07/2022
RD318	
RD319	
RD320	
RD321	
RD322	
RD324	
RD325	
RD326	
RD327	
RD328	
RD330	
RD332	
RD334	
RD335	
RD336	
RD338	
RD339	07/2021
RD340	
RD342	
RD343	

RD344	
RD345	
RD346	
RD348	
RD350	
RD352	
RD354	
RD356	07/2022
RD358	
RD360	
RD362	
RD363	
RD364	
RD365	
RD366	
RD367	
RD368	
RD370	
RD371	
RD372	
RD373	
RD374	
RD376	
RD378	
RD380	
RD382	
RD384	
RD386	07/2022
RD388	
RD390	
RD391	
RD393	
RD398	07/2021
RD399	
RD400	
RD401	
RD402	07/2021
RD403	07/2021
RD404	07/2021
RD405	
RD406	01/2022
RD407	07/2021
RD408	
RD409	
RD410	
RD412	
RD415	
RD416	
RD417	
RD419	07/2021

RD420	07/2021
RD421	
RD435	
RD436	
RD437	
RD438	
RD440	
RD442	01/2022
RD443	
RD444	
RD445	
RD450	
RD451	
RD470	
RD471	
RD481	
RD482	
RD500	01/2022
RD501	07/2021
RD502	01/2022
RD503	01/2022
RD505	
RD510	01/2022
RD515	07/2022
RD516	
RD520	
RD526	07/2022
RD530	01/2022
RD535	07/2022
RD536	07/2022
RD545	07/2022
RD546	07/2022
RD550	
RD560	01/2022
RD570	01/2022
RD575	07/2022
RD576	07/2022
RD580	
RD581	
RD590	
RD595	07/2022
RD596	07/2022
RD602	
RD610	
RD615	07/2021
RD700	
RD701	
RD702	01/2022
RD705	
RD706	

OREGON STANDARD DRAWINGS 2021 NUMBERS AND REVISION DATES

DRAWING NUMBER	REVISION DATE	DRAWING NUMBER	REVISION DATE	DRAWING NUMBER	REVISION DATE
-------------------	------------------	-------------------	------------------	-------------------	------------------

RD707	
RD710	01/2022
RD711	01/2022
RD715	
RD720	
RD721	
RD722	07/2022
RD725	
RD730	
RD735	
RD740	
RD745	07/2021
RD750	
RD770	
RD771	
RD780	07/2021
RD781	07/2021
RD782	07/2021
RD810	
RD815	
RD820	
RD825	
RD830	01/2021
RD832	
RD835	
RD840	
RD845	
RD900	01/2022
RD901	09/2021
RD902	07/2021
RD904	
RD905	01/2022
RD906	
RD908	07/2022
RD909	01/2022
RD910	01/2022
RD912	01/2022
RD913	01/2022
RD916	
RD920	01/2022
RD922	
RD930	01/2022
RD932	
RD936	01/2022
RD938	07/2021
RD940	07/2021
RD950	
RD952	07/2021
RD960	07/2021
RD1000	01/2022

RD1005	01/2021
RD1006	01/2021
RD1010	01/2021
RD1015	01/2021
RD1030	01/2021
RD1031	01/2021
RD1032	01/2021
RD1033	01/2021
RD1040	01/2021
RD1045	01/2021
RD1050	01/2021
RD1055	01/2021
RD1060	01/2021
RD1065	01/2021
RD1070	01/2021
RD1140	01/2022
BR115	
BR133	
BR135	
BR136	
BR139	07/2022
BR140	07/2022
BR141	
BR145	
BR157	
BR165	01/2021
BR175	
BR182	
BR190	
BR191	
BR195	
BR200	
BR203	
BR206	01/2022
BR207	
BR208	01/2022
BR209	
BR212	
BR214	
BR216	
BR220	
BR221	
BR222	07/2022
BR223	
BR226	01/2022
BR230	01/2022
BR233	
BR236	01/2022
BR240	

BR241	07/2022
BR242	
BR245	
BR246	
BR250	
BR253	
BR256	
BR260	
BR263	
BR266	
BR270	01/2022
BR273	
BR285	07/2021
BR286	07/2021
BR290	07/2022
BR291	
BR300	
BR310	01/2022
BR321	01/2022
BR325	
BR330	
BR335	
BR340	
BR350	
BR360	
BR365	
BR375	
BR400	07/2022
BR405	07/2022
BR410	07/2022
BR415	07/2022
BR420	07/2022
BR422	07/2022
BR425	
BR430	
BR435	
BR440	
BR445	07/2022
BR500	
BR505	
BR520	
BR525	
BR550	
BR705	
BR706	01/2021
BR707	
BR708	
BR709	
BR730	
BR740	

OREGON STANDARD DRAWINGS 2021 NUMBERS AND REVISION DATES

DRAWING NUMBER	REVISION DATE	DRAWING NUMBER	REVISION DATE	DRAWING NUMBER	REVISION DATE
-------------------	------------------	-------------------	------------------	-------------------	------------------

BR750	01/2021
BR751	
BR760	
BR800	
BR805	
BR820	01/2021
BR825	01/2021
BR830	01/2021
BR835	01/2021
BR840	
BR841	
BR970	
BR971	
BR972	01/2022
TM200	01/2022
TM201	01/2022
TM204	
TM206	
TM211	01/2022
TM212	07/2021
TM220	
TM221	07/2021
TM222	
TM223	
TM224	
TM225	
TM230	
TM231	
TM232	
TM233	
TM240	
TM300	
TM301	
TM302	
TM303	07/2021
TM450	07/2021
TM452	07/2021
TM453	07/2021
TM454	07/2021
TM456	07/2021
TM457	07/2022
TM460	07/2021
TM462	07/2021
TM466	07/2021
TM467	07/2022
TM470	07/2021
TM471	07/2021
TM472	07/2022

TM482	07/2021
TM485	07/2021
TM492	07/2022
TM493	07/2022
TM500	
TM501	01/2022
TM502	01/2022
TM503	07/2022
TM504	
TM505	01/2022
TM515	
TM516	
TM517	07/2021
TM520	
TM521	07/2021
TM530	07/2022
TM531	
TM539	
TM547	
TM551	
TM560	
TM561	
TM570	
TM571	
TM575	
TM576	
TM577	
TM600	
TM601	
TM602	
TM606	
TM607	01/2022
TM608	01/2022
TM609	01/2022
TM610	
TM611	
TM612	01/2021
TM614	
TM615	01/2022
TM616	01/2022
TM617	01/2022
TM618	
TM619	
TM620	
TM621	01/2021
TM622	
TM623	01/2022
TM624	
TM625	
TM626	

TM627	01/2021
TM628	07/2022
TM629	07/2021
TM630	07/2021
TM631	07/2021
TM635	
TM650	
TM651	01/2021
TM652	
TM653	
TM654	
TM655	07/2022
TM656	07/2022
TM657	
TM658	
TM670	01/2022
TM671	
TM672	
TM675	
TM676	
TM677	
TM678	01/2022
TM679	
TM680	
TM681	
TM687	
TM688	
TM689	
TM690	
TM691	01/2021
TM693	
TM694	
TM695	01/2021
TM696	
TM697	
TM698	
TM800	07/2022
TM810	
TM820	
TM821	
TM822	
TM830	01/2022
TM831	
TM832	
TM833	
TM840	
TM841	07/2022
TM842	
TM843	
TM844	01/2022

**OREGON STANDARD DRAWINGS 2021
NUMBERS AND REVISION DATES**

DRAWING NUMBER	REVISION DATE	DRAWING NUMBER	REVISION DATE	DRAWING NUMBER	REVISION DATE
---------------------------	--------------------------	---------------------------	--------------------------	---------------------------	--------------------------

TM850	07/2022
TM851	
TM852	
TM853	07/2022
TM854	07/2022
TM860	
TM861	
TM862	
TM870	07/2022
TM871	07/2022
TM880	07/2021

- A -**Access and Ventilation**

Hardware for Concrete Box Girders BR135, BR136

Air Release/Air Vacuum Assembly,

Water System RD266, RD270

Anchors, Pipe Slope RD330, RD332

Approaches RD715

- B -

Barricades (Types I, II, & III) TM820

Barrier, Concrete, Median

35" cast-in-place RD590

Barrier, Concrete, Standard (32" Height)

Around Median Obstacle RD535, RD536

At Bridge Expansion Joints BR263

Buried in Backslope RD526

Cast-In-Place RD505

Median Barrier Anchoring RD515

Precast RD500, RD501, RD502

RD503

Scuppers (Precast) RD595, RD596

Securing Barrier To Roadway RD516

Terminals RD510

Transition To Bridge Rail RD520

Transition To Guardrail RD530, RD580

Barrier, Concrete, Tall (42" Height)

Around Median Obstacle RD575, RD576

Precast RD545, RD546

Securing Barrier To Roadway RD516

Transition to Bridge Rail RD550

Transition To Standard Barrier RD560

Transition To Guardrail RD570, RD581

Barrier, Metal Median RD400, RD405, RD408

Bollards RD130, RD255

Bike Lane

Curb RD702

Crossing RD1140

Box Culvert, Concrete

Cast-in-place BR820, BR825,

BR830, BR835

Double Box Culverts BR840, BR841

Extensions BR805

Modified Type 2A Guardrail BR266

Wingwalls BR800

Boxes

Trapezoidal Box Reinforcement BR133

Bridge End Panel BR165

Bridge Concrete Parapet

32" Vertical BR221

42" Vertical BR222

With Steel Post BR214

Bridge Preservation

Concrete Repair BR500

General Cathodic Protection BR520

2021 OREGON STANDARD DRAWINGS INDEX

Reinforcement Continuity	BR525
Reinforcing Bar Repair	BR505
Rivet Replacement	BR550
Bridge Rail	
2-Tube Curb Mount	BR206, BR207
2-Tube Side Mount	BR226, BR230
3-Tube Curb Mount	BR208, BR209
Combination	BR223
Concrete Post and Beam	BR212
Flush Mount Combination	BR220
Pedestrian	BR246
Pedestrian On Sidewalk Mount	
Parapet	BR250
Sidewalk Mount Combination	BR216
Sidewalk Mount Parapet with	
Chain Link Fence	BR253
Thrie Beam	BR233
Thrie Beam Retrofit	BR273
Trailing End Connection	
To Guardrail	BR236
Transition From Guardrail	BR270
Transition To Guardrail	BR203
Transition To Guardrail,	
3'-6" Height	BR291
Type F	BR200
Type F 3'-6" Height	BR290
Type F with Chain Link	BR260
Type F with Pedestrian Rail	BR256
Type F with Rectangular Tube	BR285, BR286

- C -

Cathodic Protection, General	BR520
Cattle Guard	
Painted	RD110
Steel Tube	BR175
Cattle Pass	RD110
Check Dams	RD1005, RD1006
Concrete Pavement	
Plain Dowelled	RD600
Reinforced	RD600
Concrete Repair, Bridge	BR500
Concrete Truck Wash Out	RD1070
Construction Entrances	RD1000
Coupling Bands for Corrugated Metal Pipe	RD325, RD326, RD327
Cross Slopes, Roadway Superelevations	RD140
Crosswalk Closure	TM240
Curb Inlets	RD366
Curbs, Various Types	RD700, RD170
Drainage	RD701
Bike Lane	RD702
Curb Ramp	
Blended Transition	RD940
Combination	RD930, RD932, RD936, RD938
Components	RD900
Corner Identification	RD901
Detectable Warning Surface	RD902, RD904, RD905
	RD906, RD908
Detectable Guide Strip	RD909
End of Walk	RD950, RD952
Parallel	RD920, RD922
Perpendicular	RD910, RD912, RD913, RD916
Unique	RD960
Cutbanks, Rounding	RD150

2021 OREGON STANDARD DRAWINGS INDEX

Crossing

Bike Lane RD1140

-D-**Delineators**

Installation
 Freeways TM575
 Non-Freeway TM576
 Special Applications TM577
 Layout And Posts Types TM570
 Steel Post Details TM571

Detectable Warning Devices RD902, RD904, RD905,
 RD906, RD908, RD909

Drainage Details

Bore Casing RD308
 Concrete Encasement,
 Cradle, And Cap RD306
 Locator Post RD334
 Street Cut RD302
 Trench Backfill RD300
 Gutter Transition At Inlet RD363

Driveways

Curb Line Sidewalk RD730, RD735
 RD745, RD750
 Non-Sidewalk RD715
 Separated Sidewalk RD725, RD740

-E-

End Pieces, Guardrail RD415, RD417
 Energy Dissipater RD1045, RD1050

Erosion Control

Check Dams RD1005, RD1006
 Concrete Truck Wash Out RD1070
 Construction Entrances RD1000
 Energy Dissipater RD1045, RD1050
 Inlet Protection RD1010, RD1015
 Matting RD1055
 Scour Basin, Temporary RD1050
 Sediment Barrier RD1030, RD1031,
 RD1032, RD1033
 Sediment Fence RD1040
 Sediment Trap RD1065
 Slope Drains, Temporary RD1045
 Tire Wash Facility RD1060

Expansion Joints, Bridge BR139, BR140, BR141,
 BR145

-F-

Feathering A.C. Over Existing Pavement RD610

Fences

Barbed & Woven Wire
 (Types 1, 1-5W And 2) RD810
 Chain Link RD815
 Gates RD820

2021 OREGON STANDARD DRAWINGS INDEX

Pedestrian Protective	RD780, RD781, RD782 BR240, BR241, BR242, BR245
Snow, Metal Wildlife	RD825 RD830, RD832, RD835, RD840, RD845
Field Marker, Storm Water Treatment And Storage Facilities	RD399
Flag Board Mounting Details	TM204
Flashing Beacon (RRFB) Assemblies	TM493

-G-

Gates, Fence Gateway	RD820, RD832 RD810
----------------------	-----------------------

Girders

Precast Prestressed Boxes	BR425, BR430, BR435, BR440, BR445
Bulb-I	BR300
Bulb-T	BR310, BR360, BR365, BR375
BT90 And BT96	BR321
Temporary Diaphragm Beam	BR350
Type II	BR325
Type III	BR330
Type IV	BR335
Type V	BR340
Grade Crossing, Railroad	RD445

Grate

Inlets Manhole	RD365, RD378 RD356
-------------------	-----------------------

Guardrail

29" Rail Height	<i>See Guardrail - 29" Rail Height</i>
31" Rail Height	<i>See Midwest Guardrail system</i>
Anchors, Steel (Types 1 And 1 Mod.)	RD450
Bridges/Rails Installation At Railroad Crossing Placement of Guardrail on Slopes Posts, Wood Breakaway Thrie Beam	(See Rails) RD445 RD406 RD451 RD409, RD410

Guardrail - 29" Rail Height

Adjustment	RD400
Assembly Details	RD400
Blocks	RD405
End Pieces, Types B And C	RD415
Guardrail and Transitions	RD400, RD481 RD530, RD570
Installation At Bridge Ends	RD440
Over Low-Fill Culverts	RD470
Parts	RD415
Posts	RD405
Terminals, Bridges	RD440
Terminals, Cut And False Cut	RD435
Types 1, 2A, 3 & 4	RD400

2021 OREGON STANDARD DRAWINGS INDEX

Guardrail – 31” Rail Height*See Midwest Guardrail system*

Guide Posts (See Delineators)
 Gutter Transition At Inlet RD363

-H-

Handrail
 Metal RD770, RD771
 Stairway RD120
 Hydrant Installation RD254

-I-

ID Marker, Culvert RD398
 ID Marker, Bridge BR195
 Illumination TM300, TM301
 TM302, TM303

Inlets

Adjusting Existing RD376
 Concrete Cap RD376
 Concrete Type CG-3 RD371, RD372,
 RD373
 Concrete Types G, & G-2M RD364
 Concrete Types CG RD366
 Curb Inlet Channel RD367
 Concrete Types M-E, M-O, And B RD368
 Ditch, Type D RD370

Field or Area Drainage Basin RD374
 Frames and Grates RD365
 Pipe to Structure Connections RD339
 Slotted CMP Drain RD328
 Type 3 RD378

Inlet Protection RD1010, RD1015

Islands

Accessible Route RD710
 Accessible Route Channelized RD711
 Traffic RD705
 Nose Treatments RD707

-J-

Joint Seal, Asphaltic Plug BR157
 Also see Expansion Joints, Bridge

-L-

Locator Post RD334

Luminaire Poles

Breakaway Location Guidelines TM635
 Fixed and Slip Base Supports TM629, TM630, TM631
 Mounting On Structures BR970, BR971, BR972

Lifeline, Fall Arrest BR190, BR191

2021 OREGON STANDARD DRAWINGS INDEX

-M-

Mail Box Support RD100
 Mail Box Installation RD101

Manhole, Concrete

24" Manhole RD343
 Base, Cast-In-Place And Precast RD344
 Carry Through, Storm Sewer RD354
 Cover and Frame RD356
 Grate RD356
 Frame Adjustment RD360
 Inside Drop, Sanitary RD350
 Outside Drop RD352
 Pipe to Manhole Connections RD345
 Precast, Large RD346
 Precast, Pollution Control RD340
 Precast, Sanitary Sewer RD338
 Precast, Storm Sewer RD335
 Shallow RD342
 Slope Protector RD358
 Steps RD336
 With Inlet RD348

Matting RD1055

Median Barrier, Metal

Barrier and Transitions RD400, RD408, RD481,
 RD530, RD570
 RD580, RD581
 Assembly Details RD400, RD408
 Blocks RD403, RD404, RD405
 Bridge Deck Expansion Joint RD400, RD412
 Parts RD415, RD416, RD417

Posts

RD403, RD404, RD405

Median and Shoulder Barriers, Concrete

Anchoring RD515
 Cast-In-Place RD505
 Precast RD500
 Securing Barrier To Roadway RD516
 Terminals RD510

Meter Assembly, Water System RD278
 Milepost Signing Details TM221, TM222
 Moment Slab on MSE Wall BR760
 Monument Box RD115
 Multi-Use Path RD602

Midwest Guardrail System

Adjustment RD401
 Assembly Details RD407, RD408
 Blocks RD403, RD404
 Bridges/Rails (See Rails)
 Buried in Backslope RD436, RD437
 End Pieces, Types B and C RD417
 Guardrail and Transitions RD412, RD482
 RD580, RD581
 Height Conversion RD481
 Over Low-Fill Culverts RD471
 Parts RD416, RD417
 Posts RD403, RD404

Terminals, Bridges RD442
 Terminals, Buried in Backslope RD436, RD437
 Terminals, Downstream Anchor RD438
 Terminals, Energy Absorbing RD420, RD421
 Terminals, Grading RD419
 Transition to Bridge Rail BR270

Types RD402

2021 OREGON STANDARD DRAWINGS INDEX

Metal Median Barrier	RD408
Thrie beam	RD409, RD410
W-beam	RD407, RD482
Typical Layouts	
At Bridge Ends	RD442
For Embankments	RD443
For Fixed Objects	RD444
-P-	
Pavement	
Asphalt Pavement Details	RD610, RD615
Multi-Layer Construction	RD615
Surface Edge Details	RD615
Pavement Markings	
Alignment Layout	TM560, TM561
Durable Markings	TM520, TM521
Freeway Ramp	TM547, TM551
Intersection	TM530
High Performance Markings	TM521
Left Turn and Median	TM539
Railroad Crossing	TM505
Raised Marking Details	TM515, TM516
Recessed Marking Details	TM517
Standard Details Blocks	TM500, TM501, TM502, TM503, TM504, TM510
Turn Arrow	TM531
Pedestrian	
Aluminum Fence	RD780, RR781, RD782
Metal Handrail	RD770, RD771

Pipe	
Backfill/Compaction Details	RD300, RD304
Connection Details, Unlike Pipe	RD325, RD326, RD327
Corrugated Metal Coupling Bands	RD325, RD326, RD327
Culvert Embankment Protection	RD317
Culvert ID Marker	RD398
Miscellaneous Culvert Details	RD319
Multiple Installations	RD300
Paved End Slopes	RD320
Paved End Slopes	
With Removable Safety Bars	RD321
Safety End Sections, Concrete Pipe	RD324
Safety End Sections, Metal Pipe	RD322
Skew Diagram	RD316
Slope Anchors	RD330, RD332
Sloped Ends, Concrete Pipe	RD318
Sloped Ends, Metal Pipe	RD316
Slotted Drain, Metal Pipe (CMP)	RD328
Pipe Fill Height Tables	
Concrete	RD386
Corrugated HDPE	RD390
Metal, Arch	RD382
Metal, Round	RD380
Metal, Spiral Rib	RD384
Polypropylene	RD393
Poly Vinyl Chloride (PVC)	RD388
Reinforced HDPE	RD391
Poles	
Luminaire Fixed and	
Slip Base Supports	TM629, TM630, TM631
Traffic Signals	TM650, TM651, TM652 TM653, TM654

2021 OREGON STANDARD DRAWINGS INDEX

Portable Barricade TM820

-R-

Railroad At Grade Crossing RD445
 Ramp, Sidewalk RD910, RD920, RD930,
 RD940, RD950, RD960
 Reinforcement Continuity BR525
 Reinforcing Bar Repair BR505
 Rivet Replacement BR550
 Roadway Cross Slopes
 Superelevated Sections RD140
 Rounding Of Cutbanks RD150
 Root Barrier, Water Pipe RD286
 Roundabout Curb Placement RD170

-S-

Safety Edge RD615

Sanitary Sewer

Clean Out RD362
 Manhole RD338
 Piped Inside Drop Connection RD350
 Sampling Station, Water System RD282
 Sanitary Sewer,
 Service Connections RD310
 Scour Basin, Temporary RD1050
 Sediment Barrier RD1030, RD1031,
 RD1032, RD1033
 Sediment Fence RD1040

Sediment Trap RD1065
 Sidewalk RD720, RD721, RD722

Signs

Aluminum Panel TM675
 Attachment TM676
 Bracing Details TM206
 Directional Sign Layout TM223, TM224
 Exit TM225
 Flag Board Mounting Details TM204
 Installation Details TM200, TM201
 Mileposts TM221, TM222
 Mounts TM677, TM678, TM679
 Multi-Post Installations TM220
 Removable Legend
 Mounting Details TM230, TM231,
 TM232, TM233

Signs Con't

Route Makers
 Interstate Route Shields TM211
 Oregon Highways TM212
 U.S. Route Shields TM211

Sign Supports

Breakaway Location Guidelines TM635
 Cantilever TM621, TM622, TM623,
 TM624, TM625, TM626,
 TM627, TM628, TM690,
 TM691
 Multi-Post Breakaway TM600, TM601
 Sign Bridge TM614, TM615, TM616,
 TM617, TM618, TM619,
 TM620, TM693, TM694,
 TM695, TM696, TM697
 Square Tube TM681, TM687,

2021 OREGON STANDARD DRAWINGS INDEX

Temporary	TM688, TM689
Triangular Base Breakaway	TM822
Variable Message Sign	TM602
	TM606, TM607, TM608,
	TM609, TM610, TM611,
	TM612, TM621, TM622,
	TM623, TM624, TM625,
	TM626, TM627, TM628,
	TM690, TM691, TM693,
	TM694, TM695, TM696,
	TM697
Wood Post	TM670
Service Connection, Water System	RD274
Siphon Box	RD376
Slabs, Precast Prestressed	BR400, BR405, BR410,
	BR415, BR420, BR422,
	BR445
Slope	
Drains, Temporary	RD1045
Paving	BR115
Pipe Anchors	RD330, RD332
Protector, Concrete Manhole	RD358
Rounding	RD150
Slotted Drains, Metal Pipe (CMP)	RD328
Snow Fence, Metal	RD825
Soundwalls	
Masonry (Pile Footing)	BR750, BR751
Masonry (Spread Footing)	BR730
Precast Concrete	BR740
Stairway, Concrete	RD120

Steps, Manhole Precast	RD336
Stop Lane, Truck And Bus	
At Railroad Crossing	RD445
Storm Water Treatment and	
Storage Facility Field Marker	RD399
Street Cut	RD302
Subsurface Drain	RD312

-T-

Temporary Traffic Control

2-Lane, 2-Way Roadways	TM850, TM854
Abrupt Edge	TM800
Barricades	TM820
Blasting Zones	TM871
Bridge Construction	TM870
Closure Details	TM840
Concrete Barrier	TM830
Freeway Sections	TM860, TM861, TM862
Impact Attenuator	TM831, TM832, TM833
Intersection Work Zones	TM841, TM842, TM843
Message Sign	TM800
Non-Freeway Multi-Lane Sections	TM851, TM852, TM853
Pedestrian Accessible Routing	TM844
Reflective Pavement Markers	TM810
Rumble Strips	TM830
Sign Supports	TM689, TM821
Speed Reduction (Moving Operations)	TM880
Tables, Flare Rate, Taper, Spacing	TM800
Temporary Sign Support	TM822
Thrust Blocking, Water Systems	RD250

2021 OREGON STANDARD DRAWINGS INDEX

Tire Wash Facility RD1060

Traffic

Island RD705
 Separator, Concrete RD706

Traffic Signals

Color Code Chart TM470
 Controller Cabinet and Foundation TM482
 Fire Preemption Details TM456
 Junction Boxes TM472
 Maintenance Pad Details RD160
 Mast Arm Pole Details TM450
 Mounting Details
 Adjustable Signal Head TM462
 Spanwire TM456
 Pedestrian Signal TM457, TM467
 Pole Footing Details
 Mast Arm Pole TM450
 Strain Pole TM452
 Pole Mounts TM680
 Ramp Meter Details TM492
 Rectangular Rapid Flashing Beacon TM493
 Service Cabinet TM485
 Spanwire Design TM456
 Strain Pole Details TM452
 Supports TM650, TM651, TM652,
 TM653, TM654, TM655,
 TM656,
 TM657, TM658
 Temporary TM453, TM454, TM456
 Trenching & Conduit Installation TM471
 Vehicle Signal Details TM460
 Vehicle Signal Pedestal TM457

Trench Backfill RD300
 Truck Aprons on Roundabouts RD170
 Trucks and Bus Stop Lanes
 At Railroad Crossing RD445
 Truck Scale Pit BR182
 Truncated Dome RD902

-V-

Valve Box And Operator
 Extension Assembly RD258
 VMS Walk-In Bridge TM698

-W-**Walls**


Retaining, Concrete BR705, BR706, BR707,
 BR708, BR709
 Soundwall, Masonry
 Pile Footing BR750, BR751
 Spread Footing BR730
 Soundwall, Precast BR740

Water Systems



Air Release Assembly, Manual RD266
 Air Release/Air Vacuum
 Valve Assembly RD270
 Hydrant Installation RD254
 Main Dead-End Blowoff Assembly RD262
 Root Barrier RD286
 Thrust Blocking RD250
 Valve Box And Operator

2021 OREGON STANDARD DRAWINGS INDEX



Extension Assembly	RD258
Water Meter Assembly	RD278
Water Sampling Station	RD282
Water Service Connection	RD274
Wingwalls, Concrete Box Culverts	BR800
Wind Pressure Map	TM671
Wind Speed Map	TM672




SLOPED OR PROJECTING END



SLOPED END WITH SLOPE PAVING




HEADWALL AND WINGWALLS




B = Diameter of circular barrel or span of arch pipe, box, or open-bottom arch.
 D = Diameter of circular barrel or rise of arch pipe, box, or open-bottom arch.
 T = Thickness of riprap blanket, see Table A.


EMBANKMENT PROTECTION



a) Riprap pad without cutoff wall, elevation view



b) Riprap pad with cutoff wall, elevation view



c) Riprap pad, end view

RIPRAP PAD NOTES:

- ① Do not excavate non-erodible rock in order to place riprap.
- ② Use riprap geotextile under Class 200 and Class 700 loose riprap.
- ③ Top width (W) of the riprap pad is the larger of $5B$ or the width of the embankment slope protection.

RIPRAP PADS

GENERAL NOTES FOR ALL DETAILS:

1. See Std. Drg's. RD300 & RD304 for installation details.
2. Open ends of pipes normally require a site specific design, and may require special treatment (sloped ends, culvert embankment protection, paved end slopes, safety end sections, or other measures). See special details or Standard Drawings as called for on plans.

CALC. BOOK NO. _____ N/A _____

SDR DATE _____ 30-June-2022 _____

NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications

OREGON STANDARD DRAWINGS

CULVERT EMBANKMENT PROTECTION and RIPRAP PADS

2021

DATE	REVISION DESCRIPTION
06-30-22	Riprap backing to riprap geotextile


The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.

TABLE A – Embankment Slope Protection	
Riprap Class	T Distance
50	12 Inches
100	18 Inches
200	24 Inches *
700	36 Inches *


* Riprap geotextile required between riprap and embankment

TABLE B – Riprap Pad Dimensions		
Riprap Class	L * (ft)	T (ft)
50	4B or 1.3	2.3
100	4B or 1.6	3.3
200	4B or 2.0	4.3
700	4B or 3.3	5.6


* L is the greater of 4B or the listed dimension.



NOTE:
Coat outside of frame with asphalt where frame is to be placed in concrete, pavement, concrete gutter or walk.




COVER SECTION A-A



*36 inch minimum diameter cover is required for manholes with depths of 20 feet or greater. See general note 4.


FRAME SECTION A-A

STANDARD MANHOLE COVER AND FRAME




NOTE:
For use with standard manhole frame. See general note 7.

PLAN




SECTION B-B

STANDARD MANHOLE GRATE



PLAN


Tamperproof,
2 holes maximum
for sanitary covers




SECTION D-D

CAST IRON SUBURBAN MANHOLE COVER AND FRAME

For use on local streets only, as specified



PLAN




SECTION C-C

* Standard depths 1 1/2", 2", 2 1/2" and 3". Material to be grey cast iron ASTM A48, Class 35B. Tolerance on non-machined surfaces to be $\pm 0.06"$. See general note 6

MANHOLE ADJUSTMENT RING

For use with Standard Manhole Frame



PLAN

SECTION E-E

CAST IRON TAMPERPROOF AND WATERTIGHT COVER


Frames available in standard or suburban pattern

GENERAL NOTES FOR ALL DETAILS ON THIS SHEET:

1. Tamperproof covers required on sanitary or storm drain manhole where located in pedestrian ways or easement areas. Covers for sanitary manholes shall have two holes maximum.
2. Watertight covers required if located where cover may be submerged (no holes).
3. Covers and frames shall be stamped with manufacturer's initials, heat number and point of origin.
4. See Std. Dwg. RD336 for manhole steps.
5. See Std. Dwg. RD360 for manhole frame adjustment.
6. See ODOT's QPL for alternate manhole adjustment rings.
7. Manhole grate allowed only in locations not subject to bicycle or pedestrian use.
8. See ODOT's QPL for alternate bolt-down products.

1 1/4" OD x 1/8" thick
stainless steel washer,
three required per cover

1/4" neoprene
gasket, omit for
tamperproof cover



NOTE:

Three required, equally spaced, 1/2" x 1 1/2" pentagonal or hexagonal head, bronze or stainless steel. Install frame so that one bolt boss is located over the manhole steps. See general note 8

BOLT DOWN DETAIL

For tamperproof and watertight covers


CALC. BOOK NO. _____	N/A	SDR DATE _____	15-JUL-2022
<p>The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.</p>		NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications	
		OREGON STANDARD DRAWINGS	
		MANHOLE COVERS AND FRAMES	
		2021	
		DATE	REVISION DESCRIPTION
		07-2022	REVISED DETAILS AND NOTES

- GENERAL NOTES FOR ALL TABLES ON THIS SHEET:
1. Maximum height of cover is greatest vertical distance from top of pipe to finish grade.
 2. Minimum height of cover is least vertical distance from top of pipe to subgrade.
 3. For ODOT, pipes with diameters greater than 72" must be reviewed by the Geo-Environmental Section.
 4. For ODOT, pipes with maximum cover greater than those shown in the Tables shall be approved by the Senior Standards Engineer.
 5. For multiple pipe installations, see Std. Dwg. RD300.
 6. Open ends of pipes normally require a site specific design, and may require special treatment (sloped ends, culvert embankment protection, paved end slopes, safety end sections, or other measures). See special details or Standard Drawings as called for on plans.

ALLOWABLE FILL HEIGHTS FOR CIRCULAR CONCRETE PIPE HS 25 - 44 LIVE LOAD						
PIPE DIAMETER (INCHES)	REINFORCED PIPE					
	CLASS III		CLASS IV		CLASS V	
	MINIMUM COVER (Feet)	MAXIMUM COVER (Feet)	MINIMUM COVER (Feet)	MAXIMUM COVER (Feet)	MINIMUM COVER (Feet)	MAXIMUM COVER (Feet)
12	1.5	17	1.0	27	0.5	41
15	1.5	18	1.0	27	0.5	42
18	1.5	18	1.0	27	0.5	42
21	1.5	17	1.0	27	0.5	42
24	1.5	17	1.0	27	0.5	42
27	1.5	17	1.0	27	0.5	41
30	1.5	17	1.0	27	0.5	41
33	1.5	17	1.0	27	0.5	41
36	1.5	17	1.0	26	0.5	41
42	1.5	17	1.0	26	0.5	41
48	1.5	16	1.0	26	0.5	41
54	1.5	16	1.0	26		
60	1.5	16	1.0	26		
66	1.5	16	1.0	26		
72	1.5	16	1.0	25		


CALC. BOOK NO. RD07-02		SDR DATE XX-XXX-2022	
<i>The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.</i>		NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications	
		OREGON STANDARD DRAWINGS	
		FILL HEIGHT TABLE FOR CIRCULAR CONCRETE PIPE	
		2021	
		DATE	REVISION DESCRIPTION
		04-2022	REVISED NOTES

RD515.dgn 15-JUL-2022




PLAN VIEW AT S BAR
STANDARD BARRIER


PLAN VIEW AT S BAR
TALL BARRIER



ELEVATION VIEW AT ANCHOR RODS
SECURING TO PAVEMENT OPTION



GROUT DETAIL
FOR PRECAST CONCRETE BARRIER



GROUTING HOLES PLAN

GROUTING OPTION

(Dimensions between 2" dia. holes are nominal)
This detail is retained for maintenance purposes.
Do not use for new construction.

GENERAL NOTES FOR ALL DETAILS ON THIS SHEET:

1. For use in medians with width less than 8' (as measured between nearest fog lines).
2. See Std. Dwgs. RD503 & RD545 for reinforcement and other details not shown.
3. See Std. Dwg. RD516 for securing concrete barrier to roadway.
4. All pins, bolts, dowels, loop bars, and connectors shall be hot-dip galvanized after fabrication.
5. S bars to be full length as shown.

CALC. BOOK NO. N/A


SDR DATE 15-JUL-2022

NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications

OREGON STANDARD DRAWINGS
MEDIAN BARRIER ANCHORING
DETAILS

2021

DATE	REVISION	DESCRIPTION
07-2022	REVISED DETAILS AND NOTES	



GENERAL NOTES FOR ALL DETAILS ON THIS SHEET:

1. Normal use assumes an existing established slope. This detail is not intended for construction of new slope steeper than a slope of 1V:2H.
2. If the slope is flatter than 1V:1H ensure that there is a clear recovery area behind the barrier, with no funneling effect to the back of the obstruction.
3. Provide drainage as required.
4. See Std. Dwgs. RD500, RD510 and RD516 for details not shown.
5. Surfacing details same as adjacent shoulder.
6. Barrier sections, connections and appurtenances that retain backslope require stability design calculations stamped by an engineer.








TABLE A FLARE RATES AND TRANSITION PARABOLA							
FLARE RATE a:b		CONCRETE BARRIER SEGMENT					
		1	2	3	4	5	6
20:1	X (ft)	12.5	25	37.5	50	62.5	75
	Y (ft)	0.10	0.20	0.50	0.80	1.30	1.90




CALC. BOOK NO. <u> </u> N/A <u> </u>	SDR DATE <u> </u> 15-JUL-2022 <u> </u>										
<i>The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.</i>	NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications										
	OREGON STANDARD DRAWINGS										
	STANDARD CONCRETE BARRIER BURIED IN SLOPE										
	2021										
	<table><tr><td>DATE</td><td>REVISION DESCRIPTION</td></tr><tr><td>07-2022</td><td>REVISED DETAILS AND NOTES</td></tr><tr><td> </td><td> </td></tr><tr><td> </td><td> </td></tr><tr><td> </td><td> </td></tr></table>	DATE	REVISION DESCRIPTION	07-2022	REVISED DETAILS AND NOTES						
	DATE	REVISION DESCRIPTION									
07-2022	REVISED DETAILS AND NOTES										




X = Design speed (In mph)
Y = 0.5 X (In feet) (Min.)
T = (1/2 obstacle width in feet + 0.40' + a) (X)
Z = T - Y

PLAN VIEW


* Modification of barrier consists of providing 1 1/2"x4" paving ledge as shown in Section C-C.




SECTION A-A




SECTION B-B



SECTION C-C




SECTION D-D
(Precast option shown, see Section C-C for additional details not shown)




GENERAL NOTES FOR ALL DETAILS ON THIS SHEET:

1. Field verify end configurations of connecting barriers prior to forming connections at transitions.
2. All reinforcing bars shall be full length as shown and shall be placed 1 1/2" clear of the nearest face of concrete unless shown otherwise.
3. See Std. Dwgs. RD500 & RD505 for details not shown.
4. Secure precast concrete barrier to roadway, see Std. Dwg. RD516.
5. All pins, bolts, dowels, loop bars, and connectors shall be hot-dip galvanized after fabrication.
6. This barrier is not for use with bridge railing.
7. See Std. Dwg. RD536 for transition details.

CALC. BOOK NO. <u>N/A</u>		SDR DATE <u>15-JUL-2022</u>	
<i>The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.</i>		NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications	
		OREGON STANDARD DRAWINGS	
		CONCRETE BARRIER (MODIFIED) AROUND MEDIAN OBSTACLE	
		2021	
		DATE	REVISION DESCRIPTION
		05-2022	REVISED DETAILS AND NOTES




PLAN




ELEVATION

- GENERAL NOTES FOR ALL DETAILS ON THIS SHEET:
1. Field verify end configurations of connecting barriers prior to forming connections at transitions.
 2. All reinforcing bars shall be full length as shown and shall be placed 1 1/2" clear of the nearest face of concrete unless shown otherwise.
 3. See Std. Dwgs. RD500, RD501 & RD502 for details not shown.
 4. Secure precast concrete barrier to roadway, see Std. Dwg. RD516.
 5. All pins, bolts, dowels, loop bars, and connectors shall be hot-dip galvanized after fabrication.
 6. This barrier is not for use with bridge railing.



END VIEW A


(See general note 2)




END VIEW B

(See general note 2)


CAST-IN-PLACE TRANSITION



#4 LOOP BAR DETAIL




#4 LONGITUDINAL BAR




MODIFIED STIRRUP PAIRS

#4 Rebar


CALC. BOOK NO. N/A		SDR DATE 15-JUL-2022	
<i>The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.</i>		NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications	
		OREGON STANDARD DRAWINGS	
		CONCRETE BARRIER (MODIFIED) AROUND MEDIAN OBSTACLE	
		2021	
DATE		REVISION DESCRIPTION	
07-2022		NEW DRAWING CREATED	



PLAN




ELEVATION



PLAN


Cut from 5/16" thick steel plate
(See note 5 for casting instructions)



ELEVATION

Perforated C-shape

C-SHAPE DETAIL




HOLE DETAIL


GENERAL NOTES FOR ALL DETAILS ON THIS SHEET:

1. All reinforcing bars shall be full length as shown and shall be 2" clear of the nearest face of concrete unless shown otherwise.
2. All pins, bolts, dowels, loop bars, and connectors shall be hot-dip galvanized after fabrication.
3. Normal use of precast tall median barrier is restricted to curves with radii greater than 770'.
4. Chamfer all edges 3/4", typical.
5. Perforated C-shape shall be placed in location shown to a tolerance of 3/32".
6. Estimated barrier weight is 8070 pounds per 12.5' unit length, estimated narrow base barrier weight is 6550 pounds.
7. To anchor median barrier see dwg. nos. RD515 and RD516.
8. See dwg. no. RD516 for securing concrete barrier to roadway.
9. Narrow base shoulder barrier to be used only at locations with backfill behind barrier as shown on plans.
10. For barrier location details, see dwg. no. RD500.
11. When scuppers are not required, plug them with a minimum 2" of grout, as directed.


CALC. BOOK NO. N/A		SDR DATE 15-JUL-2022	
<i>The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.</i>		NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications	
		OREGON STANDARD DRAWINGS	
		PRECAST TALL (42") CONCRETE BARRIER	
		2021	
		DATE	REVISION DESCRIPTION
		07-2022	UPDATED DRAWING TO CONNECT




TYPICAL SECTION




SECTION C-C



END VIEW A-A




END VIEW B-B



TALL NARROW BASE
SHOULDER BARRIER


Only use against retaining walls or as directed. For details not shown, see other barrier details on this drawing and on dwg. no. RD545.



BARRIER END BOLT


GENERAL NOTES FOR ALL DETAILS ON THIS SHEET:

1. All reinforcing bars shall be full length as shown and shall be 2" clear of the nearest face of concrete unless shown otherwise.
2. All pins, bolts, dowels, loop bars, and connectors shall be hot-dip galvanized after fabrication.
3. Normal use of precast tall median barrier is restricted to curves with radii greater than 770'.
4. Chamfer all edges 3/4", typical.
5. Perforated C-shape shall be placed in location shown to a tolerance of 3/32".
6. Estimated barrier weight is 8070 pounds per 12.5' unit length, estimated narrow base barrier weight is 6,550 pounds.
7. To anchor median barrier see dwg. nos. RD515 and RD516.
8. See dwg. no. RD516 for securing concrete barrier to roadway.
9. Narrow base shoulder barrier to be used only at locations with backfill behind barrier as shown on plans.
10. For barrier location details, see dwg. no. RD500.
11. When scuppers are not required, plug them with a minimum 2" of grout, as directed.




U-BAR
* Vertical back barrier

CALC. BOOK NO. N/A		SDR DATE 15-JUL-2022	
The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.		NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications	
		OREGON STANDARD DRAWINGS	
		PRECAST TALL (42") CONCRETE BARRIER	
		2021	
		DATE	REVISION DESCRIPTION
		07-2022	CREATED NEW DRAWING




X = Design speed (In mph)
Y = 0.5 X (In feet) (Min.)
T = ($\frac{1}{2}$ obstacle width in feet + 0.40' + a) (X)
Z = T - Y




DETAIL WHEN CONNECTING TO PRECAST BARRIER

(See general note 1)




MOD. TALL NARROW BASE SHLDR. BARRIER

NOTE: Only use against retaining walls or as directed.
(For details not shown, see Std. Dwg. No. RD545)



SECTION D-D



ISOMETRIC VIEW

- Full width continuous key

CALC. BOOK NO. _ _ _ _ N/ASDR DATE 15-JUL-2022

NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications

OREGON STANDARD DRAWINGS
TALL CONCRETE BARRIER
(MODIFIED)
AROUND MEDIAN OBSTACLE





2021

DATE	REVISION DESCRIPTION
07-2022	REVISED DETAILS AND NOTES


The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.

Effective Date: December 1, 2022 – May 31, 2023

RD575

**CAST-IN-PLACE TRANSITION
PLAN****SECTION A-A****VIEW B-B****VIEW C-C****GENERAL NOTES FOR ALL DETAILS ON THIS SHEET:**

1. Field verify end configurations of connecting barriers prior to forming connections at transitions.
2. All reinforcing bars shall be full length as shown and shall be placed 1 1/2" clear of the nearest face of concrete unless shown otherwise.
3. See Std. Dwg. RD545 for details not shown.
4. Secure precast concrete barrier to roadway, see Std. Dwg. RD516.
5. All pins, bolts, dowels, loop bars, and connectors shall be hot-dip galvanized after fabrication.


**OPTION 1****OPTION 2****MODIFIED STIRRUP**

CALC. BOOK NO. N/A		SDR DATE 15-JUL-2022	
<i>The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.</i>		NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications	
		OREGON STANDARD DRAWINGS	
		TALL CONCRETE BARRIER (MODIFIED)	
		AROUND MEDIAN OBSTACLE	
		2021	
		DATE	REVISION DESCRIPTION
		07-2022	CREATED NEW DRAWING




1. *All reinforcement shall be full length as shown and shall be 2" clear of nearest face of concrete, unless otherwise shown.*
2. *Maximum chord length for curves with a 1425' radius or less shall be 12.5'. Maximum chord length for curves with radii exceeding 1425' shall be 25'.*
3. *Normal use of precast barrier units is restricted to curvatures with radii greater than 770'.*
4. *Concrete grout for grouting over pins, pinning holes or grouting of scuppers shall be Portland cement grout, weak in strength and of thick consistency, as directed.*
5. *Precast concrete barrier used in medians less than 8' in width shall be secured to roadway. See Std. Dwgs. RD515 and RD516 for details.*
6. *See Std. Dwg. RD501 for details not shown. See Std. Dwg. RD502 for securing concrete barrier to roadway.*
7. *All pins, bolts, dowels, loop bars, and connectors shall be hot-dip galvanized after fabrication.*


The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.




END VIEW




SECTION B-B




SECTION C-C




LONGITUDINAL BAR




LONGITUDINAL SCUPPER BAR




STIRRUP BAR "A"




STIRRUP BAR "B"




PIN SLOT BAR
(When required)



LOOP BAR



PIN DETAIL



STANDARD

ALTERNATE

WASHER DETAIL


PIN NOTE:
Washer shall be forged as integral part of pin or shall be welded as shown.

GENERAL NOTES FOR ALL DETAILS ON THIS SHEET:


1. All reinforcement shall be full length as shown and shall be 2" clear of nearest face of concrete, unless otherwise shown.
2. Concrete grout for grouting over pins, pinning holes or grouting of scuppers shall be portland cement grout, weak in strength and of thick consistency, as directed.
3. See Std. Dwg. RD516 for securing concrete barrier to roadway.
4. All pins, bolts, dowels, loop bars, and connectors shall be hot-dip galvanized after fabrication.

CONNECTING PIN ASSEMBLY DETAIL


CALC. BOOK NO. N/A		SDR DATE 15-JUL-2022	
<i>The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.</i>		NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications	
		OREGON STANDARD DRAWINGS	
		32" PRECAST TYPE "F" CONCRETE BARRIER WITH SCUPPERS REINFORCING	
		2021	
		DATE 07-2022	REVISION DESCRIPTION DRAWING CREATED




JOINT DETAIL
(Curb line sidewalk with curb and gutter shown)



C CONTRACTION JOINT
(See general note 6)



D DUMMY JOINT




E EXPANSION JOINT
(See general notes 2 & 5)

GENERAL NOTES FOR ALL DETAILS ON THIS SHEET:



1. See Std. Dwgs. RD720 and RD721 for concrete sidewalk details. See project plans for sidewalk width, placement and design specified.
2. Provide expansion joints around poles, boxes, at ends of each driveway and other fixtures which protrude through or against the structures. For sidewalk, monolithic curb and sidewalk, provide construction expansion joints at 45 feet maximum spacing.
3. On sidewalks 8 feet and wider, provide a longitudinal joint at the midpoint of sidewalk panel.
4. See Std. Dwgs. RD700 and RD701 for concrete curb details. See project plans for the curb design specified.
5. Do not place expansion joints between separate concrete pours for curb ramp system components construction. Place expansion joints outside of curb ramp runs when required. Install expansion joints flush with surface for structures protruding through the curb ramp system. See Std. Dwg. RD900.
6. Construct contraction joints at 15 feet maximum spacing, and at each curb ramp, driveway, sidewalk and curb.

LEGEND:

- New sidewalk or ramp run
- Slope 1.5% max.
(Max. 2.0% finished surface slope)
(Normal sidewalk cross slope)
- Slope 7.5% max.
(Max. 8.3% finished surface slope)
- Zero exposure



- ★ Project the existing sidewalk profile grade through transition panel to new sidewalk or curb ramp run.



SIDEWALK AND CURB RAMP TRANSITION PANELS

CALC. BOOK NO. **N/A**


SDR DATE **08-JUL-2022**

NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications


OREGON STANDARD DRAWINGS
SIDEWALK JOINTS AND TRANSITION PANELS


2021

DATE	REVISION	DESCRIPTION
07-2022	REVISED NOTES	




LEGEND:

 Detectable warning surface

 Cross slope 1.5% max.
(Max. 2.0% finished surface slope)


PUBLIC TRANSPORTATION STATION
Rail or Transit Service



- NOTES:**
- a. Detectable warning surfaces shall be outside of the dynamic envelope and pedestrian crossing arms where they exist.
 - b. Pedestrian rail crossings are generally perpendicular to the rail. Skew shown for minimum distance of detectable warning surface.

AT-GRADE RAIL CROSSING

Dynamic envelope marking, typical. See general note 6




RAIL TRACK SECTION VIEW

GENERAL NOTES FOR ALL DETAILS ON THIS SHEET:

1. Detectable warning surface details and locations are based on applicable ODOT Standards.
2. See project plans for details not shown. See Std. Dwg. RD902 for detectable warning surface installation details.
3. Place detectable warning surface along the full length of the rail station, when not protected by screens or guards on raised platforms, sidewalk, and street level boarding areas.
4. Place detectable warning surface along the full length of the transit station, when not protected by screens or guards on raised platforms and sidewalk boarding areas.
5. Detectable warning surfaces shall be outside of the dynamic envelope.
6. Dynamic envelope shall be clear of all fixed obstructions unless otherwise shown on Rail Crossing Order.

CALC. BOOK NO. N/A		SDR DATE 15-JUL-2022	
<i>The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.</i>		NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications	
		OREGON STANDARD DRAWINGS	
		DETECTABLE WARNING SURFACE PLACEMENT FOR RAIL	
		2021	
		DATE	REVISION DESCRIPTION
		07-2020	DRAWING CREATED
		07-2022	REVISED DETAIL AND NOTES




3-TUBE CURB MOUNT RAIL

Scale: 1/2"=1'-0"


NOTE

Bridge rails mounted on curb similar.




TYPE "F" CONCRETE RAIL

Scale: 1/2"=1'-0"



VERTICAL CONCRETE PARAPET


Scale: 1/2"=1'-0"



CONCRETE PARAPET WITH STEEL POST

Scale: 1/2"=1'-0"


BRIDGE RAIL TYPES



PROPOSED TEMPORARY BLOCKOUT

NOTE


Blockout joint with sandwich of polyurethane foam and 1/4" to 1/2" plywood as shown prior to placing elastomeric concrete nosing.



SIDEWALK JOINT SECTION

NOTE:
Provide joint seal having firm, stable and slip resistance top surface.


Existing armored corners, remove hatched portion of existing armor horizontal steel angle. Fill the void with elastomeric concrete. Fully intact armor leg may remain in place.



ARMORED JOINT WITH OVERLAY

NOTE


Use details for joint rehabilitation. When existing armor leg remains in place. See project plans and specifications for surface preparation before elastomeric concrete placement.



ARMORED JOINT SECTION

NOTE

Use details for new construction.




NON-ARMORED JOINT SECTION



NOTE

Use details for new construction and joint rehabilitation. Elastomeric concrete nosing may be omitted, when concrete joint surfaces are in good condition.

Preformed Compression Joint Seal						
Seal Type	Total Movement Range	Nominal Size		Joint Width		Minimum Installation Width
		Width	Height	Min.	Max.	
A	1/2"	1 1/4"	1 1/4"	1/2"	1"	3/4"
B	3/4"	2"	2"	7/8"	1 5/8"	1 1/4"
C	1"	2 1/2"	2 3/4"	1"	2"	1 1/2"
D	1 1/4"	3"	3 1/4"	1 1/4"	2 1/2"	1 3/4"
E	1 1/2"	3 1/2"	3 1/2"	1 3/8"	2 7/8"	2 1/4"



CORNER DIAGRAM

NOTES:


See project plans for joint size and details not shown.

Blockout joint with temporary blockout prior to placing elastomeric concrete nosing. See Proposed Temporary Blockout detail this sheet.

Prepare joint surfaces and install preformed compression joint seal (gutter to gutter) in one continuous piece.


See dwg. BR141 for joint armor when shown on project plans.

CALC. BOOK NO. _ _ _ _ _		SDR DATE: 08-July-2022	
<p>The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.</p>		NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications	
		OREGON STANDARD DRAWINGS	
		PREFORMED COMPRESSION JOINT SEAL	
		2022	
		DATE	REVISION DESCRIPTION
		06-2022	Revised sidewalk details.
		06-2022	Added joint note.
		-	-
		-	-




3-TUBE CURB MOUNT RAIL
Scale: 1/2"=1'-0"


NOTE
Bridge rails mounted on curb similar.



VERTICAL CONCRETE PARAPET
Scale: 1/2"=1'-0"




TYPE "F" CONCRETE RAIL
Scale: 1/2"=1'-0"




CONCRETE PARAPET WITH STEEL POST
Scale: 1/2"=1'-0"

BRIDGE RAIL TYPES




PROPOSED TEMPORARY BLOCKOUT

NOTE
Blockout joint with sandwich of polyurethane foam and 1/4" to 1/2" plywood as shown prior to placing elastomeric concrete nosing.



ARMORED JOINT SECTION


NOTE
Use details for new construction.



NON-ARMORED JOINT SECTION

NOTE
Use details for new construction and joint rehabilitation. Elastomeric concrete nosing may be omitted, when concrete joint surfaces are in good condition.


Existing armored corners, remove hatched portion of existing armor horizontal steel angle. Fill the void with elastomeric concrete. Fully intact armor leg may remain in place.



ARMORED JOINT WITH OVERLAY

NOTE
Use details for joint rehabilitation. When existing armor leg remains in place. See project plans and specifications for surface preparation before elastomeric concrete placement.

Poured Joint Seals			
Total Movement Range (max.)	Joint Width		Minimum Installation Width
	Min.	Max.	
1 1/2"	1/4"	1"	1/2"
	1/2"	2"	1"
	1"	2 1/2"	1 1/2"
	1 1/2"	3"	2"



NOTE:
Provide joint seal having firm, stable and slip resistance top surface.

SIDEWALK JOINT SECTION

NOTES:
See project plans for joint size and details not shown.

Blockout joint with temporary blockout prior to placing elastomeric concrete nosing. See Proposed Temporary Blockout detail this sheet.

Prepare joint surfaces. Install bond breaker backer rod, and install poured joint seal in one continuous piece. (gutter to gutter)

For joint armor when shown on the project plans, see dwg. BR141.

CALC. BOOK NO. -

SDR DATE: 08-July-2022

NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications

OREGON STANDARD DRAWINGS
POURED JOINT SEAL

2022

DATE REVISION DESCRIPTION

06-2022 Revised sidewalk details.

06-2022 Revised joint recess, notes and joint table.

-

-

-


-

The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.

07-2022


br222.dgn

BR222




Accompanied by dwg. BR203, BR221


CALC. BOOK NO. -		SDR DATE: 08-July-2022	
The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.		NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications	
		OREGON STANDARD DRAWINGS	
		VERTICAL CONCRETE	
		PARAPET, 42 INCH	
		2022	
DATE	REVISION	DESCRIPTION	
		07-2021 Note changes, CAD edits	
		01-2022 Modified detail notes and dimensions.	
		06-2022 Modified dimension.	
-	-		
-	-		



SOCKET WELD




POST CAP




NOTE
Alternate orientation of slotted holes on the lower clip angle.

SECTION A-A

(See dwg. BR240 for location of Section A-A)




SECTION B-B




TYPE "C" FENCE


NOTE
As an alternate to resin bonded anchor use 2- 3/4 inch dia. x 5 inch embedment concrete insert with minimum safe working loads in 3300 psi concrete of 4.3 kips tension.



SECTION C-C




PLAN




TYPE "B" FENCE


NOTE
Longitudinal sidewalk reinforcement not shown for clarity.



SECTION D-D




TYPE "A" FENCE




SECTION E-E

Accompanied by dwg. BR240 and BR242


CALC. BOOK NO. -		SDR DATE: 08-July-2022	
The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.		NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications	
		OREGON STANDARD DRAWINGS	
		PROTECTIVE FENCING	
		DETAILS-1	
		2022	
DATE		REVISION DESCRIPTION	
06-2022		Revised angle size callout	
-		-	
-		-	
-		-	




**ELEVATION: CONCRETE BRIDGE RAIL
(FIXED FORMS)**



**EXPANSION JOINT COVER PLATE
(When Required by Bridge Plans)**




SECTION A-A




DETAIL "A"

**SCORING JOINT DETAIL
(SLIP-FORMED)
(FIXED FORMS)**




SECTION C-C

**TYPE "B" JOINT DETAIL
(SLIP-FORMED)**




SECTION D-D

**OPEN OR EXPANSION JOINT DETAIL
(SLIP-FORMED OR FIXED FORMS)**




SECTION B-B


**TYPE "B" JOINT DETAIL
(FIXED FORMS)**



Detail "C"



DETAIL "B"




**PLAN: BARS AT OPEN
OR EXPANSION JOINTS
AND RAIL ENDS**

NOTES:
Place top of parapet 3'-6" above finish grade. Increase dimensions marked thus () by depth of ACWS.
**Continuous thru scoring joints. Stop 2" clear at ends and all other joints.
See dwg. BR291 for rail on end panel.
***See PLAN: BARS AT OPEN or EXPANSION JOINTS AND RAIL ENDS

ESTIMATED QUANTITIES


	3'-6" Ht.	1" added Ht.
Concrete	3.45 ft. ³ /ft.	0.12 ft. ³ /ft.
Bars "a" & longit.	17.3 #/ft.	—

Bar weight assume joints at 15'-0" ctrs.



Use when water drains towards rail and no deck joint seal is used.
Use joint fillers for length of joint opening "J"+6".

DETAIL "D"






TYPICAL SECTION (FIXED FORMS)

GENERAL NOTES:
Rail designed and crash tested to meet NCHRP 350 TL-5 requirements. Provide all reinforcing steel conforming to ASTM A706 or AASHTO M31 (ASTM A615) Grade 60. Place all bars 2" clear of the nearest face of concrete unless shown otherwise. Splice #4 bars 1'-4" min., splice #5 bars 1'-8" min. Provide Class 3300 - 1 1/2 or 3/4 concrete. Provide steel cover plates conforming to AASHTO M183 (ASTM A36). Hot-dip galvanize after fabrication. At skewed bents up to 20° make joints parallel to the bent center line. For skews greater than 20° make joints normal to rail.

Accompanied by dwg. BR291

CALC. BOOK NO. _ _ _ _ _		SDR DATE: 08-July-2022	
<p>The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.</p>		NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications	
		OREGON STANDARD DRAWINGS TYPE "F" CONCRETE RAIL, 42 INCH	
		2022	
		DATE	REVISION DESCRIPTION
		06-2022	Modified dimensions.
		-	-
		-	-
		-	-
		-	-



CALC. BOOK NO.

SDR DATE: 08-July-2022

NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications

OREGON STANDARD DRAWINGS
12" PRECAST
PRESTRESSED SLAB





2022

DATE	REVISION DESCRIPTION
07/2020	Revised stirrup and tie bar spacing
07/2020	Updated drawing to current stds.
07/2022	Added breakout angle.
-	-
-	-

The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.

Effective Date: December 1, 2022 - May 31, 2023





BR400



NOTE "A" (Slab End Bars)
2- #4 x 7'-6", slab 5
2- #4 x 10'-0", slabs 6, 7, and 8
2- #4 x 12'-6", slab 9
Place bars each end of each slab (Epoxy coat).





NOTE:
Grout keyway as specified in General Notes.
Omit keyway on exterior side of exterior slabs.
Keyway is continuous.

SECTION PROPERTIES	
Area =	562in ²
c.g. =	7.45 in
I =	12,769 in ⁴
St =	1691 in ³
Sb =	1714 in ³
Weight =	605 lbs/ft
J =	31,900 in ⁴
K =	0.69
V/S =	4.46
Form wt =	10 lbs/ft
(tubes)	
Total wt	
w/forms=	615 lbs/ft
Diaphragm Weight	
No Skew	170 lb
15° Skew	270 lb
30° Skew	470 lb
45° Skew	750 lb



Accompanied by dwg. BR445





CALC. BOOK NO. -		SDR DATE: 08-July-2022	
<p>The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.</p>		NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications	
		OREGON STANDARD DRAWINGS	
		15" PRECAST PRESTRESSED SLAB	
		2022	
		DATE	REVISION DESCRIPTION
		07/2020	Added end zone relnf.
		07/2020	Revised debonded lengths
		07/2020	Updated drawing to current stds.
		01/2022	Revised #4 bars to be inside of #4 stirrup, Removed "D1" hoop notation.
		07/2022	Added breakout angle.



NOTE "A" (Slab End Bars)
2- #4 x 10'-0", slabs 4, 5, and 6
4- #4 x 15'-0", slabs 7, 8 and 9
Place bars each end of each slab (Epoxy coat).

NOTE:
Grout keyway as specified in General Notes.
Omit keyway on exterior side of exterior slabs.
Keyway is continuous.





SECTION PROPERTIES	
Area =	621 in ²
c.g. =	8.94 in
I =	21,626 in ⁴
St =	2386 in ³
Sb =	2420 in ³
Weight =	668 lbs/ft
J =	52,200 in ⁴
K =	0.71
V/S =	4.70
Form wt =	14 lbs/ft
(tubes)	
Total wt	
w/forms =	682 lbs/ft
Diaphragm Weight	
No Skew	260 lb
15° Skew	430 lb
30° Skew	740 lb
45° Skew	1170 lb



Accompanied by dwg. BR445






CALC. BOOK NO. -		SDR DATE: 08-July-2022	
<p>The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.</p>		NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications	
		OREGON STANDARD DRAWINGS	
		18" PRECAST PRESTRESSED SLAB	
		2022	
		DATE	REVISION DESCRIPTION
		07/2020	Added end zone reinf.
		07/2020	Revised debonded lengths
		07/2020	Updated drawing to current stds.
		07/2022	Added breakout angle.
		-	-





NOTE "A" (Slab End Bars)
2- #4 x 10'-0", slabs 6 and 7
4- #4 x 12'-6", slabs 8, 9, 10, 11, 12 and 13
Place bars each end of each slab (Epoxy coat).

NOTE:
Grout keyway as specified in General Notes.
Omit keyway on exterior side of exterior slabs.
Keyway is continuous.



SECTION PROPERTIES


Area =	851 in ²
c.g. =	12.92 in
I =	63,596 in ⁴
St =	4862 in ³
Sb =	4923 in ³
Weight =	916 lbs/ft
J =	128,800 in ⁴
K =	0.77
V/S =	5.75
Form wt =	20 lbs/ft (tubes)
Total wt	
w/forms =	936 lbs/ft

Diaphragm Weight

No Skew	430 lb
15° Skew	710 lb
30° Skew	1230 lb
45° Skew	1940 lb

Accompanied by dwg. BR445


CALC. BOOK NO. -		SDR DATE: 08-July-2022	
<p>The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.</p>		NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications	
		OREGON STANDARD DRAWINGS	
		26" PRECAST PRESTRESSED SLAB	
		2022	
		DATE	REVISION DESCRIPTION
		07/2020	Added end zone reinf.
		07/2020	Revised debonded length.
		07/2020	Updated drawing to current stds.
		07/2022	Added breakout angle.
		-	-



NOTE "A" (Slab End Bars)
2- #5 x 10'-0", slabs 2 and 3
4- #5 x 10'-0", slabs 4, 5 and 6
4- #5 x 12'-6", slabs 7, 8 and 9
4- #5 x 15'-0", slabs 10, 11, 12 and 13
Place bars each end of each slab (Epoxy coat).


NOTE:
Grout keyway as specified in General Notes.
Omit keyway on exterior side of exterior slabs.
Keyway is continuous.

SECTION PROPERTIES	
Area =	938 in ²
c.g. =	14.91 in
I =	97,278 in ⁴
St =	6447 in ³
Sb =	6524 in ³
Weight =	1009 lbs/ft
J =	180,800 in ⁴
K =	0.80
V/S =	6.01
Form wt =	27 lbs/ft (tubes)
Total wt	
w/forms=	1036 lbs/ft
Diaphragm Weight	
No Skew	550 lb
15° Skew	900 lb
30° Skew	1560 lb
45° Skew	2380 lb



Accompanied by dwg. BR445


CALC. BOOK NO. -		SDR DATE: 08-July-2022	
<i>The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.</i>		NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications	
		OREGON STANDARD DRAWINGS	
		30" PRECAST PRESTRESSED SLAB	
		2022	
		DATE	REVISION DESCRIPTION
		07/2020	Added end zone reinf.
		07/2020	Revised debonded lengths and locations.
		07/2020	Updated drawing to current stds.
		07/2022	Added breakout angle.
		-	-



TYPICAL DETAIL FOR INSTALLING BOXES OR SLABS ON CROWN

NOTE:
Tighten tie rods until the bottom corners of the boxes or slabs are in contact. Loosen the tie rod and install the plates and wedges per detail. Shift wedge location as required to avoid conflict with the tie rod.

Tension the tie rods. Install boxes or slabs level and build up roadway crown with AC wearing surface when roadway width is 28' or less (for bridges with ACWS).



TIE ROD DETAIL






PLATE AND WEDGE DETAIL

NOTE:
Add steel plates and wedge at each tie rod crossing before tensioning tie rods. Hot-dip galvanize wedges and plates.




DETAIL "A" Non-Tensioning End

NOTE:
1 3/4 inch @ tie rod center (2 1/2 inch depth may be used for slabs with an appropriate reduction in tie rod length)



KEYWAY GROUT DETAIL



DETAIL "B" Tensioning End

NOTE:
Form recess bearing area perpendicular to tie rod as shown. Use Detail "B" at tensioning end of tie rod.

GENERAL NOTES FOR PRESTRESSED BOXES AND SLABS

Boxes and slabs are designed for live and superimposed dead loading as shown in the General Notes for the Project. Provide the class of concrete shown in the Slab or Box Schedule with nominal maximum size aggregate of 1 or 3/4. Transfer prestress after the concrete reaches the minimum concrete strength at transfer shown in the Slab or Box Schedule.

Select a keyway grout from the QPL for filling keyways, lifting blockouts and tie rod blockouts.

Allow traffic on the bridge only after keyway grout has reached design strength.

Provide reinforcing steel as specified in the General Notes for the Project.

Provide smooth dowels conforming to AASHTO M31, Grade 60 (ASTM A615, Grade 60), ASTM F1554, Grade 55 or ASTM A529, Grade 55.


Provide 1/2 inch diameter 7 wire low relaxation prestressing steel strand conforming to AASHTO Specification M203 (ASTM A416), Grade 270 Supplement 1.

Tension strand initially to 31.0 kips per strand (after harping deflected strand). Debond strands where specified using either split or solid plastic sheathing with a minimum wall thickness of 0.025.

Provide high strength tie rods conforming to ASTM A449. Provide heavy hexagon nuts conforming to ASTM A563. Provide hardened steel washers conforming to ASTM F436. Hot-dip galvanize tie rods, plates, nuts and washers (except DTIs) after fabrication.


Tighten tie rods to 39 kips (minimum) using mechanically galvanized direct tension indicators (DTIs) conforming to ASTM F959 and ASTM F3125, Grade A325. Tighten all tie rods (per box or slab) to about one half the specified tension before proceeding with final tensioning.

Keep boxes and slabs upright at all times. Support them within 2'-0" of the ends during storage (to prevent excessive camber, overstress or failure). Locate transport supports and lifting devices within 2'-0" of the ends of boxes and slabs. Transport boxes and slabs after the concrete has reached the 28 day design strength and a minimum of 7 days after casting.




BREAKOUT ANGLE DETAIL

NOTE:
Provide steel angle conforming to ASTM A36. Hot-dip galvanize breakout angle after fabrication. Shift headed studs as required, no more than 2", to avoid prestressing strands.




PARTIAL ELEVATION CHAMFER DETAIL

CALC. BOOK NO. --		SDR DATE: 08-July-2022	
<i>The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.</i>		NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications	
		OREGON STANDARD DRAWINGS	
		PRECAST PRESTRESSED	
		BOX AND SLAB DETAILS	
		2022	
		DATE	REVISION DESCRIPTION
		07/2020	Revised steel grade for dowels and tie rods.
		07/2020	Updated drawing to current stds.
		07/2020	Moved rail anchorage detail to det3465.
		06-2022	Revised General Notes. Added breakout Angle Detail.
		--	--



Pedestal Foundation Number	Max. Assembly Height	Foundation Depth	Depth of Square Foundation	Anchor Rods (ASTM F 1554 Grade 36)	Reinforcing Steel			Collar
					Vertical Rebar	Hoop Size & Spacing	Hoop Lap Length	
1	6' - 0"	2' - 0"	4"	3/4" x 18" x 4" (6" Thread)	N/A	N/A	N/A	N/A
2	10' - 0"	3' - 0"	4"					
3	20' - 6"	8' - 0"	12"	1" x 36" x 4" (6" Thread)	8-#6	#4-12"	6" with 2 hooks	Req'd


PEDESTAL FOUNDATIONS



DETAIL A - FRANGIBLE BASE

General Notes:

1. All Bolts, Nuts And Washers To Conform To 02560.20 And Be Galvanized Steel According To 02560.40 Unless Noted Otherwise.
2. All Anchor Rods To Be Galvanized Steel Conforming To 02560.30.
3. All Pole Entrances Containing Wiring To Be Smooth.
4. Install 1/4" Thick Preformed Expansion Joint Filler Around Footing In Sidewalk Areas.
5. The Entire Foundation To Be Located On A Single Plane With Less Than 3% Slope. The Flat Edge(s) Of The Foundation May Be Adjacent To The Turn Space, Back Of Walk, Or A Curb Ramp Grade Break Line.
6. Install Commercial Grade Concrete Pad Above Rough Float Surface With Top Surface Matching Sidewalk Grade And Less Than 1/4" Vertical Exposure From Adjacent Grade. Clean Rough Float Surface Prior To Placing Fresh Concrete By Removing All Scum, Laitance, Loose Gravel, And Sediment. Pour During Sidewalk Installation After Installing Pipe And Appurtenances.
7. Non-Shrink High Early Strength Grout (Non-Ferrous) with 3/4" Diameter Pole Drain And A Minimum Strength of 5000 psi. Do Not Use Footing Concrete.




Notes:

1. Equipment Shown In The Assembly Detail Is An Example Of The Equipment That May Be Mounted. Install Equipment As Shown.
2. See TM492 For Ramp Meter Pedestal Mounting Details.
3. See TM493 For RRFB Pedestal Mounting Details.



TRAFFIC SIGNAL PEDESTAL ASSEMBLY

CALC. BOOK NO. _ N/A _ _ _ _ _		SDR REPORT DATE 8-Jul-2022		
<p><i>The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.</i></p>		NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications		
		OREGON STANDARD DRAWINGS		
		PEDESTAL FOUNDATION AND TRAFFIC SIGNAL ASSEMBLY		
		2021		
		DATE	REVISION DESCRIPTION	
		01/21	Updated All Anchor Rod Details. Corrected Std. Dwg. Reference	
		7/22	Complete redesign of foundation and installation procedure	


The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.




STANDARD PUSHBUTTON



SIGN FOR PEDESTRIAN SIGNALS



SIGN FOR WARNING BEACON ASSEMBLY





PEDESTRIAN SIGNAL MOUNT (CLAM SHELL)

General Notes:

1. All Screws, Bolts, Nuts And Washers To Be Type 304 Or 316 Stainless Steel Unless Noted Otherwise.
2. Bolts And Screws To Have Square Or Hex Heads. Allen Head Fasteners Not Allowed.
3. Drill And Tap Pole As Per Orientation Shown On Plans.
4. Horizontal Reach To The Pushbutton To Be 10 Inches Maximum. See Plans Or Consult Engineer To Ensure Compliance.

NOTES:

1. Where Two Heads Are Side Mounted On 4" Conduit, Proper Clearance To Be Maintained To Allow Legend To Be Fully Visible.
2. Clam Shells To Be Orientated So That The Heads Can Be Opened For Maintenance. (Verify Hinge Placement Of Clamshell).



CLAM SHELL ORIENTATION

CALC. BOOK NO. _ N/A _

SDR REPORT DATE 8-Jul-2022


NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications

OREGON STANDARD DRAWINGS
PEDESTRIAN SIGNAL MOUNT
AND
PEDESTRIAN PUSHBUTTON
DETAILS


2021

DATE	REVISION	DESCRIPTION
7/22	Added R10-25 sign. Added extension mounting note for 2 pushbuttons on same 4" dia. pole.	

The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.




SECTION B-B



JUNCTION BOX INSTALLATION
IN UNSURFACED AREA


(This Detail Only Applicable for Junction Boxes Located In Incidental Travel Areas; Gravel Shoulders, Behind Guardrail, Etc. Do Not Install In Travel Lanes, Paved Shoulders, Or Other Areas Exposed To Traffic.)



SECTION A-A


JUNCTION BOX INSTALLATION IN PCC SIDEWALK

(This Detail Only Applicable for Junction Boxes Located In Flat Areas Of Sidewalks. Do Not Install In Slopes Of Ramps Or Driveways)




In The Tandem JB/3 Nearest The Controller Cabinet Install Signal And Illumination Wiring In One JB/3 And Detector And Interconnect Cables In The Other JB/3


TANDEM JB/3A JUNCTION BOX DETAILS



DELINEATION OF JUNCTION BOX & HAND HOLE IN UNSURFACED AREA




JUNCTION BOX
COVER DETAILS



Type*	L	W	D
JB1	17"	10"	12"
JB2	22"	12"	12"
JB3	30"	17"	12"
HH-1	24"	30"	24"
HH-2	30"	48"	24"
HH-3	30"	48"	36"

*Junction Box Or Handhole Type As Shown On Plans

DIMENSION TABLE



FIBER OPTIC CABLE HAND HOLE INSTALLATION

CALC. BOOK NO. _ N/A _ SDR REPORT DATE _ 8-Jul-2022 _

NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications


OREGON STANDARD DRAWINGS

JUNCTION BOXES/ HAND HOLES


2021

DATE	REVISION	DESCRIPTION
7/22	Added new marking (ILLUMINATION & ELECTRICAL) for JB cover	

The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.



RAMP METER SIGNAL ASSEMBLY



RAMP METER ADVANCE WARNING SIGN ASSEMBLY

General Notes:

1. Equipment Shown In the Assembly Details Is An Example Of The Equipment That May Be Mounted. Install Equipment As Shown.
2. Do NOT Install Assemblies Within Paved Gore Area.
3. Locate Ramp Meter Signal Assembly 25'- 0" Beyond Stop Line Or As Shown.

CALC. BOOK NO. N/A

SDR REPORT DATE 8-Jul-2022

NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications


OREGON STANDARD DRAWINGS

RAMP METER ASSEMBLIES

2021


DATE	REVISION	DESCRIPTION
01/21	Revised Drafting, Added Radar Mount Reference, Added Sloped	
1/22	Ground Details, Changed Note 2 From 10 To 25 Feet.	
7/22	Referenced TM457 for all pipe info	
	Revised to match TM457 revisions/format	

TM493



- Note:
- Equipment Shown In the Assembly Detail Is An Example Of The Equipment That May Be Mounted. Install Equipment As Shown.
 - This detail is also applicable to mounting RRFB equipment on a large signal pole.







RECTANGULAR RAPID FLASHING BEACON PEDESTAL ASSEMBLY
(Use Green Sheet Listed Items Only)



RECTANGULAR RAPID FLASHING BEACON MAST ARM ASSEMBLY
(Use Green Sheet Listed Items Only)

CALC. BOOK NO. <u> N/A </u>		SDR REPORT DATE <u> 8-Jul-2022 </u>	
<i>The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.</i>		NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications	
		OREGON STANDARD DRAWINGS	
		RECTANGULAR RAPID FLASHING BEACON (RRFB) ASSEMBLIES	
		2021	
		DATE	REVISION DESCRIPTION
		7/22	New Drawing

TM530.dgn 7-06-2022



* = Refer to Std Dwg RD916

General Note:
1. Install crosswalk bars such that the throat of the ADA ramp is entirely within crosswalk markings, or 5' back of extended fog line, edge of pavement, or curb face.

LEGEND

← Direction of Travel

L - Lane line dimensions are shown on the striping plans

To be accompanied by Standard Dwg. Nos. TM500 thru TM504


CALC. BOOK NO. N/A	SDR DATE July 06, 2022
NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications	
OREGON STANDARD DRAWINGS INTERSECTION PAVEMENT MARKINGS (CROSSWALK, STOP BAR & BIKE LANE STENCIL)	
2021	
DATE 7/06/22	REVISION DESCRIPTION Added Roadway Standard Drawing reference to detail for clarity

The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.


Effective Date: December 1, 2022 - May 31, 2023

TM530


TM530




DRILLED SHAFT DETAILS
No Scale




SECTION A-A




SECTION B-B



LAPPED SPLICE



MECHANICAL SPLICE
(Not allowed for ASTM A82 spirals)



WELDED SPLICE

SPIRAL SPLICE DETAIL
No Scale

GENERAL NOTES:

Use ASTM A706 for all welded splices, except ASTM A615 Grade 60, ASTM A82 or ASTM A496 may be used if copies of the chemical composition analysis are submitted and approved as weldable by the Engineer.

Anchor spirals at each end or discontinuity with one extra turn and a splice to itself as shown. Where permitted on plans, provide closed hoops conforming to the requirements of this detail.

Securely tie CSL tubes to reinforcement.

Use temporary casing as required. Permanent casing not permitted.

Cap concrete shall be Class 3600 - $\frac{3}{4}$ " commercial grade, classified as a structural item. Remainder of shaft shall be Class 4000 - $\frac{3}{8}$ " without air entrainment and with $8 \frac{1}{2}$ " \pm $1 \frac{1}{2}$ " slump.

Contractor shall field verify elevations prior to installation.

The transition between the $3 \frac{1}{2}$ " to 6" pitches may use two separate spiral cages with $1 \frac{1}{2}$ " horizontal turns at the start and end of each cage and the lapped splice details between the cages.

Note:

The base plate reactions shown in the table are worst case Extreme I and Service I loads. Engineer of Record to specify shaft depth and confirm shaft design for local soil conditions based on a site specific geotechnical study and loads shown in table. If shaft size or reinforcement shown in table are not adequate for local soil conditions, Engineer of Record must adjust the shaft design accordingly.

The shafts designs shown in table were based on an analysis to encompass worst case soil conditions by applying Extreme I loads to the top of shaft and analyzing below ground shaft forces using Brom's method for two different soil types. The assumed cohesive soil minimum undrained shear strength, c , is 600 psf. The assumed non-cohesive soil friction angle is 25 degrees and bulk weight is 100 pcf.

Monotube Cantilever Design No.	Monotube VMS/Sign Bridge Design No.	Reinf. Steel	Shaft Dia.	No. of CSL Tubes	Reaction At Base Plate (Factored)				Reaction At Base Plate (Service)			
		"a"	"D"	"b"	Axial (lb)	Shear (lb)	Moment (ft-lb)	Torsion (ft-lb)	Axial (lb)	Shear (lb)	Moment (ft-lb)	Torsion (ft-lb)
1	-	30 - #9	5'-0"	6	22,600	26,200	839,000	672,000	20,500	10,100	384,000	259,000
2	-	30 - #9	5'-0"	6	28,100	20,000	784,200	707,000	25,500	8,500	501,200	279,000
3	-	30 - #9	5'-0"	6	18,400	19,600	622,000	517,000	16,700	7,700	293,000	204,000
4	-	30 - #9	5'-0"	6	21,800	13,200	500,800	430,000	19,800	5,200	339,200	169,000
5	-	30 - #9	5'-0"	6	16,900	13,400	431,600	357,000	15,300	5,300	222,000	140,000
6	-	24 - #9	4'-6"	5	12,800	12,300	381,000	240,000	11,600	4,900	171,000	94,000
7	-	24 - #9	4'-6"	5	13,000	7,200	268,000	222,000	11,800	2,800	181,000	87,000
8	-	20 - #9	4'-0"	5	7,800	5,600	170,000	110,000	7,100	2,200	86,000	44,000
9	-	30 - #9	5'-0"	6	26,900	26,500	884,000	745,000	24,400	10,500	498,000	294,000
-	1	30 - #9	5'-0"	6	36,800	40,700	952,600	396,000	33,400	27,000	449,600	156,000
-	2	30 - #9	5'-0"	6	28,500	30,300	754,700	252,000	25,900	17,900	343,500	99,500
-	3	30 - #9	5'-0"	6	23,200	22,900	592,300	128,700	21,100	12,100	261,700	51,000

Accompanied by dwgs. TM621, TM622, TM623, TM624, TM625, TM626, TM627

CALC. BOOK NO. 6921-6930, 6969-6972 6974	SDR DATE 08-JUL-2022											
<i>The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.</i>	NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications											
	OREGON STANDARD DRAWINGS											
	STD. MONOTUBE SIGN/VMS SUPPORT DRILLED SHAFT DETAILS											
	2021											
	<table><tr><th>DATE</th><th>REVISION DESCRIPTION</th></tr><tr><td>07/20</td><td>Added "Monotube" to the design number columns.</td></tr><tr><td>01/21</td><td>Changed conduit note.</td></tr><tr><td>01/22</td><td>Slump was 8" ± 1/2".</td></tr><tr><td>07/22</td><td>Added spiral tie notes and conduit base plate note.</td></tr><tr><td></td><td></td></tr></table>	DATE	REVISION DESCRIPTION	07/20	Added "Monotube" to the design number columns.	01/21	Changed conduit note.	01/22	Slump was 8" ± 1/2".	07/22	Added spiral tie notes and conduit base plate note.	
DATE	REVISION DESCRIPTION											
07/20	Added "Monotube" to the design number columns.											
01/21	Changed conduit note.											
01/22	Slump was 8" ± 1/2".											
07/22	Added spiral tie notes and conduit base plate note.											

tm656.dgn 08-JUL-2022

TM656

GENERAL NOTES:

1. Signal supports shall be designed in accordance with the AASHTO Standard Specifications for Structural Supports for Highway Signs, Luminares and Traffic Signals LRFD 1st edition with 2017 and 2018 interim revisions.
2. All traffic signal supports shall conform to the design criteria and details shown on these drawings except as approved by the Engineer.
3. The design basic wind speed (3 second gust) shall be 145 mph, gust factor $G = 1.14$, 50 yr recurrence, Fatigue Category I, no galloping, and truck speed = 65 mph.
4. The design service basic wind speed (3 second gust) shall be 91 mph.
5. Signal poles from this standard are not allowed over highways I-5, I-84, I-205, I-405, US 26 (Sunset Hwy) between mile points 64.3 – 73.0, I-105, and I-82.
6. Pole and arm shafts must be round. Dimensional tolerances of ASTM A595 shall apply to all tapered steel tubing members. Additionally, the diameter of round tapered steel tubing members not vary more than 2% from specified dimension. Two ply and fluted poles or arms are not permitted.
7. Pole taper shall be equal to .0117 in/in.
8. Anchor rods shall conform to ASTM Specification F1554 Gr. 55, Supplemenetary Requirement "S2" that include grade and manufacturer's identification.
9. High strength bolts shall conform to ASTM Specification F3125 Grade A325 Type 1.
10. Nuts for high strength bolts shall be heavy hex and conform to ASTM A563 Grade DH with supplementary requirements "S1" and "S2".
11. Hardened steel washers shall conform to ASTM F436 Type 1.
12. Direct Tension Indicators (DTI) shall be the compressible-washer type, mechanically galvanized, conforming to ASTM F959.
13. Steel sheet for poles and arm shall conform ASTM A595, Grades A or B, ASTM A572 Gr. 50, or approved equal. All other steel sheet and plate shall conform to AASHTO specification M223 (ASTM A572), or approved equal. Supplement S18 of ASTM A6 regarding maximum tensile strength shall apply.
14. All structural steel including fasteners shall be hot dip galvanized after fabrication unless otherwise noted.
15. Galvanize-Control Silicon, typical. Silicon content of the base metal shall be in the range of 0 to 0.06% or 0.13% to 0.25%.
16. Footing concrete shall be according to TM628.
17. Reinforcing steel shall conform to AASHTO M31, Grade 60 (ASTM A615 or A706). A min. lap splice length of 32 bar diameters shall be used unless shown otherwise.
18. Computed deflection of these poles at full design loading shall be limited to 5% of the pole length. Computed dead load deflection of the poles shall be limited to 1% of the pole length. Rake pole, apply mast arm and appurtenance loads, and verify final pole position is plumb.
19. Luminaire arms and pole extensions to support luminaire arms shall meet requirements of drawing TM629.
20. Hubs for cabinets and/or other appurtenances shall be welded into the pole prior to galvanizing. Poles may be tapped for up to 1" galvanized bolts after pole has been galvanized.
21. Longitudinal seam welds within 6" of a cirumferential weld shall be complete penetration welds. Weld inspection shall be in accordance with AWS D1.1 and the special provisions. Inspect seam welds using cyclically loaded criteria. Hubs shall be 3000# threaded forged carbon steel flat weld hubs by Anvil Products Inc., Phoenix Forging Co., Bonney Forge & Tool Works or approved equal.
22. Grounding terminal shall be 1/2" UNC x 1 1/2" Type 308, 309 or 310 threaded stainless steel weld studs.
23. Tighten 4 bolt connection bolts in accordance with 962.46(j)(2).
24. Tighten 8 bolt arm connection bolts in accordance with 930.40(d).
25. Round and smooth all edges along electrical way.

Signal Pole Type	Reaction At Base Plate (Factored)				Reaction At Base Plate (Service)			
	Axial (lb)	Shear (lb)	Moment (ft-lb)	Torsion (ft-lb)	Axial (lb)	Shear (lb)	Moment (ft-lb)	Torsion (ft-lb)
SM6L	7,430	13,000	301,000	322,000	6,520	5,200	163,000	127,000
SM7L	8,860	13,100	349,000	385,500	8,080	5,190	212,720	153,000

Note:
The base plate reactions shown in the table are worst case Extreme I and Service I loads. Engineer of Record to specify shaft depth and confirm shaft design for local soil conditions based on a site specific geotechnical study and loads shown in table. If shaft size or reinforcement shown in the table on TM628 for the required design number are not adequate for local soil conditions, Engineer of Record must adjust the shaft design accordingly.

Accompanied by dwgs. TM654, TM655, TM657, TM658, TM628

CALC. BOOK NO. 7088		SDR DATE 08-JUL-2022	
<i>The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.</i>		NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications	
		OREGON STANDARD DRAWINGS	
		TRAFFIC SIGNAL 60' THROUGH 75' MAST ARM SUPPORTS	
		NOTES AND REACTIONS	
		2021	
		DATE	REVISION DESCRIPTION
		07/20	Added Accompanied by dwg TM654.
		07/22	Added Reactions to title and added reactions table.

TAPER TYPES & FORMULAS	
TAPER	FORMULA
Merging (Lane Closure)	"L"
Shifting	"L"/2 or ½"L"
Shoulder Closure	"L"/3 or ⅓"L"
Flagging (See Drg. TM850)	50' – 100'
Downstream (Termination)	Varies (See Drawings)

★ Use Pre-Construction Posted Speed to select the Speed from the Tables below:

TEMPORARY BARRIER FLARE RATE TABLE	
★ SPEED (mph)	MINIMUM FLARE RATE
≤ 30	8:1
35	9:1
40	10:1
45	12:1
50	14:1
55	16:1
60	18:1
65	19:1
70	20:1

MINIMUM LENGTHS TABLE					
"L" VALUE FOR TAPERS (ft)					BUFFER "B" (ft)
★ SPEED (mph)	W = Lane or Shoulder Width being closed or shifted				
	W ≤ 10	W = 12	W = 14	W = 16	
25	105	125	145	165	75
30	150	180	210	240	100
35	205	245	285	325	125
40	265	320	375	430	150
45	450	540	630	720	180
50	500	600	700	800	210
55	550	660	770	880	250
60	600	720	840	960	285
65	650	780	910	1000	325
70	700	840	980	1000	365
FREEWAYS					
55	1000	1000	1000	1000	250
60	1000	1000	1000	1000	285
65	1000	1000	1000	1000	325
70	1000	1000	1000	1000	365

NOTES:

- For Lane closures where W < 10', use "L" value for W = 10'.
- For Shoulder closures where W < 10', use "L" value for W = 10' or calculate "L" using formula, for Speeds ≥ 45: L = WS, Speeds < 45: L = S²W/60, S = Speed, W=Width


TRAFFIC CONTROL DEVICES (TCD) SPACING TABLE				
★ SPEED (mph)	Sign Spacing (ft)			Max. Channelizing Device Spacing (ft)
	A	B	C	
20 – 30	100	100	100	20
35 – 40	350	350	350	20
45 – 55	500	500	500	40
60 – 70	700	700	700	40
Freeway	1000	1500	2640	40

NOTES:

- Place traffic control devices on 10 ft. spacing for intersection and access radii.
- When necessary, sign spacing may be adjusted to fit site conditions. Limit spacing adjustments to 30% of the "A" dimension for all speeds.

NOTES:


- When paved shoulders adjacent to excavations are less than four feet wide protect longitudinal abrupt edge as shown.
- Use aggregate wedge when abrupt edge is 2 inches or greater.



EXCAVATION ABRUPT EDGE

NOTES:


- Abrupt edges may be created by paving, operations, excavations or other roadway work. Use abrupt edge signing for longitudinal abrupt edges of 1 inch or greater.
- If the excavation is located on left side of traffic, replace the 8' B(III)R barricades with 8' B(III)L barricades and replace the "RIGHT" (CW21-8C) riders with "LEFT" (CW21-8A) riders.
- Continue signing and other traffic control devices throughout excavation area at spacings shown.
- If roll-up signs are used, attach the correct (CW21-9) plaques to the sign face using hook and loop fasteners. Place roll-up signs in advance of barricades.



TYPICAL ABRUPT EDGE DELINEATION

NOTES:


- Install PCMS beyond the outside shoulder, when possible.
- Use the appropriate type of barricade panels for PCMS location. Right shoulder, use Type B(III)R Left shoulder, use Type B(III)L
- Use six drums in shoulder taper on 20' spacing. The drums and barricade may be omitted when PCMS is placed behind a roadside barrier.
- Detail as shown is used for trailered and non-crashworthy components of:
 - Portable Traffic Signals
 - Smart Work Zone Systems



PORTABLE CHANGEABLE MESSAGE SIGN (PCMS) INSTALLATION

NOTES:

- Install Flagger Station Lighting beyond the outside shoulder, where practical.
- Use six tubular markers in shoulder taper on 10' spacing.
- Place cart / generator / power supply off of the shoulder, as far as practical.



FLAGGER STATION LIGHTING DELINEATION

GENERAL NOTES FOR ALL TCP DRAWINGS:

- Signs and other Traffic Control Devices (TCD) shown are the minimum required.
- Place a barricade approx. 20' ahead of all sequential arrow boards.
- Arrows shown in roadway are directional arrows to indicate traffic movements.
- All signs are 48" x 48" unless otherwise shown. Use fluorescent orange sheeting for the background of all temporary warning signs.
- All diamond shaped warning signs mounted on barrier sign supports shall be 36" by 36". All other signs mounted on barrier sign supports shall not exceed 12 sq. ft. in total sign area.
- Low speed highways have a pre-construction posted speed of 40 mph or less. High speed highways have a pre-construction posted speed of 45 mph or higher.
- Do not locate sign supports in locations designated for bicycle or pedestrian traffic.
- Combine drawing details to complete temporary traffic control for each work activity.
- Coordinate and control pedestrian movements through a Temporary Accessible Route using Flaggers, Traffic Control Measures, or as directed.
- To be accompanied by Dwg. Nos. TM820 & TM821.

CALC. BOOK NO. _ _ _ _ TM09-01 _ _ _ _

SDR DATE _ _ _ _ 01-JUL-2022 _ _ _ _


NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications

OREGON STANDARD DRAWINGS
TABLES, ABRUPT EDGE AND
PCMS DETAILS


2021

DATE	REVISION	DESCRIPTION
07/01/22	Added a note for TPARs.	


The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.




2-Lane, 2-Way
SHOULDER CLOSURE




2-Lane, 1-Way
RIGHT LANE CLOSURE




2-Lane, 2-Way
ONE LANE CLOSURE



4-Lane, 2-Way
RIGHT LANE CLOSURE, NEAR SIDE



4-Lane, 2-Way
RIGHT LANE CLOSURE, FAR SIDE



4-Lane, 2-Way
LEFT LANE CLOSURE, FAR SIDE

- NOTES:
- When work is in place for 14 consecutive days or more, place temporary lane direction legends in mandatory turn lanes, as shown or directed.

- NOTES:
- When work is in place for 14 consecutive days or more, place temporary lane direction legends in mandatory turn lanes, as shown or directed.

GENERAL NOTES FOR ALL DETAILS:

- Additional Traffic Control Measures (TCM) may be required for all legs of the intersection.
- The "SIGNAL AHEAD" (W3-3a) sign may be substituted with the signal ahead symbol (W3-3) sign.
- To determine Taper Length ("L") and Buffer Length ("B"), use the "MINIMUM LENGTHS TABLE" on Dwg. TM800.
- For left lane or shoulder work, place TCD to close left lane or shoulder. Use "LEFT LANE CLOSED AHEAD" (W20-5) sign, "LEFT LANE ENDS" (W4-2L) symbol sign, or "LEFT SHOULDER CLOSED" (W21-5a) sign, where applicable.
- To determine sign spacing A, B, and C, use "TRAFFIC CONTROL DEVICES (TCD) SPACING TABLE" on Dwg. TM800.
- When a through road intersects within the work zone, place a "ROAD WORK AHEAD" (W20-1) sign in advance of the intersection at sign spacing A.
- Tubular markers may be used in lane closure tapers where posted speed is 40 mph or less.
- Where shoulder width is limited, Sequential Arrow may be placed within the lane closure taper.
- Place channelizing devices around intersection radii, business accesses and driveways at 10' spacing.
- Install a "BICYCLES ON ROADWAY" (CW11-1) sign in advance of the closure when a bike lane is closed, or when the shoulder is closed and bikes are expected.
- To be accompanied by Dwg. Nos. TM820, TM821 TM840 & TM854.

- Automated Flagging Assistance Device (AFAD)
- 28" Tubular Markers See TCD Spacing Table on TM800 for max. spacing.
- Temp. Plastic Drums See TCD Spacing Table on TM800 for max. spacing.
- UNDER TRAFFIC
- UNDER CONSTRUCTION

CALC. BOOK NO. _____ N/A _____

SDR DATE _____ 01-JUL-2022 _____

NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications




OREGON STANDARD DRAWINGS

INTERSECTION WORK ZONE DETAILS

2021

DATE	REVISION	DESCRIPTION
07/01/22	Added AFADs to the drawing.	

The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.



GENERAL NOTES FOR ALL DETAILS:

- Install temporary striping as directed.
- Signing and other TCD shown to be installed in conjunction with the work areas, shall move with the work areas.
- To determine Taper Length ("L") and Buffer Length ("B"), use the "MINIMUM LENGTHS TABLE" on Dwg. No. TM800.
- Cover all applicable existing passing lane signing prior to installing TCD.
- Install Type III barricades in closed lanes at 1/4 mile intervals.
- When passing is allowed in opposing lanes, restrict passing with double yellow centerline and appropriate signing as directed.
- Channelization devices may be placed on 10' around the Work Area for emphasis or if the area is to be exposed to traffic on both sides simultaneously.
- Install a "BICYCLES ON ROADWAY" (CW11-1) sign in advance of the closure when a bike lane is closed, or when the shoulder is closed and bikes are expected.


- To determine sign spacing A, B, and C, use "TRAFFIC CONTROL DEVICES (TCD) SPACING TABLE" on Dwg. No. TM800.
 - When the length of the area under construction is less than 600 ft. use a DOUBLE REVERSE CURVE (W24-1) sign in place of the first REVERSE CURVE (W1-4) sign in each direction.
 - • • 28" TUBULAR MARKERS
See TCD Spacing Table on TM800 for max. spacing.
 - • • TEMP. PLASTIC DRUMS
See TCD Spacing Table on TM800 for max. spacing.
- UNDER TRAFFIC
- UNDER CONSTRUCTION

CALC. BOOK NO. _ _ _ _ _ N/A _ _ _ _ _		SDR DATE _ _ _ _ _ 01-JUL-2022 _ _ _ _ _	
<i>The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.</i>		NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications	
		OREGON STANDARD DRAWINGS	
		NON-FREEWAY MULTI-LANE SECTIONS	
		2021	
		DATE	REVISION DESCRIPTION
		07/01/22	Replaced temporary traffic control sign in detail.

tm854.dgn 01-JUL-2022


TM854

- NOTES:
- An AFAD operator shall be provided for each AFAD. A single operator may not simultaneously operate two AFADs.



2-Lane, 2-Way Roadway
ONE LANE CLOSURE, TWO AFADs

- NOTES:
- The AFAD operator shall not flag traffic and operate an AFAD at the same time.




2-Lane, 2-Way Roadway
ONE LANE CLOSURE, ONE AFAD & ONE FLAGGER

GENERAL NOTES FOR ALL DETAILS:

- Flagger station shall be delineated according to "FLAGGER STATION" detail shown on Standard Drawing TM800
- Bottom of lens housing shall be a minimum of 7 ft. above surface when mounted on shoulder and at least 17 ft. above any portion of the travel lane.
- The gate arm shall cover at least one half of the approaching vehicle travel lane.
- Signing and other TCD installed in conjunction with the work area, shall move with the work area.
- Use 1/3 "L" taper for shoulder closure, where necessary.
- For Taper Length ("L") and Buffer Length ("B") shown on this sheet, use the "MINIMUM LENGTHS TABLE" shown on Drg. No. TM800.
- The AFAD operator shall be a certified flagger who has been trained in the operation of the AFAD in use.
- Operator shall operate AFAD from a designated area. Designated area should maintain visual presence of the AFAD and should be at least 50' away from the AFAD and have an escape route available for the operator.
- Remove existing striping and install temporary striping as required.
- See "TRAFFIC CONTROL DEVICES (TCD) SPACING TABLE" on Drg. TM800 for sign spacing A, B, and C.
- Cover existing passing lane signing (as directed)
- When extended traffic queues develop during AFAD operations, protect traffic by providing advance flaggers(s) and signing according to the "Extended Traffic Queues Detail" shown on Standard Drawing TM850.
- When AFAD is not in use for less than one work shift, turn off AFAD, or switch YELLOW lens to flashing mode, and cover or remove all accompanying signing.
- When AFAD is not in use for longer than one work shift, remove AFAD and all accompanying signing from the roadway.
- Do not use the AFAD to control more than one lane of approaching traffic.
- Use temporary pavement markings or a white portable rumble strip for temporary stop line. Remove temporary stop line when AFAD is no longer in use.
- Tubular markers along centerline placed in advance of AFAD to first sign are optional, unless the DO NOT PASS sign is used.

- Automated Flagger Assistance Device (AFAD)
- 28" Tubular Markers
See TCD spacing table on TM800 for max. spacing.
- UNDER TRAFFIC
- UNDER CONSTRUCTION



OVER-DIMENSIONAL VEHICLE ACCOMMODATION DETAIL

CALC. BOOK NO. _____ SDR DATE _____ 01-JUL-2022 _____

NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications


OREGON STANDARD DRAWINGS

2-LANE, 2-WAY ROADWAYS

2021


DATE	REVISION	DESCRIPTION


The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.




2-Lane, 2-Way Roadway

BRIDGE CONSTRUCTION USING SIGNALS





4-Lane, 2-Way Roadway
BLASTING ZONE



4-Lane, 2-Way Roadway
BLASTING ZONE
(Non-Freeway)

GENERAL NOTES FOR ALL DETAILS:

- Configurations are NOT to be used on freeways. For freeways, a total closure or rolling slowdown should be used for blasting operations, as shown in the plans or directed.
- The signs shall be covered or removed when there are no explosives in the area or when the area is otherwise secure.
- Whenever a side road intersects the roadway between the "BLASTING ZONE AHEAD" (W22-1) sign and the "END BLASTING ZONE" (W22-3) sign, or a side road is within 1000' of any blasting cap, similar signing, as on the mainline, shall be erected on the side road.
- Before blasting, the "Explosives Specialist" shall determine whether highway traffic in the blasting zone will be endangered by the blasting operation. If there is danger, highway traffic shall not be permitted to pass through the blasting zone during blasting operations.

- The "SIGNAL AHEAD" (W3-3a) sign may be substituted with the Signal Ahead (W3-3) symbol sign.
- Do not stop or hold traffic in excess of 20 minutes including rock and debris clean up.
- All offsets between sign pairs in multi-lane sections are 30' with median signs closest to approaching traffic.
- To determine Taper Length "L" and Buffer Length "B" use the "MINIMUM LENGTHS TABLE" on Dwg. No. TM800.
- To determine sign spacing A, B, and C, use "TRAFFIC CONTROL DEVICES (TCD) SPACING TABLE" on Dwg. No. TM800.
- To be accompanied by Dwg. No. TM820, TM821 & TM854.

- Automated Flagging Assistance Device (AFAD)
- 28" Tubular Markers
See TCD Spacing Table on TM800 for max. spacing.
- Temp. Plastic Drums
See TCD Spacing Table on TM800 for max. spacing.
- UNDER TRAFFIC
- UNDER CONSTRUCTION

CALC. BOOK NO. _ _ _ _ N/A _ _ _ _

SDR DATE _ _ _ _ 01-JUL-2022 _ _ _ _

NOTE: All material and workmanship shall be in accordance with the current Oregon Standard Specifications

OREGON STANDARD DRAWINGS

BLASTING ZONES

2021

DATE	REVISION	DESCRIPTION
07/01/22	Added AFADs to the drawing.	

The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer.