

Appendix

H

**DIRECTORY
OF FIGURES
AND TABLES**

DIRECTORY OF FIGURES

| | |
|---|------|
| Figure 2-1: Median Detail: Right In Right Out..... | 2-11 |
| Figure 2-2: Raised Median Detail: Right In Right Out..... | 2-11 |
| Figure 2-3: Vehicle-Pedestrian Conflict | 2-13 |
| Figure 2-4: Pork Chop with Non-Traversable Median..... | 2-14 |
| Figure 2-5: Left Ingress from One Direction Only..... | 2-15 |
| Figure 2-6: Left Ingress from Both Directions | 2-16 |
| Figure 2-7: Example of Frontage Road Locations..... | 2-19 |
| Figure 2-8: U-Turn at Intersection | 2-20 |
| Figure 2-9: U-turn at Midblock | 2-21 |
| | |
| Figure 3-1: Determining Stopping Sight Distance..... | 3-3 |
| Figure 3-2: SSD on Horizontal Curves | 3-7 |
| Figure 3-3: Standard Superelevation..... | 3-13 |
| Figure 3-4: Developing Superelevation on 2-Lane Highways..... | 3-14 |
| Figure 3-5: Developing Superelevation on 2-Lane Highways (Cont'd) | 3-15 |
| Figure 3-6: Examples of Additional Methods for Developing Superelevation..... | 3-16 |
| Figure 3-7: Developing Superelevation on 4-Lane Highways..... | 3-17 |
| Figure 3-8 : SSD Crest Vertical Curve | 3-21 |
| Figure 3-9 : SSD Sag Vertical Curve | 3-22 |
| | |
| Figure 4-1: Rounding of Cutbanks..... | 4-10 |
| Figure 4-2: Full Width Median..... | 4-15 |
| Figure 4-3: Landscaping Accommodation..... | 4-17 |
| Figure 4-4: Median Tree placement..... | 4-19 |
| Figure 4-5: End Treatments..... | 4-21 |
| Figure 4-6: Interstate Clearance Envelopes for Single Lane..... | 4-27 |
| Figure 4-7: Freeway & Highway Clearances..... | 4-28 |
| Figure 4-8: Railroad Clearances | 4-29 |
| Figure 4-9: Concrete Barrier Placement at Bridge Column..... | 4-33 |

| | |
|--|------|
| Figure 4-10: Truck Speed Distance Curve | 4-48 |
| Figure 5-1: Standard Urban Freeway Section (Includes Non-Interstate Facilities)..... | 5-11 |
| Figure 5-2: Standard Freeway Section (Includes Non-Interstate Facilities)..... | 5-12 |
| Figure 6-1: OHP Land Use Designation Overlay | 6-5 |
| Figure 6-2: Expressway Median Widths and Dual Left Turn Lanes | 6-12 |
| Figure 6-3: Positive and Negative Offset | 6-13 |
| Figure 6-4: Typical Special Transportation Area (STA)..... | 6-17 |
| Figure 6-5: Potential Urban Business Area (UBA)..... | 6-29 |
| Figure 6-6: Commercial Center | 6-37 |
| Figure 6-7: Urban Fringe/Suburban Area..... | 6-43 |
| Figure 7-1: Standard Sections For Rural Highways | 7-13 |
| Figure 8-1: Accommodating And Designing For Vehicles..... | 8-4 |
| Figure 8-2: Offset Approaches..... | 8-6 |
| Figure 8-3: Functional Intersection Area | 8-6 |
| Figure 8-4: Throat Distance at Approaches | 8-7 |
| Figure 8-5: Driveway Approaches With Sidewalks | 8-11 |
| Figure 8-6: Driveway Approaches Without Sidewalks | 8-12 |
| Figure 8-7: Sidewalk Ramp Details | 8-13 |
| Figure 8-8: Right Turn Channelization | 8-16 |
| Figure 8-9: Left-Turn Channelization..... | 8-22 |
| Figure 8-10: Reversing Curve Option for Left-Turn Channelization | 8-23 |
| Figure 8-11: Right Turn Acceleration Lane from at Grade Intersection..... | 8-27 |
| Figure 8-12: Median Acceleration Lane - Narrow Median | 8-31 |
| Figure 8-13: Median Acceleration Lane - Wide Median..... | 8-32 |
| Figure 8-14: Left Turn Add Lane | 8-33 |
| Figure 8-15: Typical Multi-Lane Channelized Intersection..... | 8-34 |
| Figure 8-16: Curb Extension | 8-36 |
| Figure 8-17: Skew Angle and Field of View | 8-38 |
| Figure 8-18: Island Geometry | 8-39 |

| | |
|--|------|
| Figure 8-19: Crosswalk Ramp Placement | 8-41 |
| Figure 8-20: Signal Pole Placement..... | 8-42 |
| Figure 8-21: Dual Left Turn Channelization | 8-45 |
| Figure 8-22: Channelization & Intersection Details..... | 8-46 |
| Figure 8-23: Dual Right Turn Channelization..... | 8-48 |
| Figure 8-24: Elements of a Roundabout..... | 8-52 |
| Figure 8-25: Estimated Vehicle Speed and Radius Relationship – Fastest Path..... | 8-60 |
| Figure 8-26: Five Critical Path Radii for Fastest Path Analysis | 8-62 |
| Figure 8-27(a): Fastest Vehicle Path Through a Single Lane Roundabout..... | 8-63 |
| Figure 8-27(b): Fastest Vehicle Path Through a Multi-Lane Roundabout | 8-63 |
| Figure 8-28: Roundabout Cross-Section..... | 8-64 |
| Figure 8-29: Truck Apron Mountable Concrete Curb..... | 8-67 |
| Figure 8-30(a): Typical Truck Apron and Circulating Roadway Cross-Slope | 8-68 |
| Figure 8-30(b): Truck Apron and Crowned Circulating Roadway Cross-Slope..... | 8-69 |
| Figure 8-31: Modified Truck Apron | 8-70 |
| Figure 8-32: Approach Alignment..... | 8-73 |
| Figure 8-33: Angle Between Approaches..... | 8-74 |
| Figure 8-34: Skewed Alignments | 8-75 |
| Figure 8-35: Three Legged Approaches | 8-76 |
| Figure 8-36: Five Approach Roundabout | 8-77 |
| Figure 8-37: Exit Geometry – Alternate Speed Prediction Method..... | 8-79 |
| Figure 8-38(a): Oversize Vehicle Entrance Apron | 8-81 |
| Figure 8-38(b): Swept Path of Oversize Vehicle Using an Entrance Apron..... | 8-82 |
| Figure 8-39: Minimum Splitter Island Dimensions, Single Lane Roundabout | 8-83 |
| Figure 8-40(a): Various Multi-Lane Roundabout Entrance and Exit Options..... | 8-86 |
| Figure 8-40(b): Additional Multi-Lane Roundabout Entrance and Exit Options | 8-87 |
| Figure 8-41: Path Overlap | 8-88 |
| Figure 8-42: Minimizing Path Overlap | 8-89 |
| Figure 8-43(a): WB-67 Entering in the Inside Lane, Using Gore Striping | 8-90 |
| Figure 8-43(b): WB-67 Entering in the Outside Lane, Using Gore Striping..... | 8-91 |
| Figure 8-44: Bike Curb Cut | 8-94 |
| | |
| Figure 9-1: Examples of System Interchange Forms | 9-8 |

| | |
|--|-------|
| Figure 9-2: Common Service Interchange Forms | 9-9 |
| Figure 9-3: Examples of Compact Diamond Interchange Forms | 9-10 |
| Figure 9-4: Directional Ramps with Diamond Interchange Superimposed | 9-11 |
| Figure 9-5: Non-Freeway Interchange Forms | 9-12 |
| Figure 9-6: Examples of Specialized Interchange Forms..... | 9-13 |
| Figure 9-7: Freeway Lane Drops..... | 9-16 |
| Figure 9-8: Minimum Ramp Terminal Spacing | 9-20 |
| Figure 9-9: Discrete Areas of A Typical Ramp..... | 9-23 |
| Figure 9-10: Ramp Types | 9-25 |
| Figure 9-11: Entrance Ramp Details | 9-28 |
| Figure 9-12: Exit Ramp Details..... | 9-29 |
| Figure 9-13: Consecutive Entrance Ramps | 9-30 |
| Figure 9-14: Two-Lane Parallel Entrance Ramp | 9-31 |
| Figure 9-15: Entrance Ramps on Curves..... | 9-34 |
| Figure 9-16: Exit Ramps on Curves | 9-35 |
| Figure 9-17: Interchange Ramp Spread..... | 9-39 |
| Figure 9-18: Detail at Ramp and Crossroad Intersection..... | 9-40 |
| Figure 9-19: Ramp Terminal Curve Design..... | 9-41 |
| Figure 9-20: Maximum I.D.V. Swept Path..... | 9-43 |
| Figure 9-21: Two-Lane Ramp Meter with Taper to One-lane Entrance Ramp..... | 9-45 |
| Figure 9-22: Freeway Ramps Standard Typicals | 9-47 |
| Figure 9-23: Non-Freeway Interchange Ramp Typical Section..... | 9-48 |
| Figure 9-24: Partial Cloverleaf Intersection Detail | 9-50 |
| Figure 9-25: Folded Diamond Terminal Detail..... | 9-51 |
| Figure 9-26: Non-Freeway Interchange | 9-57 |
| Figure 9-27: Non-Freeway Interchange Example And Future Improvements | 9-58 |
| | |
| Figure 12-1: Minimum Bus Pullout Details..... | 12-11 |
| Figure 12-2: Near-Side Bus Stop with Curb | 12-13 |
| Figure 12-3:-Far-Side Bus Stop with Curb | 12-18 |
| Figure 12-4: Fully Developed Bus Stop..... | 12-19 |
| Figure 12-5: Typical Intersection Design for Bus..... | 12-26 |
| Figure 12-6: Conceptual Park and Ride Applications..... | 12-32 |

| | |
|--|-------|
| Figure 13-1: On-Road Bikeway Definition | 13-2 |
| Figure 13-2: Handrail at Bridges and Vertical Drops greater than 5' | 13-13 |
| Figure 13-3: Criteria for Pedestrian Rail At Back Of Walk..... | 13-14 |
| Figure 13-4: Continuous Raised Median versus Cut-Through Crossing Island | 13-19 |
| Figure 13-5: Sight Lines with Curb Extensions..... | 13-20 |
| Figure 13-6: Types of Separated Paths | 13-24 |
| | |
| Figure 16-1: Display of Components with Existing Ground Contours and Triangles | 16-6 |
| Figure 16-2: Sample Template from ODOT Template Library | 16-9 |
| Figure 16-3: Top View of Adjacent Corridors | 16-14 |
| Figure 16-4: Rotated View - Vertical Gap Problem Between Corridors | 16-14 |
| Figure 16-5: Surface Triangulation Error | 16-20 |
| Figure 16-6: Display of 3D Solids..... | 16-21 |
| Figure 16-7: Display of Solids and Roadway Prism | 16-21 |
| Figure 16-8: Index in Spreadsheet..... | 16-23 |
| Figure 16-9: Index Contained in Narrative..... | 16-24 |
| Figure 16-10: Index in HTML Document with Links to Reports..... | 16-24 |
| Figure 16-11: Delete Unused Alignments | 16-25 |
| Figure 16-12: Alignments Displayed in Design File | 16-26 |
| Figure 16-13: Review Active Alignment Report | 16-27 |
| Figure 16-14: LandXML Translator for Alignments..... | 16-28 |
| Figure 16-15: Rotated View of Features and Triangles Displayed in Design File..... | 16-29 |
| Figure 16-16: Index of Surface Names and Locations | 16-30 |
| Figure 16-17: LandXML Translator for Surfaces..... | 16-31 |
| Figure 16-18: Critical Section Choices for Cross Sections..... | 16-32 |
| Figure 16-19: Cross Sections Displayed and Labeled..... | 16-33 |
| Figure 16-20: Cross Section Report Using One of Many Stylesheets | 16-34 |
| Figure 16-21: Create Report When Calculating End-Area Volume..... | 16-35 |
| Figure 16-22: Grid Volume..... | 16-36 |
| Figure 16-23: Stitch Mesh Faces When Displaying Components | 16-37 |
| | |
| Figure M-1: Approximate Durations - Roadway Digital Design Delivery Schedule (Typical) | M-2 |

Figure P-1: Estimated Vehicle Speed and Radius Relationship..... P-1
Figure P-2: Vehicle Path Through a Roundabout - Speed, Radius..... P-3
Figure P-3: Vehicle Path Through a Roundabout Speed,Radius, Acceleration Distance P-4
Figure P-4: Exit Geometry - Comparison Tangential and Small Radius P-8

DIRECTORY OF TABLES

| | |
|---|------|
| Table 1-1: Design Standards Selection Matrix..... | 1-23 |
| Table 3-1: Stopping Sight Distance | 3-4 |
| Table 3-2: Open Road Superelevation & Spiral Lengths | 3-10 |
| Table 3-3: Urban Superelevation & Spiral Lengths | 3-11 |
| Table 3-4: Suburban Superelevation & Spiral Lengths | 3-12 |
| Table 3-5: Comfort Speed..... | 3-19 |
| Table 4-1: Additional Embankment Widening on High Fills | 4-9 |
| Table 4-2: Left Side Shy Distance | 4-15 |
| Table 4-3: Clear Zone Distances | 4-30 |
| Table 4-4: Horizontal Curve Adjustments..... | 4-31 |
| Table 5-1: Median Barrier Systems | 5-7 |
| Table 5-2: ODOT 4R/New Freeway Design Standards Minimums | 5-10 |
| Table 5-3: Maximum Gradient | 5-15 |
| Table 5-4: Interstate Maintenance Design Features..... | 5-17 |
| Table 5-5: Interchange Spacing | 5-26 |
| Table 6-1:ODOT 4R/New Urban Standards – Expressways | 6-15 |
| Table 6-2: ODOT 4R/New Urban Standards – STAs..... | 6-28 |
| Table 6-3: ODOT 4R/New Urban Standards – UBAs..... | 6-36 |
| Table 6-4: ODOT 4R/New Urban Standards – Urban Fringe/Suburban Area | 6-48 |
| Table 6-5: ODOT 4R/New Urban Standards -Traditional Downtown/ Central Business District..... | 6-56 |
| Table 6-6: ODOT 3R Urban Non-Freeway Design Standards | 6-58 |
| Table 6-7: Minimum Useable Bridge Widths | 6-60 |
| Table 6-8: Mandatory 3R Design Features..... | 6-62 |
| Table 6-9: Low-Cost Safety Measures | 6-63 |

| | |
|---|-------|
| Table 6-10: Urban Preservation Design Features..... | 6-65 |
| Table 6-11: Additional Urban Design Features..... | 6-68 |
| Table 7-1: ODOT 4R/New Rural Standards - Expressway | 7-3 |
| Table 7-2: ODOT 4R/New Rural Arterial Design Standards | 7-9 |
| Table 7-3: Minimum 3R Lane and Shoulder Widths..... | 7-21 |
| Table 7-4: Minimum Useable Bridge Widths | 7-22 |
| Table 7-5: Mandatory Design Features | 7-24 |
| Table 7-6: Low-Cost Safety Measures | 7-25 |
| Table 8-1: Typical Private Approach Style and Width | 8-8 |
| Table 8-2: Desirable Length of Full Width Median Acceleration Lane | 8-29 |
| Table 8-3: Speed, Radius Relationship | 8-61 |
| Table 8-4: Inscribed Diameters | 8-65 |
| Table 9-1: Freeway and Non-Freeway Interchange Spacing | 9-2 |
| Table 9-2: Ramp Design Speed..... | 9-26 |
| Table 9-3: Single Lane Ramp Capacity..... | 9-26 |
| Table 9-4: Maximum Degree of Curvature and Sight Distance on Ramps..... | 9-32 |
| Table 9-5: Maximum Grades For Ramps | 9-36 |
| Table 10-1: List of Permits and The Units Responsible..... | 10-34 |
| Table 10-2: 20 Year Design-Mobility Standards (Volume/Capacity [V/C]) Ratio..... | 10-61 |
| Table 10-3: Ideal Daily Capacity | 10-63 |
| Table 10-4: Signalized Intersection Adjustment Factor (FS) | 10-64 |
| Table 10-5: FT (Reduction factor for presence of trucks)..... | 10-64 |
| Table 12-1: Typical Ranges for Bus Stop Spacing Based on Highway Segment Designation.... | 12-4 |
| Table 12-2: Advantages and Disadvantages of Far-side, Near-side and Mid-block Bus Stops | 12-7 |
| Table 12-3: Advantages and Disadvantages of Bus Pullouts..... | 12-9 |
| Table 13-1: 4R Shoulder Widths and Bicycle Accommodations..... | 13-5 |
| Table 13-2: 3R Shoulder Widths..... | 13-6 |

Table 13-3: 4R Sidewalk Widths.....13-11

Table 14-1: Data Needs For Exception Justification14-11

Table 14-2: Design Exception Request Form.....14-14

Table 14-3: Design Exception List.....14-19

Table P-1: Speed, Radius Relationship P-2

Table P-2: Maximum Straight Line Acceleration Performance by Vehicle P-11